

Where ever you are working we won't over stress the installation.

By limiting test over-voltages to 2%, rather than the usual 10-20%, the **NEW MIT400/2** series sets a new standard for insulation testing!

- Insulation testing up to 1000 V and 200 GΩ range
- Single range, faster continuity testing from 0.01 Ω to 1 M Ω
- User variable insulation test voltage from 100V to 1000V
- Test result storage and Bluetooth® downloading
- Rechargeable options for mains and car charging


Search MIT400/2 at RS Online today!

hken.rs-online.com/tct

Megger.

High-performance tools, precision test & measurement devices and great value consumables





With a massive product range, powerful online search and rapid delivery, we've everything you need to get the job done.

See for yourself at

hken.rs-online.com/tct



The biggest brands, the latest technologies, the most exciting innovations.

RS Online has a massive range of high-quality tools and test & measurement devices from brands like Fluke, Megger and Keysight. And our strong links with many of the world's leading manufacturers means we're regularly first to market with new innovations.







COMARK

(LASCAR

digitron

■ GOSSEN METRAWATT **KEYSIGHT**



Test & Measurement

HIOKI

HANNA

₹TT

Castle

Stuart

Megger.

pico

≎FLIR

CHAUVIN'

FLUKE.

ISO-TECH

JUMO

Kestrel

METCAL

 $^{\mathscr{B}}$

DLP

G GREENLEE

(DIDT.

DORMER

CALLEN

LUXO

E A





Contents



Consumables & Safety

Pages 43 - 57



Test & Measurement

Pages 58 - 82

















STANLEY

raaco

C ECLIPSE

PRESSOL

COOPER

GEARWRENCH

ARMSTR NG

KERN

FACTORY





HOZ/JN

BOSCH

Terry

(CK)

Nicholson





Record

























ABUS

Creda

Schneider

BELIMO

CABLOFIL

EMIT

ebmpapst

ABECO

PINET

OXXAN

Teknik

Chemtronics

LEDLENSER

PowerBreaker' PANDUIT

igus





Wolf

southco

PETZL

Weller

C

Richco

ANTEX

PMA

3M E-A-R

EBERLE

F-T-N





Fellowes

Trotector

ERSA

21:...







COOPER

YUASA

CAREL

Dino-Lite

Camloc

EnerSys

ΛBL

MAG LITE







Starrett























Everything you need, all in one place.

With 500,000 products in stock globally, all ready for sameday despatch, RS Online promises you unrivalled choice and availability. So you can find everything you need, all in one place.

Search online at hken.rs-online.com/tct

Please visit RS Website to view the latest prices for all quantities and full terms and conditions

2 INTRODUCTION CONTENTS 3

Search online at hken.rs-online.com/tct

TOOLS & STORAGE

Set, Mechanics Tools, 1/4" Drive, 47 pc

- 42 pc 1/4in ratchet handle, bit & socket set
- Reversible 72 tooth ratchet
- · Ergonomic magnetic bit holder
- Manufactured from Chrome Vanadium with SuperLock





663-588 RS Pro 24 pc VDE/1000V Electricians Tool Kit

Comprehensive Insulated Tool Kit

713-8944 Cooper Tools 47 pc Mechanical Tool Kit

37 Piece Socket & Driver Bit Set Kit Contents

COOPER

- pcs in set: 37
- · Storage case material: Polypropylene
- Metric sockets (mm): 5.5, 6, 7, 8, 9, 10, 12, 13, 14
- Hexagonal bits (mm): 3, 4, 5, 6, 7
- Slotted bits (mm): 4.5, 6.5, 8
- Pozidriy® bits: Pz0. Pz1. Pz2

FACOM)

- Philips® bits: Ph0, Ph1, Ph2
- Tamperproof Torx® bits: Tx10, Tx15, Tx20, Tx25, Tx27, Tx30, Tx40



MPN: CTK47EU

MPN: R.2A

MPN: MET-0450

BAHCO

MPN: 3045V-2

30pcs 1/2in Sq Drive Socket/Spanner

439-1811 Facom 37 pc Mechanical Tool Kit

. A 30-pc socket/spanner set, equivalent to an 88 pc traditional set.

- . Manufactured from high quality chrome vanadium steel, all sockets conform to DIN 3124, ratchets and accessories to DIN 3122 and 3123
- · All tools have a bright polished finish
- Metrinc Metrinch® tools are designed to drive on the hexagon flats, not the corners. This enables one tool to drive metric/AF in. BSW and BSF hexagons. This unique drive system also makes these tools particularly useful for use on old or rounded-off hexagon nuts or bolts
- . This set is supplied complete in a strong/ robust polypropylene storage case



327-5235 Wiha Tools 27 pc ESD Tool Kit

MPN: XX272

HK\$2 736 00

Tool Roll Bag

. Manufactured in accordance with DIN EN 60 900



76pcs Metrinch Socket &Combi Spanner Set

157-1632 Metrinch 30 pc Mechanical Tool Kit

- $\frac{1}{4}$, 3/8 and $\frac{1}{2}$ in. combined socket and combination spanner set, equivalent to a 135 pc traditional set. Manufactured from chrome vandium high quality steel, all sockets conform to DIN 3124, ratchets and accessories to DIN 3122 and 3123
- Metrinch® tools are designed to drive on the hexagon flats, not the corners. This enables one tool to drive Metric and A/F, BSW and BSF fasteners. This unique drive system also makes these tools particularly useful for use on old and rounded off hexagon nuts and bolts
- Set is supplied complete in a heavy duty blow moulded plastic carrying case

479-5718 76 pc Mechanical Tool Kit



MPN: 71A METRINCH HK\$2,162.40 SKT SER

HK\$1,386.00

- Electrician's tool kit, comprising pliers, screwdrivers and voltage tester
- · Screwdriver blades bronzed with chrome vanadium steel, with ergonomic VDE power-grip handle
- Standards EN/IEC 60900:2004



HK\$2.754.00

473-350 RS Pro 7 pc VDE/1000V Electricians Tool Kit

• High quality

Cutters

• VDE approved

Electrically insulated hand tools

· Ideal for fine and delicate work

Diagonal, Wire and Cable

Optimum balance of torque and control

Universal Tool Case 19 pcs

- For work on electrical installations
- A resistant leather briefcase with metallic reinforcements
- 430 x 260 x 160mm



688-0461 Bahco 19 pc VDE/1000V Electricians Tool Kit

Esd Set Pliers/Screwdriver

• 27 pc ESD Tool Set in Carry Case



HK\$8.072.07





457-4072 Knipex 15 pc VDE/1000V Electricians Tool Kit

MPN: 98 99 13

7-piece VDE set

- VDE pliers with inlaid joint
- · Supplied in a plastic case with transparent folding lid





Technicians Tool Kit

- · A professional tool kit consisting of a carefully selected
- range of quality tools in a robust ABS case.
- The kit contains the most common basic tools for an electrical/electronic engineer
- Space is available for further tools which can be bought separately
- The vacuum formed base tray has 4 compartments (50mm deep) for the storage of component parts, aerosols or a test meter



COOPER

228-4301 Cooper Tools 12 pc Electronics Tool Kit 9 Piece Ergo General Purpose Tool Kit

12pcs Service And Repair Tool Kit

A 12 pc kit, ideal for servicing and repairs on PCs.

Supplied complete in a vinyl tool roll

9 pc maintenance kit

331-9379 Bahco 9 pc Electricians Tool Kit

 A kit with carefully selected high quality general purpose tools for the discerning engineer

Professional Tool Kit

· All items have ergonomically designed handles · Cutters and pliers feature a unique return spring



MPN: 9845

HK\$736.59

HK\$1.156.07

663-550 RS Pro 23 pc Technicians Tool Kit

- From Pheonix Contact, this professional tool set consists of a versatile selection of common tools to complete most jobs. The kit is supplied in a robust and lockable tool case with rubber carry straps. Including everything from voltage testers to safety glasses, this is the perfect tool set for both

CONTACT

- A socket set, hex keys, cabinet key and ferrules.
- · A hammer, knife, tape measure, hammer, scriber, and safety glasses.
- · A voltage tester and continuity tester



- The strong, black ABS moulded case
- A removable (empty) tray fits into the lower half of the case with compartments of 450×130; 320×190 and 115×190
- All compartments are 50mm deep



HK\$5,071.00

419-0107 Bahco 17 pc Electricians Tool Kit MPN: 9852 HK\$2.173.30

Engineers Tool kit

 A comprehensive service engineers tool kit containing a range of high quality tools

478-0687 Bahco 62 pc Engineers Tool Kit

General Purpose Tool Kit

· A professional tool kit with carefully selected high quality

general purpose tools for the discerning engineer



Electricians Tool Kit including an ISO-TECH multimeter

- 2.5; 0.5 x 3; 0.8 x 4; 1 x 5.5 mm; Pozidriv 1000 Volt Screwdriver: PZ1; PZ2; PZ3; Phillips 1000 Volt Screwdriver: PH1; PH2; PH3; Side Cutter: 120: 180 mm: 180 mm Combination Plier: 160 mm Snipe Nose Plier; 200 mm Cable Cutter; 225 mm Slip Joint Plier; 300 mm Hacksaw frame; Junior Hacksaw Frame: 8 in Adjustable Wrench: Fibre Glass Claw Hammer: Club Hammer: Floorband Saw (Venner saw); Half Round Second Cut File; Wood Chisel: 16; 20; 25 mm; Arbour: 14 to 30 mm; Holesaw: 20; 25; 32 mm; Multimeter
- Number of Pieces 31



HK\$7.833.43

478-1309 Bahco 31 pc VDE/1000V Electricians Tool Kit



478-0693 Bahco 16 pc Engineers Tool Kit

MPN: 4730

Visit hken.rs-online.com to order today!


Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.


Visit hken.rs-online.com to order today!



HK\$2 590 00











Professional Service Engineers Tool Kit


- Upper and lower, detachable PVC covered boards hold the tools





A professional tool kit designed for electricians,

Mains Tester Screwdriver: Slotted 1000 Volt Screwdriver: 0.4 x



















94 Piece Mechanics Tool Kit

- Large tool kit for automotive work comprising of a comprehensive socket and bit, spanner and precision screwdriver sets.
- Chrome Vanadium construction with Chrome Molybdenum Steel sockets



Hardbottom Toolbag W/Zip, 330X254X178mm

- Durable welded plastic waterproof
- base for added protection
 - Made from tough padded tear resistant polyester Multi-pocketed for assorted tools
 - Completed with heavy duty steel
- zip and clips to avoid any wear and tear Shoulder Stran





734-8889 RS Pro 94 pc Mechanical Tool Kit



Plano Zipper Polyester Tool Bag 330mm x 178mm MPN: 513000

HK\$270.30

Bahco 8 piece Mixed Plier Kit in Modular Foam Insert

- This Modular Foam kit from Bahco offers an 8 pc set of mixed pliers including locking, adjustable, water pump, and combination
- Featuring tools from the ERGO range that are scientifically designed to help prevent musculoskeletal issues



HK\$2,652.59

Facom Rolling Probag

- Textile tool box in highly resistant fabric with rigid, waterproof compartment.
- Aluminium handle with leather trim.
- Cushioned shoulder strap and closure with soft top. Elasticated strap to hold tools in place.
- Easy access to the compartment



BAHCO

898-7365 Bahco 8 pc Tool Kit MPN: FF1F4001

- 12-nc Screwdriver Set
- 5 Slotted drivers 1x35, 1.2x35, 1.5x35 2x35 and 2.5x35

• A range of high quality, ergonomically designed, precision

drivers and cutters, for use within the micro-electrics.

electronic and precision engineering industries

12 Piece Micro-Tech Tool Set

- 2 Phillips drivers No. 00 and No. 0
- 2 Torx driver: T6 and T7
- 3 Hexagon drivers 0.9, 1.3 and 1.5mm



■ FACOM

Facom Zipper Polyester, Polypropylene Tool Bag 550mm x 360mm x 440mm

MPN: BS.R20PB

HK\$1.021.57

Handyline Pss Compact Bag

- Antigrip cloth bag • 2 removable PSS bag
- Shoulder strap
- Handle
- · 2 large side pockets



= FACOM

162-2853 Facom 12 pc Electronics Tool Kit **Micro-Tech Tool Sets**

MPN: MT.RS2



666-2317 GT Line Tool Bag 200mm x 300mm x 100mm

MPN: PSS COMPACT BAG HK\$541.62

Technician'S Rucksack

380mm x 250mm x 420mm



= FACOM

162-2910 Facom 11 pc Electronics Tool Kit

MPN: MT.RS1



CK Zipper Polyester Tool Bag 380mm x 250mm x MPN: MA2631

HK\$622.20

Reinforced PVC Toolbag, 600X250X230mm

- · Includes pockets for storing smaller tools . Twin zips meet on the top of the bag
- Weight 1.6kg



FatMax® Tool Back Pack

- FatMax tool back packs manufactured from tough hard wearing tear resistant material
- Complete with removable dividers which allow the user to separate different tools and for a laptop.
- Features an air mesh shoulder strap and back support system





RS Pro Zipper Nylon Tool Bag 660mm x 250mm x

706-4711 Stanley Zipper Nylon Tool Bag 360mm x 270mm x MPN: 1-95-611

HK\$632.40

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Textile Tool Box

- . Textile tool box in highly resistant fabric with
- rigid, waterproof compartment.
- · Aluminium handle with leather trim
- Cushioned shoulder strap and closure with soft top.
- . Elasticated strap to hold tools in place.
- . Easy access to the compartment, many side pockets



HK\$768.57

Dewalt Tstak Trolley

- · Large 7in wheels for excellent control and maneuverability
- Compact and lightweight with a foldable handle for easy transport and storage
- Front wheels lock to avoid unwanted movement when in transit or loading
- Locking strap makes sure TStak boxes do not mo



= FACOM

787-7504

Bahco Tools At Height Back Pack

Facom Zipper Polyester, Polypropylene Tool Bag 355mm x 225mm x 460mm

MPN: BS.L30PB

- Preofessional tool transportation to help free your hands at height. • Available in two sizes.
- · Foam padded back
- · Adjustable shoulder straps · Quick release attachments
- · Multiple compartments
- Hard wearing
- · External pockets



788-3887 Bahco Polyester Tool Bag 400mm x 300mm x 100mm MPN: **3875-BP1**

- · Waterproof Base
- · Ergonomic Handle
- Inner Divider



813-4987 Dewalt Plastic Folding Tool Case Trolley for DeWalt MPN: DWST1-71196

MPN:TP010

Plastic Power Tool Box, 365X315X125mm

- A black polypropylene power tool case large
- enough for most power tools Includes protective foam interior
- Dimensions: 365 x 315 x 125mm



HK\$1,102.10

Dewalt TOTE/TOOL bag

- Professional range of Dewalt TOTE/TOOL bags

Terry Tool Box Carry Black Polypropylene; Polycarbonate, 365 x 315 x 125mm

- Plastic Tool Box, 210X395X220mm · Robust toolbox made of high impact polypropylene
- · Removable tote trav

Terry

411-4232

- Strong ergonomic handle for comfortable and easy handling
- Padlock eyelet for securing box Dimensions: 395x220x210mm



= FACOM

· Top opening with zipper

· Removable base board

· Separate front pocket

Complete with shoulder strap

793-2746 Dewalt Zipper Nylon Tool Bag 330mm x 500mm x MPN: 1-79-211

829-2910 Facom Zipper Polyester Tool Bag 460mm x 150mm MPN: BS.TLBPB

Maintenance Fabric Tool Bag

- A compact and lightweight versitile tool bag ideal for the storage and transport of tools.
- . Big enough for the safe transportation of tools or even a laptop . External and internal pockets for quick and
- easy access when on the job Robust, sturdy and designed to last and
- survive the rigors of the building site · Shoulder strap for added security


12" Hard Bottom Tool Bag

· Constructed from tough, waterproof Polyeste



raaco Raaco Tool Box General Purpose Polypropylene, 395 MPN: 135207

- 28" Splashproof Toolbox
- All round water seal for ultimate protection of equipment Extra large capacity for maximum volume utility
- Structural Foam for a rigid and sturdy tool box,
- with integrated V Groove for cutting Portable Tote tray designed to carry tools and small parts, yet
- enables large tool storage inside the tool box as it is 34 length
- . Large metal rust proof latches with padlock for locking possibilities





Stanley Tool Box Splash proof Black, Yellow Structural MPN: 1-93-935



Facom Pro Box 20"

HK\$508.72

HK\$800.00

- This tool box for professional use stands
- out in particular for its robustness. Its reinforced polypropylene compartment is
- resistant to impacts and common chemicals. Its hinge with a metal wire is the pledge of its rugged performance and its aluminium ha



788-7205 RS Pro Zipper Polyester Tool Bag 310mm x 200mm

= FACOM

HK\$184.80

Facom Tool Box Carry Polypropylene, 502 x 268 x MPN: BP.P20

HK\$387.83



HK\$155.04

HK\$137.19





20" Fatmax Metal Plastic Toolbox

- Large metal latches with padlock eye for
- rust protection and long life TPR Coated handle - ergonomic and comfortable grip
- . 1 long metal hinge reduces possibility of hinge failure
- · Design allows vertical storage



Hdpe Trolley Case W/Latch, 470X390X347mm

- Manufactured from high impact shock resistant HDPE resin and a thick aluminium extruded frame
- Protruding corneRS Protect handles and latches from damage
- Stackable design
- Ball bearing wheels
- Fitted internally with 2 tool boards and a document pouch



Stanley Tools Tool Box Carry Green; Gray Metal; Plastic, 497 x 295 x 293mm

MPN: 1-95-615

410-2576 GT Line HDPE Tool Case with 2 Tool Boards & Key MPN: TURTLE 350 PEL HK\$3,304.80 Lock, 470 x 390 x 347mm

Cantilever Tool Box 450X215X240mm

- Tubular full length handle
- Sturdy hinged mechanism
- Lacquered finish with Cadium & lead free colour
- · 0.6mm thickness



HK\$400.00

Zipped Large Probag Polyester Tool Case

- External business card pocket Large external zip pocket for documents
- Dimensions: 420 x 320 x 90mm





773-9367

RS Pro Tool Box Cantilever Metal, 450 x 215 x

HK\$540 00

Biomedical Case With Trolley

• A comprehensive tool kit for the professional, containing 155 tools

373-8304 Plano Polyester Tool Case & Zipper Lock, 420 x 320 MPN: PL552T

Ideal for technician



HK\$386 37

Toolboxes

Metal latch, professional quality and strength

Classic Leather Tool Case,

Strong leather tool case with sturdy polypropylene

. Rear wall with 11 loop injection moulded tool holder

side walls and aluminium edge reinforcements Semi-fold-out front wall with 9 tool loops

420X160X250mm

· Large internal loose tool space

- Soft grip handles on 19" and 26" boxes for greater comfort and better grip
- . Tote tray for smaller items
- Integral level storage on 26" box for most 24" levels
- . The image shown is for the 16in. 19in, and 26in, tool boxes, the 12in. tool box has one central latch and is not padlockable



727-2325

Sgos Polypropylene Tool Case & Key; Combination MPN: 4BIOMEDICALTR HK\$9,320.00 Lock, 465 x 352 x 215mm

Steel Storage Box 197X105X38mm

- · Sturdy latches keep the box shut when carrying





HK\$792.75

· Steel shaft constructed

773-9358 RS Pro Steel Tool Case & Latch Lock, 197 x 105 x

HK\$172.50

PARAT

· Front document space

408-8559 Parat Leather Tool Case & Key, Latch Lock, 420 x 250 x 160mm MPN: 5363.000-031

Stanley Tool Box Carry Polypropylene, 489 x 260 x MPN: 1-92-066

Hd Abs Toolcase+ 2 Boards. 485X350X180mm

- Aluminium/ABS ribbed with feet
- · Strong toggle locks, 2 keys supplied
- . Two tool boards with elasticised loops, pockets, soldering iron holder and document wallet
- Base tray with 5 storage boxes
- Internal dimensions: 485 x 350 x 180mm
- Weight: 5.1kg



619-345 RS Pro ABS with Aluminium Frame Tool Case with 2 Tool Boards & Key, Latch Lock, 485 x 350 x 180mm HK\$1,460.00

4Pc Mini Hook And Pick Set

Dual material cushioned handle for user comfort & reduce fatigue



768-7099 Gear Wrench 4 pc Pick Tool Kit MPN: 84040

PELI

• 10 inch sizes

Waterproof Wheeled Equipment Case

- The Peli Storm iM2720 large transit case, engineered for extreme, industrial and military applications. Constructed with HPX high performance resin for a lightweight. watertight case which is virtually indestructible.
- Strong, wide handles for a comfortable, secure grip
- · Smooth, push and pull latches for easy locking and opening
- O-ring sealed for watertight construction
- · Moulded padlockable twin hasps for excellent security and peace of mind In-line ball bearing wheels for a smooth, low friction pull
- Vortex valve for excellent dust and water protection and internal pressure control so you can use and open the case at any altitude without the risk of vacuum locking

811-2081 Peli Storm Storm iM2720, 297 x 625 x 500mm

Bahco File Set 5 Piece, Ergo Handles

. Each set comprises one each hand, half-round, round,

198-5255 Bahco 250mm, 5 pcs Engineers File Set

. Constructed from tool grade steel for strength & durability · Dual material cushioned handles for reduced user fatigue

4Pc Standard Files Set

three-square and half-round rasp, all second cut All files are fitted with ergonomically designed plastic handles for improved grip and resistance to industrial chemical, oils and solvents · Supplied complete with PVC wallet

 Design to rigorous Military standards including MIL standards for water tightness, impact resistance and vibration



Needle File Set

- · Assortment of 12 needle files for finishing work. Their diversity provides the right solution whatever the shape of the work pc.
- Comprises one of each of the following file shapes: pillar, half round, crossing, knife, flat, three-square, square, round, barrette slitting, joint file round edges, half round, cut on back only



Nicholson'

203-4594 CooperTools 160mm, 12 pcs Needle File Set MPN: 0014470602

12 Pcs Needle File Set, 160mm L Cut 2

- Precision files manufactured in accordance with SQS quality management system to ISO9001/EN29001
- Files are manufactured from high-grade chrome steel, hardened to 65 HRC for greater cutting capactiy and prolonged tool life
- 12 assorted Swiss needle files, overall length 160mm, Cut 2 • Contents: Round profile, half round profile, 3 square profile, flat/warding profile, knife profile, oval profile, pillar profile, barrette profile, crossing profile, marking profile, crochet profile and round edge profile





HK\$4,437.95

Vallorbe 160mm Chrome Steel, 12 pcs Needle File MPN: VLA 2483-2

5 Piece Diamond Needle File Set

- · Professional quality files, suitable for use on tungsten carbide, hardened steel 40 HRC and above, ceramics, glass, gold
- High quality file blanks are electro plated with D126 medium cut diamond grit
- Contents: Round profile, half round profile, 3 square profile, square profile and flat/warding profile



381-4846 RS Pro Diamond Coated Steel, 5 pcs Needle File Set

8in Hand File (Ergo Handle) Cut 1,8in Square File (Ergo Handle)

Cut 1,8in Half Round (Ergo Handle) Cut 1,8in Round File (Ergo

Handle) Cut 1,8in Triangular File (Ergo Handle) Cut 2

HK\$1,216,37

768-7092 Gear Wrench 8in, 4 pcs Engineers File Set MPN: 82820

File, Set, 10pcs

HOZ/JN

- The set includes 10 different files: triangle, flat, oval, round, spear, square, ellipse, half-round, sword. And semi-triangle.
- The are packaged in a nylon pouch for ease of use and to protect the filing edges

642-1021 Hozan 160mm, 10 pcs Needle File Set







MPN: K-215

MPN: 1-477-10-2-2

HK\$157.24

710-8782 Bahco 8in, 5 pcs Engineers File Set

5 Piece Ergo File Module

Will fit all Bahco Tool Trolleys

Diamond Needle File Set

- · Very high quality industrial standard needle files coated with diamond grit enabling them to file materials such as tungsten carbide, ceramics, carbon, glass, hardened steels etc.
- File length is 160mm
- Contents: Round profile, half round profile, 3 square profile, square profile, flat/warding profile and hand profile



MPN: EF-1/T8/5



732-145 RS Pro 160mm, 6 pcs Needle File Set

HK\$713.79

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Estwing Claw Hammer, 200z

- A very high quality 20oz (570g) claw hammer constructed from a single pc steel forging giving excellent strength
- The leather handle ensures a good grip and comfort in use



6 Piece Long Pin Punch Set

- Manufactured from Chrome Molybdenum Vanadium steel
- Hardened & tempered
- Induction hardened striking heads
- Sizes 3,4,5,6,7,8 x 175mm



GEDORE

772-4396 Gedore 6 pc Punch Set. 175 mm MPN: 119L HK\$427.50

734-387 Estwing 560g Curved Steel Claw Hammer, 318 mm MPN: E20CRS

Hammer 200G · Series of hammers with steel heads

- hardened with electrical induction.
- The ash joystick has a form that guarantees excellent grip



Drift Punch Set

- · Fach nunch is hardened tempered and ground with a chemically blackened knurled body.
- DIN 6453 standard punch set made of
- chrome molybdenum forged steel. Heat treated to increase the life of the punches.
- Special treatment of the hitting surface to prevent burring and risks to the user.
- Anti-shock handles.
- Anti-rust finish



= FACOM

784-5932 Facom 7 pc Punch Set Anti-Vibration, 140 mm, 150 mm, 190 mm, 200 mm, 210 mm, 216 mm, 230 mm HK\$687.59

717-9254 Bahco 5400g Sledgehammer, 729mm Handle

Small Automatic Centre Punch. 120mm

Two hand operated centre punches which do not require a hammer

to be used. Once positioned and pressed the punches make

an impression to the depth set by a knurled impact adjuster

The tool resets when removed from the workpc

- **Safety Sledge Hammer 5400G** A recoilless safety sledgehammer with a convex
- face. Special heat-treated impact head
- . Flexible face to avoid cracks or chips. Unbreakable rubber grip reinforced by a rigid steel core

205-7783 CK 200g HCS Cross Pein Hammer



Punch & Chisel Set

- · Hardened along full tool length to resist splitting on head . Shanks are individually tempered
- Octagonal section handle
- Head style/type Chisels: 15, 12 & 5mm. Punches: 4, 4 and 3mm



542-3363 RS Pro 6 pc Punch Set

Manufactured from Chrome Molybdenum Vanadium steel

HK\$1,957.00 6 Piece Chisel & Punch Set Metal Case

- · Hardened & tempered
- IInduction hardened striking heads



ECLIPSE

545-389 Eclipse 4 mm Automatic Punch, 120 mm HK\$205.47 MPN: E171RS

5 Piece Anti-Vibration Punch Set

- 5 pc parallel punch set
- Shock absorbent handle Conforms to DIN7225
- · Hardened to 43HRC at head and 58HRC at tip
- · Prevents clipping and gives user maximum safety and comfort



GEDORE 772-4400 Gedore 6 pc Punch Set, 150 mm

HK\$402.90 MPN: 106 D

4 Piece Anti-Vibration Chisel Set

- A 4 pc chisel set which features a unique shock absorbent handle with integral hand guard protection
- Manufactured from a ergonomical, flexible material with special
- gripping qualities, which are unaffected by temperature changes.
- Conforming to DIN7255



297-1869 Facom 4 pc Cold Chisel Set MPN: 263.G

= FACOM

220-0662 Facom 5 pc Punch Set Anti-Vibration, 55 mm MPN: 249.GPB HK\$506 13



MS750 5pcs Set

- . Extra Large Strike Cap for use with hammers at different angles
- Splitproof Acetate Handle for superior durability
- Protouch Over-Mould Grip for added comfort
- Fully Forged Steel Core to better transfer energy from handle to blade
- · Blade Hardened and Tempered



Pipe Flaring & Tube Cutter Set

• Double flaring adaptor 3/16in, 1/4in ,5/16in ,3/8in and 1/2in



879-2990 Irwin 5 pc Steel Wood Chisel Set MPN: 10503421 HK\$780.90

7 Piece Proto Cold Chisel Set

- · Proto chisels are hardened, quenched and tempered to precise specifications for durable, hard tips and cutting edges
- Every Proto chisel has a cutting edge that is hand ground to the exact angle for the best and easiest cut through tough material

Set of 4 wood cutters in a plastic box. The handle is profiled for

a perfect grip, and the blade is in high strength alloy steel.

 Chisels and punches feature modified parabolic struck ends and special heat treatment provides long service life with qualities that resist mushrooming and chipping

264-2410 Stanley 7 pc Cold Chisel Set

Bevel Edge Wood Chisels

• 4 blade sizes offered: 6, 13, 19 and 25 mm.

· Supplied complete with a silicon carbide oilstone



BAHCO

519-816 3/16 -> ½ in Flaring Pipe Cutter MPN: 4480/2-ZD

Compound Action Snips, Straight, L/R.

- Metalmaster Compound Action Snips
- Cuts straight, left or right in light stock Cuts low carbon cold rolled steel
- Non-slip serrated jaws are made of wearresistant molybdenum steel
 - Provides extra service demanded by the compound lever action



COOPER

Cooper Tools 171.45 mm Left; Right Compound Action Snips for Low Carbon Cold Rolled Steel

Lightweight Shear

- · General purpose shears for cutting small wires, metal shim, plastic, card, paper and fabrics
- · Stainless steel blades, one serrated for efficient scissor action
- · Comfortable grip moulded handles with spring return
- Safety catch to lock jaws closed Overall length 190mm



454-7525 CK 4 pc Chrome Vanadium Steel Wood Chisel Set MPN:T1180

Stripping Knife, 5X3in Blade





450-3474 RS Pro 190 mm Shears for Various Materials

- Made from special spring temper carbon steel · Machine ground and polished to a sharp edge



MPN: 86B



205 mm Left, Right Tin Snip Closed position locking system.

- · 2 positions: small hands and large hands
- Maximum opening capacity: 36 mm.
- Dual material grips.
- Suitable for cutting: plastic, packaging straps, sheet metal, nylon, leather, rubber etc





RS Pro Hardwood 125 x 75 mm Putty Knife with Polished Blade

Plastic Conduit Cutter

- A high quality, heavy duty, multi-purpose tool which
- produces quick, clean cuts with the minimum of effort. Ergonomically designed in cast alloy with stainless steel laws
- . Cuts nylon hose, rubber hose, soft cable wire, prefabricated timbers, plastic cable trunking, leather, etc
- Maximum cutting dia 15mm
- · Overall length 210mm, blade length 65mm, weight 310g



= FACOM

COOPER

611-4111 Universal shears - 36 mm opening

HK\$179.16

WISS(R) Right-Cut Compound Action Snip

- WISS-Metalmaster® special hardened snips feature Molybdenum steel blades designed to cut TITANIUM, INCONEL, and STAINLESS STEEL up to 18 gauge.
- Spring action-compound handles for a fast, effortless cut. fitted with Non-Slip vinyl textured handles and safety latch





208-2149 15 mm Cast Allov Pipe Cutter HK\$367.20

Cooper Tools 9.75 in Right Compound Action Snips MPN: M2RS1

HK\$533.70

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

10

Visit hken.rs-online.com to order today!

Stanley Interlock Knife Snap-Off 9mm

- · Metal body for strength
- Quick and easy blade changel, no tools required



Folding Pocket Knife

- Black, epoxy-coated die-cast metal with spring loaded blade
- Blade can be locked securely in the extended position or stored safely in the body
- Supplied with two straight, general purpose, light duty blades

Stanley Folding Pocket Safety Knife with Craftman MPN: 0-10-598

Stanley Retractable Instant Change Trimming Knife MPN: 1-98-456 with Standard Rlade



HK\$68.20

HK\$115.57

Mini Swagger

· Pocket size knife

Black finish


· Frame lock handle design

Stanley Retractable Interlock Safety Knife with 9mm MPN: 0-10-095 Snap-off Blade

Quick Change Knife

232-1977

- · Retractable blade knife with quick & easy front loading, push button blade change - no tools required
- Precision die-cast body for strength & durability,
- bi-material soft panels for comfort & grip
- Intergral string cutting feature operates when blade is safely retracted





#GERBER

763-8062 Gerber 160 mm Lock Knife with Various Features MPN: 22-31-000593

Safety catch and unlocking in two operations for optimum safety

Full Stainless Steel Knife

handle and universal suspension eyelet.

• Knife designed as a tool with one-pc stainless steel

Rapid opening with one hand using the thumbwheel.

Dynagrip Cartridge Knife High quality cutting knives with retractable snap-off blades.

- Excellent cutting power
- 'Click-action' slider indicates when new blade auto-feeds into position
- . Storage for up to six blades
- · Blades available in packs of ten
- · Uses standard 18mm blade



= FACOM

Spare Trapezoid Blade

RS Pro Standard Utility Knife Blades

496-4330 Facom 189 mm Stainless Steel Lock Knife with Various Features

MPN: 840LE

353-4512 Stanley Retractable Cartridge Safety Knife with 18mm MPN: 0-10-480 Snap-off Blade HK\$1.823.20

Utility and Trimming Blades

 Our range of Stanley utility and trimming knife blades fit most standard utility knives, are suitable for many tasks including carpet, vinyl, cartons, cardboard to list just a few



HK\$96.49



541-6646 RS Pro Knife Blade, 1 Blade Segments

484-7522 Stanley 2-11-921 Knife Blade, 1 Blade Segments For Use With General Purpose MPN: 2-11-921

HK\$#N/A

Disposable Knife

- Red injection-moulded polypropylene plastic handle
- Permanent general purpose, light duty straight blade
- . Supplied in threes with plastic blade guards



Strap/Sheet Cutting Knife

- Manufactured from glass reinforced polystyrene
- Designed for cutting thick plastic sheeting, leather,
- box strapping, belting materials etc
- · Head design prevents personal injury Blades available in packs of 10
- Note: Blades on 541-6624 for strapping knife 541-6630



12

184-7872 Craft Knife Set 3 Polypropylene

MPN: 0-10-601

RS Pro Knife Blade, 1 Blade Segments For Use With

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



Automatic Retracting Blade Safety Knife

- Aluminium-bodied safety knife with automatic blade retraction. When cutting, the blade remains outside the body, but when pressure is relaxed the spring loaded blade retracts into the handle
- Supplied with one blade



Extractor Set 12 Pce

- · For extracting screws and studs of medium tensile strength
- Set contains extractor sizes 1-6 plus appropriate HSS drills
- · Complete with plastic case



RS Pro Retractable Automatic Trimming Knife with

HK\$121.00

446-863 RS Pro 12 pc HSS Screw Extractor Set, Plastic Case

Craftsman's Knife Blades

 Spare blades for Folding Pocket Knife and Craftsman's Knife, supplied on a card of 3



12Pc Fatmax Screwdriver Set

Large diameter handles for greater torque

- · Handle moulded directly onto bar for durability & extra long life
- High grade steel bar allows for high torque & reduces the chance of tip breakage
- Anti-slip soft grip handle with a mix of smooth & textured panels



617-2735 Diecast Metal Scalpel Blade MPN: 0-11-221

Trimmer And Alignment Tool Kit (X10)

 Set of 10 tuning screwdrivers ideal for adjusting potentiometers, coils, cores, etc



316-863 Stanley 12 pc Compact Screwdriver Set

MPN: 5-65-426

Screwdriver 1212550

- The tools feature ergonomic two-component safety handles · Large contact surface of blades inside screw head
- Individually tested safety screwdrivers according.
- to DIN EN 60900 (VDE 0682-201)





322-2360 CK Thermoplastic Trimmer Tool Set

MPN:T4857

MPN: IN 19 19

855-6472 Phoenix Contact 200 mm Alloy Steel Screwdriver, MPN: 1212550 Flat 0.6 x 3.5 mm Tip

Screwdriver Bit Socket 1/2in Hex 19mm

- Square drive with ball retaining locking groove
- Knurled grip
- · Vanadium Steel construction with Manganese Phosphate finish



Phillips Ergonomic Screwdriver, No2X100mm

- Insulated screwdrivers with three-component ergonomically designed handles combining a strong core with excellent grip
- Maximum comfort even when used in wet or oily conditions Smoothly rounded shape eliminates pressure points on the hand in use
- High grade vanadium alloy blades fully
- hardened to DIN and ISO standards
- · IEC 60900 compliant



288-7786 Bahco 100 mm Alloy Steel 1000V Screwdriver, Phillips MPN: BE-8620S PH2 Tin

HK\$120.00

7- Piece VDE Screwdriver Set

772-3656 Vanadium Steel 19 mm Hexagon Bit

- · High quality insulated precision micro-driver sets. Available in slotted, crosspoint and Torx ® head types.
- · Ideal for repair/servicing technicians and engineers working
- Manufactured to DIN IEC78 (CO)11, VDE 0680 Part 201//07-83 and IEC900 1987 standards.
- Proof tested to 10000V

GEDORE

- Manufactured from high alloy special steel., Supplied
- in black shockproof storage case. • Comprising slotted and Philips tips
- near electrically energised systems up to 1000V a.c. or 1500V.



RS 4-in-1 Multi-Bit Screwdriver

- · Professional 4 in one multi-blade screwdriver with exchangeable slotted and Phillips bits suitable for most general screwdriving applications.
- Very guick bit changes Strong durable Steel construction for long tool life
- Comfortable handle for extended use





542-3442 RS Pro 7 pc Flectrical Screwdriver Set

573-384 RS Pro Interchangeable Screwdriver, Slotted; Phillips

















HK\$90.30

4-in-1 Pocket Driver

- Non slip textured surface with soft bi-material grip
- Magnetic bits attract and hold small screws
- . S2 Steel for maximium durability · Supplied with 2 double ended bits



Picof, Hex Nut Driver 5/32X60mm

- Chrome Vanadium steel
- Through hardened
- Chrome-plated · PicoFinish handle for rapid rotation
- Ideal for high-precision work with electrotechnical & precision components



Stanley Steel 4 in 1 Pocket Driver; Magnetic Screwdriver, Standard; Phillips 1/8 in, 5/32 in, PH0,

MPN: 66-344M HK\$37.18

Wiha Tools 60 mm Chrome Vanadium Molybdenum Steel Precision Screwdriver, Hexagon Nut 5/32 in Tip 707-3159

7Piece Soft Feel Nut Metric Spinner Set

- Ergonomically designed handle, optimising balance between comfort and torque
- Handles are hard red acetate with soft texture inlay providing a comfortable grip
- . Sizes refer to size of nutspinner not the size of nut
- · Hardened steel heads



13Pc Imperial Allen Ball-Plus Driver Set

 Drivers feature Toughneck[™] ball, designed to be 20% stronger than conventional drivers in order to reduce breakage, and incorporate HEX-Plus® drive profile, allowing up to 20% more torque to be applied while reducing fastener and tool wear





460-1758 RS Pro 7 pc Engineers Nut Driver Set

HK\$369.00

CALLEN

297-1617 Allen 13 pc Screwdriver Set

MPN: IC18RS-N2

Nut Driver Set, 9 Piece, 5 - 12 mm

- Latest innovation utilising GearForce[™] Technology brings a new standard in ratchet drive tools
- Fine tooth reversible ratchet mechanism for proven strength and fine arc
- · Variety of interchangeable shafts and handles allows access to nearly any fastener



Phillips/Crosspointscrewdriver, No2X125mm

- Designed to protect the user during live working, accidental contact or 'flashover' when working on or adjacent to energised systems, and guaranteed up to 1000V
- Insulation tested to a minimum of 10kV. 50 Hz for 3 minutes



Three-component handle

509-9415 Gear Wrench 9 pc Interchangeable Screwdriver Set MPN: 8909D

• Designed using a comprehensive 11-point ergonomic programme

Flexible Blade Nut Spinner, 7mm

Soft, high-friction material for optimum torque & comfort

395 Ho Nutdriver Hollow 1/2 X 80 Hollow shaft (HO) enabling seized or long threaded screws to be tightened or removed

. Soft zones for extra grip and pressure with optimal

contact zones resulting in increased torque transfer Hard zones designed for full hand contact when

· Rounded shape - no pressure areas on the hand

· High grade chrome plated vanadium blades

FACTORY

815-559 Sibille 125 mm Insulated Screwdriver, Phillips; Crosspoint PH2 Tip

Micro-Tech Philips Tip Driver, No.00X35mm

- Handles have revolving ends and colour coded Blades are chromed with burnished tips





HK\$125.97

HK\$53.95

Bahco 150 mm Alloy Steel Ergonomic Screwdriver, MPN: BE-7607 Hexagon Nut 7 mm Tip

104-4168 Facom 35 mm Bi-metal Precision Screwdriver, Phillips MPN: AEFP.00X35 PH00 Tip

Phillips Screwdriver, No.1X75mm

Phillips, Chrome Molybdenum Vanadium Steel Blade



Wera

driving for fast friction free working

· Hexagon shoulder to avoid rolling

875-9090 Wera 80 mm Electrical Nut Driver, Nut Spinner ½ MPN: 05029507001 in Tin

RS Pro 75 mm Chrome Vanadium Steel Ergonomic Screwdriver, Phillips PH1 Tip

HK\$30.10

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Phillips(Tm) Screwdriver, Ph

- No.2X100mm . Three-component handle
- · Soft, high-friction material for optimum torque & comfor
- High grade vanadium · Polished and chrome plated
- Hardened to DIN and ISO standards



10 Piece Insulated Screwdriver Set

- Insulated 1000V VDE screwdrivers with TPR grip and
- polypropylene injected shafts and handles
- Silicone Chrome Molybdenum Vanadium Steel blades with black finish
- Heat treated to HRC: 55 59
- Supplied complete with zip case



Stanley 200 mm Chrome Vanadium Steel Parallel Screwdriver, Phillips PH4Tip

Bahco 100 mm Alloy Steel Ergonomic Screwdriver, MPN: BE-8620

253-015 RS Pro 10 pc Insulated Screwdriver Set

Screwdriver Philips Bulk Ph4 X 200mm

- High grade steel bar allows for high torque & reduces the chance of tip breakage
- Flared style handle with anti-slip soft grip
- for excellent comfort & grip
- Pinched waist for detailed precision adjustment

Electricians S'Driver 2, 5X60

Flange design to stop hand from slipping

. Injection moulded handles bonded to core

Extremely tough Chrome Alloy Steel blade

Smooth domed end for spinning action, speed & comfor



MPN: 1-65-317

Pozidriv(Tm) Screwdriver, No.1X75mm

- Three-component handle
- . Soft, high-friction material for optimum torque & comfort
- · High grade vanadium
- · Polished and chrome plated
- Hardened to DIN and ISO standards



BAHCO

HK\$109.98

HK\$44.39

264-2599 Bahco 75 mm Alloy Steel Ergonomic Screwdriver, MPN: BE-8810 Pozidriv PZ1 Tip

Wera Chrome Molybdenum Steel Double Ended Offset Screwdriver, Supadriv; Pozidriv PZ1, PZ2 Tip

HK\$92.19

Supadriv/Pozidriv(Tm) Offset Screwdriver

- Double ended design at 90° & 180°
- Black handle for extra grip

Wera

548-029



MPN: 05017305001 919 PZ Gr. 1 + 2

Chrome Plated black tips

665-8529

STAHLWILLE 60 mm Alloy Steel Electricians

FatMax® XL 1000V VDE Insulated

- **Screwdrivers** Slotted 5.5 mm Tip
- Offer maximum comfort & grip, to enable extra torque & less effort when driving screws. Each style is colour coded for immediate identification.
- . 1000V VDE tested for safety in live working situations
- . Flared style handle with anti-slip soft grip
- for excellent comfort & grip
- High grade steel bar allows for high torque & reduces the chance of tip breakage



Screwdriver Pozi Bulk Pz2 X 30mm High grade steel bar allows for high torque &

- reduces the chance of tip breakage Flared style handle with anti-slip soft grip
- for excellent comfort & grip Pinched waist for detailed precision adjustment Smooth domed end for spinning action, speed & comfort



STANLEY

Stanley 150 mm Chrome Vanadium Steel Insulated MPN: 1-65-413 Screwdriver. Slotted 5.5 mm Tip

Insul Supadriv(Tm) Screwdriver, No1X100mm Designed to protect the user during live working, accidental

contact or 'flashover' when working on or adjacent to energised systems, and guaranteed up to 1000V Insulation tested to a minimum of 10kV, 50 Hz for 3 minutes



Stanley 30 mm Chrome Vanadium Steel Stubby Screwdriver, Pozidriv PZ2 Tip

FACTORY

621-354

Sibille 100 mm Insulated Screwdriver, Pozidriv; Supadriv PZ1 Tip

MPN: IP18RS-N1

HK\$118.00

HK\$72.80


Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.





Tvis Protwist Pz 2X125

- AND/AWD screwdrivers for Pozidriv® head screws.
- Matt chromed blade, black treated head.
- AND: extra-long round blade for accessing
- difficult and hard-to-reach areas.





8 Piece Torx Key Set

- 8 pc torx key set supplied in a compact plastic holder.
- Long arm design
- Black finish
- Size marked on plastic sleeve for quick identification

Screwdriver Tamperproof Torx

High grade steel bar allows for high torque &

reduces the chance of tip breakage Flared style handle with anti-slip soft grip

 Pinched waist for detailed precision adjustment Smooth domed end for spinning action, speed & comfort

Hanging hole on holder for easy storage or hanging on a LANyard



= FACOM

418-852

Facom 125 mm Silicon Carbide Steel Protwist Screwdriver, Pozidriv PZ2 Tip

MPN: AND2X125

HK\$74.16

FACOM)

Tt10X75mm

762-1538 Facom 8 pc T10, T15, T20, T25, T27, T30, T40, T45 L MPN: 89S.JP8A Shape I ong Arm Torx Kay Sat

HK\$565.16

Torx(R) Ergonomic Screwdriver, Tx20

- Three-component handle
- Soft, high-friction material for optimum torque & comfort
- High grade chrome plated vanadium
- · Fully hardened to DIN and ISO standards



STANLEY.

for excellent comfort & grip

665-8545 Stanley 75 mm Chrome Vanadium Steel Tamperproof MPN: 1-65-340 Screwdriver. Torx TT10 Tip

Precision Torx Screwdriver T6X60mm

Bahco 100 mm Alloy Steel Ergonomic Screwdriver, MPN: BE-8920 Torx T20 Tip

Blades made from high grade Chrome-vanadium steel

18-pcs Torx Driver And L Key Set

Manufactured from high grade chrome vanadium steel, set

drivers, supplied in a blow-moulded plastic storage case

comprises 9 TORX® screwdrivers and 9 'L'-shaped TORX key

- · Rotating cap allows user to drive easily and adjust precisely
- Tri-lode shape of handle provides comfortable grip during rotation



HK\$58.05

28 Piece Interchangeable Screwdriver Set

• Set contains one chuck type handle with SWIVELTOP™ and 27 interchangeable blades





264-2836

RS Pro 60 mm Chrome Vanadium Steel Precision Screwdriver. Torx T6 Tip

RS Pro 18 pc T8; T9; T10; T15; T20; T25; T27; T30; T40; 8; 9; 10; 15; 20; 25; 27; 30; 40 L Shape Torx Key Set

(CK)

157-1604 28 pc Interchangeable Screwdriver Set

MPN: B1571604

HK\$489.46

HK\$230.81

Xcelite Mini-Driver Set

- . The M60V is a miniaturised convertible screwdriver set comprising jewellers type slotted and Philips screwdriver blades, 22mm long, moulded in colour coded handles
- The set contains a black torque amplifier handle



Xcelite

314-2731 Cooper Tools 6 pc Compact Screwdriver Set

MPN: M60

6 Piece Slotted/Phillips Screwdriver Set

- Ergonomic design with a three component handle to
- reduce user fatigue over extended periods of use Colour coded ends and ring for quick identification
- of the right tool even in a busy tool box
- · Specially designed handle grip to provide secure
- handling even with oily greasy hands
- Chrome plated with Black Oxide tips for durability and long tool life



264-3126 Bahco 6 pc Engineers Screwdriver Set

MPN: BE-9881

HK\$432.60

Watchmakers Screwdrivers

· High quality miniature screwdriver set with burnished hardened steel shafts, chrome finish bodies, with revolving heads and colour coded for ease of identification



Lindstrom Adj Torque Driver, 40-200Ncm

- Micro-adjustable torque screwdriver
- Window scale and precise, positive locking, pullout adjustment knob
- Stainless steel ¼" hexagon driver for all standard drive bits
- . Spring-loaded high -security bit holder for convenience and safety
- Model MA500-1 Works



= FACOM

205-5103 Facom 6 pc Precision Screwdriver Set

45 Piece Precision Screwdriver Bit Set

 Precision screwdriver set containing popular sizes supplied in a zip pouch



MPN: HB.2B

>LINDSTROM

385-1794 Lindstrom ¼ in Hex Adjustable Torque Driver, 40 -> MPN: MA 500-2 HK\$1,826.00

Pre-Settable Torque Drivers

- Bi-directional mechanism signals when torque has been achieved
- Precision radial ball clutch and cam design
- End cap protects the pre-set mechanism and prevents tampering





· Phosphate black finish

Soft grip handle

668-5723 RS Pro 45 pc Precision Screwdriver Set

• 1000V set cotaining popular sizes of Slotted and Phillips

screwdrivers containing in a zipper wallet.

• Blades constructed from Chrome-Molybdenum Steel

6 Piece Insulated VDE Screwdriver Set

HK\$352.00

HK\$319.82

603-592

RS Pro ¼ in Hex Pre Settable, Minor Torque Driver, 2 → 135Ncm

Quickset Drivers

- · Calibrated 'micrometer' style vernier scales
- Torque value easily set using the ribbed adjusting collar Precision radial ball clutch and cam design
- Bi-directional mechanism signals when
- set torque has been achieved



HK\$737.00



668-5871 RS Pro 6 pc Insulated Screwdriver Set

Bahco Precision Screwdriver Set · Precision screwdrivers are ideal hand tools to use on small, intricate devices like watches, calculators and mobile phones.

- It sometimes referred to as the jewel screwdriver. Ideal for small, intricate devices
- Comes in a handy plastic hanging case
- · Varied set options available





RS Pro ¼ in Hex Quickset, Minor Torque Driver, 20 → 120Ncm

Bit length: 75 mm

Security Bit Set 32-pcs Long 32-pc set in sturdy plastic insert box Hardness: 60 HRC

396-6111 32 pc Chrome Vanadium Steel Driver Bit Set



MPN: 560-201

HK\$1,460.00

BAHCO

876-6278 Bahco 24 pc Precision Screwdriver Set

Ergonomic Slip Joint Pliers Self locking jaws, grip tightly at 3 points

- Push button adjuster
- Ergonomic non slip handle Long narrow jaws ISO 8976; DIN 8976

418-9315









Bahco 210 mm Single Thumb Button Water Pump Pliers Ergonomic Slip Joint with 37mm Jaw Capacity

MPN: 8223

MPN: 706-5

HK\$293.55

HK\$1.642.00

Visit hken.rs-online.com to order today! Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



8 Pce Protwist Set, Slotted, Ph, Pozi

- · Round blade screwdriver set with precision machined tips
- Hardened and tempered silicone carbon steel blades for strength and endurance
- Colour and icon coded for fast tip recognition

'Bahco' Precision Pliers

· All types incorporate return springs

· Very high quality pliers for precision work

 Multi material polyamide and polyurethane handles designed for intensive



8" Push Button T&G Pliers

- Double the number of jaw positions for increased
- flexibility and gripping comfort 8 in, 10 in or 12 in versions available
- Forged Chrome-Vanadium Steel for strength and durability
- Anti-rust coating for longer life
- Easy clean dipped grips
- Meets or exceeds ASME performance requirements



= FACOM

519-692 Facom 8 pc Engineers Screwdriver Set

GEARWRENCH

913-9337 Gear Wrench Push Button Slip Joint Pliers MPN: 82158

418-6271 RS Pro 3 pc Plier Set

HK\$885.80

4 Piece Ergonomic Pliers Set

- · Cutters and pliers with ergonomic non-slip hand grips · Optimum comfort in use and application of the
- greatest possible force with the least effort Combination Pliers 180 mm
- Side Cutters 160mm
- Snipe nose pliers 160mm Slip joint pliers 250mm





544-409 Bahco 130 mm Long Nose Pliers

MPN: 40993RS

BAHCO

Ultra flush 120mm side cutters

Semi flush 125mm side cutters • 130mm short plain jaw flat nose pliers · 140mm long plain jaw long nose pliers

305-7419 Bahco 4 pc Plier Set

4 Piece Set Of Technicline Pliers

TECHNICline range. Supplied in a zipped ESD case

ESD safe 4 pc precision plier and cutter set from Bernstein's

MPN: 9897

MPN: 3-970

MPN: 10505483

· Solid style, forged construction with polished head

Internal, Straight, Circlip Pliers, 19-60mm

- · Non-slip, solid tips
- Chrome Vanadium electric steel, oil-hardened and tempered PVC plastic-coated handles



HK\$367.71





strength and corrosion resistance

spring for excellent jaw pressure

• Nickel Plated Vanadium Steel construction for

Adjustment screw and quick release lever with

Forged and tempered jaws with welded upper jaw for a firm hold

Grip Wrench 12

Knipex 180 mm Chrome Vanadium Steel Circlip Pliers MPN: 44 11 J2 with Straight Tip, Internal, Range 19 -> 60 mm

BERNSTEIN

834-8013 Bernstein 4 pc Chrome Vanadium Steel Plier Set

Propliers 3pcs Set

- Chromium nickel steel for improved durability Moulded one component handle



HK\$1,849.60

GEDORE

847-8101

Gedore 300 mm Vanadium Steel Locking Pliers with MPN: 137 12 Maximum of 45mm Jaw Capacity

Short Nose Lock Grip Pliers Multi

- Serrated parallel jaws for excellent grip
- . Multi position slip joint system . Thumbwheel fine jaw adjustment
- Jaw locking trigger to avoid accidental opening
- Knurled grip for frim holding
- Chrome finish



HK\$507.01

Circlip Pliers

Converts easily for external or internal use on snap rings Unique push-button feature allows for effortless change

879-3084 Irwin 3 pc Chrome Nickel Steel Plier Set

- Tool comes with heavy duty cushion grip handles to provide
- comfort and broached jaws for tip control and stability



■ FACOM

876-5193

18

Facom 225 mm Chrome Molybdenum Steel Locking MPN: 500APB Pliers with 40 (Square) mm, 50 (Hexagonal) mm, 50 (Round) mm Jaw Capacity

182-436

RS Pro Tough Steel Circlip Pliers with Straight Tip,

HK\$225.50

HK\$336.60

Visit hken.rs-online.com to order today!

3 Piece Vise Grip(R) Locking Plier Set

- Consists of 5" and 10" locking pliers with wire cutter, plus 6" long nose locking plier
- · Guarded release mechanism is an important safety feature - helps keep work safe and secure
- Supplied in plastic tool roll pouch



HK\$527.50

Side Cutter 160 mm

- For use with medium hard wire
- Oil hardened
- Induction hardened cutting edges to 63 65 HRC
- · Chrome plated finish
- · Bi-component handles for firm, comfortable grip



MPN: 360C

Convertible Circlip Plier Set

- Available as a 4 pc set, these pliers have a patented quickchange design for use on internal and external circlip rings.
- · All tips are precision formed, and induction hardened Pliers are fitted with return springs to reduce fatigue
- US Federal Spec: GGG-P-00480D and ANSI Standard B107.19-198



GEDORE

772-4144 Gedore Cutter MPN: 8314-160 JC HK\$245.00

4 Piece Mechanics Plier Set

- · Ergonomic set of bi-material pliers offering high performance at realistic cost
- Extended contact area and asymmetric handle profile
- fit naturally in hand, improving comfort and power Spring wedges the handles between fingers, for comfort and accuracy



297-1516 Stanley 4 pc Plier Set

RS ESD pliers

- · Range of ESD electronic pliers manufactured
- to exacting Din standards. . ESD Protected for conducting away static electricity
- All pliers are of box joint design Manufactured from high grade steel
- · Smooth non serrated jaw Made in Germany
- Standards: DIN ISO9655



FACOM) **452-9612** Facom 4 pc Plier Set

- **RS 3 Piece Steel Plier Set** . Manufactured from drop forged steel
- · Induction hardened laws
- Ergonomic handles



MPN: CPE.1

161-063 RS Pro ESD 120 mm Steel Flat Nose Pliers

3 piece General Purpose Set

- Ideal for live working
- VDE approved
- · Two component comfort grip handle





HK\$220.00

623-6407 RS Pro 3 pc Steel Plier Set

Ergonomic Slip Joint Plier, 315mm L

- Self locking jaws, grip tightly at 3 points
- Push button adjuster Ergonomic non slip handle
- Long narrow jaws ISO 8976; DIN 8976

BAHCO

734-264



HK\$285.00

HK\$489.25

161-158 RS Pro 3 pc Steel Plier Set

- **Ergonomic Pliers** · High quality pliers with ergonomically designed non-slip
- hand grips which allow increased access into tight areas These products also feature a unique return spring which has an on/ off function allowing the option of having an approximate 15° return
- Also available in a set
- Manufactured to ISO 5745

BAHCO

184-7692




MPN: 2430 G-160 IP





HK\$216.30

Safety Wire Twisting Pliers

- Designed for use on safety wire used within the aviation industry and other applications where vibration may cause fasteners to back out
- Heat treated cutting edges for cutting
- tough stainless steel safety wire Flat top diamond serrations on jaws hold









297-2648 Stanley Cutter 228 mm

Bahco 315 mm Single Thumb Button Water Pump Pliers Ergonomic Slip Joint with 55mm Jaw Capacity



MPN: 196

HK\$1,132,20

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Bahco 160 mm Alloy Steel Long Nose Pliers with 50mm Jaw Length



Metrinch(R) Deep Wall Impact Socket

- Fits the majority of metric and imperial hexagon sizes
- · Protects new hexagons and turns old, rounded ones efficiently
- . Equal to a standard 42 pc traditional set · Fast selection fewer sockets needed



37pcs 1/4in Drive Metrinch(R) Socket

- Equivalent to a 53 pc traditional socket set and fits the majority of metric/imperial hex, sizes
- Faster selection, fewer tools required
- Reversible ratchet has 50-teeth gear • Made from chrome vanadium steel with a bright chrome finish



157-1806 Metrinch MET-2450 15 pc Deep Socket Set ½ in MPN: MET-2450

HK\$1,300.00

Metrinch MET-0325 37 pc Socket Set ¼ in Square

MPN: MET-0325 HK\$720.00

9pcs Metrinch(R) Vde Insulated Skt Set

- Drive Size ½ in
- ½ in. Metric Socket 10, 13, 14, 16, 17, 19, 20/21mm
- · Extension 125mm screw lock extension
- In FemaleTo in Male Socket Adaptor



53 Piece Ratchet Socket Set

- . Comes with High Density Polythene (HDPE) case
- · Matt chrome finish
- Comes with extension bar and adapters





231-7912 RS Pro 9 pc Insulated Socket set ½ in Square Drive

HK\$3,500.00

20pcs 1/2in Sq Drive Ratchet & Skt Set

- 17 sockets: 8/10/11/12/13/14/16/17/18/19/21/22/23/24/27/30 and 32 mm
- 1 1/2" ratchet
- One 250 mm extension and one articulated socket adaptor
- Weight: 3.95kg



Bahco S530T 53 pc Ratchet Socket Set ½ in, ¼ in, MPN: S530T 3/8 in Square Drive

HK\$2,289.69

27 Piece 1/4in Socket Set

- Metric Hexagon Sockets: 3.2; 4; 5; 5,5; 6; 7; 8; 9; 10; 11; 12; 13mm
- Imperial Hexagon Sockets: 3/16; 7/32; 1/4; 9/32; 5/16: 11/32: 3/8: 13/32: 7/16: 1/2: 9/16"
- Extension bars 55 and 150mm
- · Spinner handle
- Universal joint



■ EBCOM

329-7594 Facom S.6 20 pc Ratchet Socket Set ½ in Square MPN: S.6

HK\$1,427.07

40 Piece Bahco 1/2in Drive Socket Set

- Sockets have Dynamic Drive for higher efficiency & maximum grip
- Reversible ratchet with quick release button Practical dispenser for combination spanners
- · Supplied in robust polypropylene case



= FACOM

769-1795 Facom R.420MU 28 pc Socket Set ¼ in Square Drive MPN: R.420MU

51Pc 1/4in Drive 12 Point Socket Set

- Serration inside socket as deep as fastener for a sturdy grip
- Entry angle guides fastener into socket for an excellent fit
- Size stamped on sockets for quick & easy indentification
- Surface drive on sockets provides stronger grip & reduces fastener rounding



358-2230 Bahco S-400 40 pc Socket Set ½ in Square Drive MPN: S-400

Drive, Socketrail, Set, 10Piece

• To find a similar product, based on selected attributes, click the green button

- Drive Size ¼ in
- Set Type Socket and Wrench Set Drive Type Square
- Number of pcs 13





768-6991

Gear Wrench 80301 51 pc Socket Set ¼ in Square MPN: 80301

HK\$1,490.08

HOZ/JN

20

Hozan W-510 13 pc Socket & Wrench Set ¼ in

MPN: W-510

HK\$264.48



Socket Set 1/4ln+1/2in 50 Piece 4-30

- Square drive construction with ball retaining locking groove
- · Knurled grip
- Manufactured from Chrome Vanadium steel



24 Piece Socket Set

- Sockets have Dynamic Drive for higher efficiency and maximum
- grip. Reversible ratchet with quick release button., Contents:
- 18 $\frac{1}{2}$ " Hexagonal Dynamic Drive sockets 10, 11, 12, 13, 14, 15, 16,17,18, 19, 20, 21, 22, 23, 24, 27, 30 and 32mm
- 1/2 " Extension bars 125 and 250mm
- ½ " Universal joint
- ½ " T-joint
- ½ " Breaker bar 250mm
- 1/2 " Ratchet 1/2 " Ratchet



GEDORE

Made in the USA

Gedore 19 V20U-10 50 pc Socket Set ½ in, ¼ in Square Drive 772-4104

Stanley Proto in.Sq Drive Socket Sets

Proto hand sockets incorporate the TorquePlus™ driving system.

rounding. This characteristic meets aerospace specifications, and all metric sockets conform to ANSI B107.7 specifications. All Proto sockets are made from special alloy steel that permits a high strength, thin wall design, for use on fasteners that are extremely close to obstructions. Four internal detents on the drive end provide positive engagement to the drive tool

This allows the socket to contact the fastener away from the corner

while dispersing stresses over a larger area. This feature allows up

to 15% more torque to be applied, whilst reducing the risk of corner

MPN: 19 V20U-10

HK\$5,310.00

361-3132 Bahco S-240 24 pc Socket Set ½ in Square Drive

- 72 teeth Micro-Tough® ratchet gives 5° arc swing
- Supplied in polypropylene case



420-6000 Stanley 2-85-582 17 pc Ratchet Socket Set ¼ in

MPN: 2-85-582

MPN: S-240

- Square drive socket and bit set, housed in a steel storage case. • "Sure Drive" system ensures grip on the flats of the
- sockets and eliminates rounding-off at high torque
- Slim head pushbutton release ratchet with 45 teeth giving 8° minimum movement arc



3/8in Socket Sets

efficiency and maximum grip

. Supplied in polypropylene case

· Sockets have Dynamic Drive for higher

Reversible ratchet with quick release button

337-3957 Bahco S-330 34 pc Socket Set ¼ in, 3/8 in Square MPN: S-330

264-2246 Stanley 47203 11 pc Deep Socket Set ¼ in Square MPN: 47203

- · A square drive socket and bit set, housed
- in moulded plastic storage case. Sockets have Dynamic Drive for higher

46 Piece Socket Set

- efficiency and maximum grip. A reversible ratchet with quick release button The set includes " compact spinner disc, 150 mm long flexible
- extension bar and 1.5 mm, 2 mm and 2.5mm hexagon wrenches. Supplied in robust polypropylene case



38 Piece Ultra compact Ratchet Set

- Ultra compact set easy to carry with immediate tool selection (pictograms of screw head patterns)
- 1/4" drive spinner
- · Self-closing, metal catch



358-1265 Bahco S-460 46 pc Socket Set ¼ in Square Drive

Bahco 94 Piece Socket & Tool Set . A comprehensive 94 pc tool set from Bahco featuring a wide

- selection of sockets and power tool bits plus accessories complimented by two high quality spanner sets. · Ideal set for automotive mechanics with a large choice
- of sockets including a 21mm spark plug socket . Supplied in a impact resistant fitted case with
- strong metal latches for a secure fit . Built in carry handle for easy transportation



- Professional hex socket set with ¼in drive and a hard wearing high density polythene case.
- Alloy steel construction
- · Quick release socket ratchet
- Standards: ISO 1174; DIN 3120



Bahco S87-7 94 pc Socket Set ½ in, ¼ in Square

Visit hken.rs-online.com to order today!

MPN: S87-7



763-0816 Bahco S290 29 pc Socket Set ¼ in Square Drive

Visit hken.rs-online.com to order today!

HK\$977.06

HK\$472.00

HK\$425.00

HK\$1,391.58

BAHCO



17 Piece 1/4" Drive Socket Set Stanley

- Sockets have Maxi-Drive® system for increased grip
- Bi-material handles for improved grip



- **RS 39 Piece Socket Set**
- Forged chrome vanadium steel, sockets are satin chrome plated







- Rotating handle ratchet ¼"
- Metal hinge rod






722-7160

Facom R.360NANO 38 pc Ratchet Set ¼ in Square MPN: R.360NANO












21

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Facom 21 Piece Telescopic Socket Set

- Professional tool set with an extendable ratchet handle that has a dustproof head, strong handle and solid trigger.
- Cost saving
- · 8 position ball mechanism extension
- · Powerful, more torque with less effort
- · Head resists all dusts and liquids
- Compact size with high precision
- Strong and easy to use
- Set includes 8 to 32 mm sockets, 130 mm and





MPN: SXL.DBOX1PB

57Pc 3/8in Drive 12 Point Socket Set

- Serration inside socket as deep as fastener for a sturdy grip
- Entry angle guides fastener into socket for an excellent fit Size stamped on sockets for quick & easy indentification



= FACOM

800-4277 Facom SXL.DBOX1PB 21 pc Extendable Ratchet

- 1/2" Square Drive 9 Piece Socket Set • Sizes, 8,10,13,16,17,18,19,21,24mm
- Sockets have O-ring and pin fixing for securing to drive
- Supplied in a tough injection moulded case



HK\$1.855.27

768-7005 Gear Wrench 80551 57 pc Socket Set 3/8 in Square MPN: 80551

HK\$1.750.25

Socket Adaptor Set

- Includes 3 chrome vanadium hand socket adaptors manufactured to FED spec GGG-W-641e and ANSI spec B107.10M
- Includes 3 black oxide impact sockets

40 Piece Flexible Head Ratchet Set

Durable high grade Steel construction

handling and reduced user fatigue

Ergonomical, soft grip handle for comfortable

· 2 extensions and compact bit set makes this an ideal all-in-one set for any job

Professsional, high quality flexible head ratchet wrench with

forward and reverse direction. Suppplied in a compact storage case.

RS_Pro 40 pc Flexible Head Ratchet Socket Set 3/8

Supplied on socket rail clip



297-1500 Stanley 6 pc Imperial Combination Spanner Set MPN: 52006 HK\$704.48

848-3652 Makita D-41517 9 pc Socket Set ½ in Square Drive MPN: D-41517

RS 46 Piece Screwdriver & Socket Set

- A " square drive socket and bit set housed. in moulded plastic storage case.
- High torque reversible ratchet drive with magnetic shaft, fitted with cushion grip handle and internal bit storage compartment
- · All bits and sockets are manufactured from high grade alloy steel with rust resistant finish and are supplied in removable plastic clips to prevent loss
- ¼ in square drive adaptor

c/w Accessories, Tray



22

RS Pro 46 pc Square Drive Socket Set 1/4 in Square

140pc Square Drive Hex Sockets & Bits

Contents: ¼" drive metric (mm) Sockets (6pt) 4, 5, 5.5, 6, 7, 8, 9,

3/16 . 7/32 . 1/4. 9/32. 5/16 . 11/32 . 3/8. 7/16. 1/2 and 9/16 .1/4" drive

. 11/32 . 3/8. 7/16 and 1/2 .3/8" drive metric (mm) Sockets (6pt)

10, 11, 12, 13, and 14,1/4" drive imperial (inch) Sockets (6pt) 5/32,

metric (mm) Deep Sockets (6pt) 4, 5, 6, 7, 8, 10, 11, 12 and 13,1/4"

drive imperial (inch) Deep Sockets (6pt) 3/16 , 7/32 , $\frac{1}{4}$, 9/32, 5/16

13, 14, 15, 16, 17, 18, 19, 20, 21 and 22, 3/8" drive imperial (inch) Sockets (6pt) 3/8, 7/16, 1/2, 9/16, 5/8, 11/16 and 3/4,3/8" drive metric

(mm) Deep Sockets (6pt) 9, 10, 11, 12, 13, 14, 15 and 16,3/8" drive

imperial (inch) Deep Sockets (6pt) 3/8, 7/16, 1/2, 9/16, 5/8, 11/16 and ¾ ,1/2" drive metric (mm) Sockets (12 pt) 15, 17, 18, 19, 21, 22,

24, 27, 30 and 32,1/2" drive imperial (inch) Sockets (12 pt) 1/2, 9/16,

(mm) Deep Sockets (6pt) 14, 15, 16, 17, 18, 19, 20, 21, 22, 23 and

5/8 , 11/16 , ¾ , 13/16 , 7/8 , 15/16 , 1, 1 1/16 and 1 ¼,½" drive metric

24 ,3/8" drive metric (mm) Hexagon Bits 3, 4, 5, 6, 7, 8 and 10 ,3/8" drive Torx Sockets T-40, T-45, T-47 and T-50 ,½" drive Torx Sockets

T-55, T-60,3/8" drive Spark Plug Sockets (mm) 16 & 21,1" Bits with

Torx T15, T20 & T25, Robertson S1, S2 & S3,1/4, 3/8 and 1/2" Ratchet

holder: Slotted (mm) 4-5, 6-8 and 8-10, Phillips PH1, PH2 & PH3,

handles. 1/4" Spinner (red handle). 1/4" sq. x 1/4" Hex. Adaptor

HK\$180.78

32 Piece - Socket Set

- All components are manufactured from chrome vanadium steel with chrome mirror finish. Contents
- Standard sockets: 10, 11, 12, 13, 14, 15, 16, 17, 18. 19. 20. 21. 22. 24. 27. 30 and 32mm
- Deep sockets: 10, 11, 12, 13, 14, 15, 17 and 19mm 1 x 125mm and 1 x 250mm extension bars
- 1 x universal joint
- 1 x 250mm quick release ratchet
- 1 x 16mm and 1 x 21mm plug sockets



229-7278 RS Pro 32 pc Socket Set ½ in Square Drive

HK\$519.00

12 Piece Combination Ratchet Spanner

- . Slim open end for added strength & high torque
- · Precision ground heads Lever operared direction change
- High tensile Chrome Vanadium steel construction
- Size stamped on open end for quick & easy tool identification
- Bright finish



480-6789 RS Pro 140 pc Socket & Bit Set ½ in, ¼ in, 3/8 in Square Drive HK\$2,500.00

GEDORE

Gedore 12 pc Vanadium Steel Metric Combination MPN: 7 UR-012

HK\$3,390.00

Manoskop Torque Wrench

- . Dual stop signal and cut out
- Dual scale N m/ft.lb
- Accuracy of ±4% · Supplied with certificate



C.K 6-In-1 Cross Key

- 6 key types: 5 mm, 6 mm, 7-8 mm square, 8-9 mm
- triangular, 6 mm hex and 3.5 mm winged
- Tough construction
- · Handy pocket clip



737-0680 STAHLWILLE ¾ in Square Drive Ratchet Torque Wrench 200 -> 1000nm

Adjustable Spanner Phosphated 24

Vanadium Steel construction with Phosphate

finish and polished head



MPN: 96502001



910-7289 CK Universal Cabinet Cross Wrench Key

Easily adjustable with simple left hand roller thread

HK\$14.759.90

- Small L-shaped in chrome vanadium steel





450-1002 RS Pro 8 pcs L Shape Chrome Vanadium Steel Hex

HK\$25.92

GEDORE

Gedore 610 mm Vanadium Steel Adjustable Spanner MPN: 62 P 24 with 63mm Jaw Capacity

Short Adjustable Wrench 6"

Available with a 6" or 8" handle



Designed to give greater strength, torque and access Three sets with long reach L-shaped pattern keys with

finish, to ASME/ANSI B18.3 (imperial), ASME



= Escomi

898-7447 Facom 6 in Adjustable Spanner with 30mm Jaw MPN: 113AS.6CPB

Adjustable Wrench Extra Thin Jaws

- An 8in wrench with wider opening and extra thin laws. 40% wider opening and 45% thinner jaws when compared to a standard adjustable wrench of equivalent size.
- . Thermoplastic no slip handle Phosphated
- · Precision-hardened
- · Anti-corrosion treated
- Standards: ISO 6787, DIN 3117, BS 6333. UNE 16532, ASME B107.8M-2003



710-8798 Bahco 218 mm Thermoplastic Grip Alloy Steel Adjustable Spanner with 38mm Jaw Capacity

- · Designed to operate in narrow spaces
- The nylon strap avoids damage to the work pc Ideal for plastic tubes, oil filters
- Orange lacquered finish
- · Manufactured from forged Chrome Vanadium Steel with a Nylon Strap

Plastic Strap Wrench



MPN: 9031-T

297-1572 Allen 22 pcs L Shape Long Arm Alloy Steel Hex

· Long reach L-shape ball ended hex keys for



194-2719 Facom 8 pcs L Shape Long Arm Hex Key Set

9Pc Britequard Hex Key

- · Length of keys are fully hardened
- Kev material: S2



542-3515 RS Pro 9 pcs L Shape S2 Steel Hex Key Set

HK\$196.84



519-894 Bahco 220 mm Nylon Strap Wrench

MPN: 375-8

HK\$309.00

HK\$262.65

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

HK\$143.19

MPN:T4454



- with chemically blackened finish
- Supplied in plastic wallet







22pcs Combination Hex Ball Driver Set

ball ends for improved access to restricted spaces Manufactured from heat treated alloy steel with black



OALLEN

L-Shaped Ball Drivers

- improved access to restricted spaces
- Available in individual metric sizes or an 8 pc imperial or 9 pc metric set



MPN: 56618G

■ FACOM









RS Pro Hex Key Boxed Sets

- Two L-shaped hexagon key sets supplied in a storage box
- Keys manufactured from 8650 chrome nickel alloy steel • ANSI B18-3 & US FED SPEC GGG-K-275D standards



Rack Mounted

- Available in two sets, each with bench mounting metal storage rack
- Keys manufactured from chrome-vanadium steel, with chemically blackened finish



RS Pro 15 pcs L Shape Short Arm Chrome Nickel

537-811 RS Pro 10 pcs T Shape Chrome Vanadium Steel Hex HK\$339.00

Triple Pack Ball Ended Hexagon Keys

- Suitable for all types of hex screws Balldriver allows screws to be tightened/loosened at angles up to 25°
- Gorilla grip handle stronger than steel Longer length keys for additional
- leverage and extended reach



Strap Wrench

. A 6in, diameter capacity strap wrench for the clockwise or anticlockwise turning of awkwardly shaped items, such as pipework and oil filters. Ideal for maintenance and service applications



541-7324 RS Pro 33 pcs L Shape Long Arm Hex Key Set

542-3751 RS Pro 155 mm Nylon Strap Wrench

Penknife Style Hex Key Sets

 Available in metric or imperial sized sets, with either smaller or larger key sizes



10-piece set of hinged ratchet combination spanners

- Set of reversible ratchet system combination spanners with hinged head.
- Small recovery angle of 5°.
- Ideal for work on site thanks to its hinged pocket case.
- Contains 10 snanners: 467 8-10-11-12-13-14-16-17-18-19 mm



= FACOM

= FACOM

216-6118 Facom 138 mm 6 pc Silicon Steel Hexagon Folding MPN: 86H.JU6

Facom Hex-Plus, Moulded Handle

Tee-handle allows effective use of either end of key -

of up to 30° - ideal for use in restricted access areas

 Handle moulded onto monobloc blade and is resistant to hydrocarbon materials

combines standard hexagon profile on short end with

spherical hexagon head on long end, giving working angle

Compatible with all commercially available hexagon socket head

screws. Hex-Plus® is highly effective for removing/loosening stubborn seized fasteners – gives up to 20% increased torque loads

220-0612 Facom 6 pcs T Shape Long Arm Hex Key Set

A range of multi-purpose enclosure key wrenches designed

The four arms of the tool offer five differing drive possibilities: 6.5 mm (¼ in) & 8.1 mm (5/16 in) square sockets, 6.4 mm (¼ in) AF hex

socket, 9.8 mm triangular socket and 9 mm winged key drive.

Available with either a bright chrome or zinc plated finish.

Supplied with: a hex to ¼ in square drive adaptor, a 7mm

slotted blade & No.2 pozi drive screwdriver bit

Switch Key Universal Wrench

for use within maintenance & service applications.

HK\$420.50

Manufactured from Chrome Vanadium Steel

Thinner profile compared traditional fold-ups

with Satin Chrome finish flexible keys

Canvas pouch for compact storage

675-8966 Facom 10 pc Metric Combination Spanner Set

5 Piece Sae Flexible Hex Key Set Silver

667-3376 Gear Wrench 5 pcs Chrome Vanadium Steel Hex

7 Piece Metric Gear Wrench Spanner

Available as individual metric items or as metric or imperial sets

· Ratcheting box wrench requires only 6° arc

72 Teeth ratcheting box head

Fully hardened all metal construction

nickel-chrome plated mirror finish

Meets ANSI, DIN & BS torque specifications

MPN: 467FJP10

High mechanical performance combined with compact HK\$2,095.18

GEARWRENCH

- design complying with aeronautical standards
- Ring clearancedesigned for better access to recessed or closely spaced screws
- . 12-point OGV profile for a high torque without damaging the nut



= FACOM

8 Piece Combination Spanner Set

- . Slim open end for added strength & high torque
- · Precision ground heads with strong, thin walled rings
- . Size stamped on open end for quick & easy tool identification



Combination Wrench Set

- High performance alloy steel
- Open end angle 15° with a slimmer head to get more accessibility
- 12 points Dynamic-Drive Profile provides
- longer life for screws and nuts Ring end angle 15° for knuckle clearance or better grip
- Chrome plated micro matt finishing provides high quality surface
- Plastic tool roll
- Standards: ISO 691, ISO 7738, ISO 3318, ISO 1711-1 and DIN 3113



877-0754

Bahco 17 pc Alloy Steel Metric Combination

MPN: 111M/17TL

HK\$2.954.45

Small Combination Sets, 10-piece

- · Manufactured in carbon steel, with polished chrome plated finish
- Supplied in plastic wallets



ARMSTR NG

Set

12 Piece, Reversilble Ratchet Spanner

Tighten or loosen quickly with a flip of the reversing lever

15° offset provides access and knuckle clearance

Surface Drive[®] box end virtually eliminates

the rounding of fasteners

. 72 Teeth ratcheting box head

Fully hardened all metal construction

Stillson Pipe Wrench (361 Series)

HVAC engineers, maintenance through to the DIY man.

Designed to provide an instant grip with

· Springs housed inside casing for extra durability

Suitable for repair & maintenance applications

self tightening ratchet style action

Chrome Vanadium construction

· Induction hardened laws

BAHCO

• 3 sizes

Black oxide finish

· Plumbers wrench, or Pipe Wrench for use with round pipes and

fittings. Ideal for many areas and professions including plumbers,

731-9398 Bahco 8 in Stillson Pipe Wrench, 1in Jaw Capacity MPN: 361-8

Adjustable C Hook Wrench, 19-51mm

Armstrong 6.375 in Black Oxidized Forged Alloy Steel MPN: 34-301

HK\$222.10

184-8033

RS Pro 10 pc Carbon Steel Metric Combination

HK\$164.50

26 Piece Combination Wrench Set Sizes from 6mm to 30mm in 1mm steps plus 32mm

- · Supplied in robust blow moulded carry/storage case



511-2710 Gear Wrench 12 pc Metric Combination Spanner Set MPN: 9620N

440 Series Combi Wrench Set 8-24mm

HK\$1,410.00

388-3690 RS Pro 26 pc Metric Combination Spanner Set

12 Piece Reversible Ratcheting Spanner

- . 12 pc ratcheting metric spanner set.
- 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19mm . 72 Teeth ratcheting box head
- 6° movement on 8 and 9mm, 5° movement on 10 to 18mm
- Meets ANSI and DIN standards
- · Fully hardened all metal construction



562-185 Facom 16 pc Metric Combination Spanner Set

HK\$1,539.25

RS Pro 12 pc Chrome Vanadium Steel Metric

HK\$750.03

- High tensile Chrome Vanadium steel construction
- · Bright finish



Flex Head Ratchet Spanner Set Flex head ratcheting metric spanners.

- 180° flex head allows the ratcheting spanner to
- reach and work in tight places and angles
- Continuous tension design controls the flex head
- . 72 Teeth ratcheting box head
- · Manufactured from Chrome Vanadium



GEDORE

Gedore 8 pc Vanadium Steel Metric Combination

MPN: 1 B-080

487-268

RS Pro 12 pc Chrome Vanadium Steel Metric

HK\$1,220.00

439-3019 RS Pro Chrome Universal Cabinet Cross Wrench Key

MPN: 84TZS.PB

351-7589 Gear Wrench 7 pc Metric Combination Spanner Set MPN: 9417

HK\$390.00

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Visit hken.rs-online.com to order today!

25

TOOLS & STORAGE

23 Piece Combination Set

- Supplied in handy tool roll
- . Sizes in Set Imperial: 1/4; 5/16; 3/8; 7/16; 1/2; 9/16; 5/8; 11/16; 3/4; 13/16; 7/8 in; Metric: 6; 7; 8; 9; 10; 11; 12; 13; 14; 17; 19; 22 mm



1000V Torque Wrenches 1/2"

- Reversible for tightening of lefthanded threads
- Lockable torque adjustment
- Easy and secure locking of attached sockets due to screw lock

Knipex ½ in Square Drive Reversible Torque Wrench, MPN: 98 43 50 5 -> 50nm

Facom ¼ in Square Drive ElectronicTorque Wrench, MPN: E.306A30R 1.5 -> 30nm 9 x 12mm

Chrome Vanadium stee



487-274

RS Pro 23 pc Chrome Vanadium Steel Imperial

12 Piece Reversible Head Spanner Set

12 pc metric reversible combination ratcheting spanner

set, flip the reversing lever to change direction.

Electronic Torque Wrench 30 Nm

- · High performance wrench even in intensive
- use (accurate ±2% ±1digit)
- 250 memory with USB link
- Measuring Units N.m, ft.lb, in.lb, Kg.cm



• 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19mm

- · Tightens or loosens quickly depending on the direction of the reserving lever
- 15° offset provides access and knuckle clearance
- 72 Teeth ratcheting box head
- Fully hardened all metal construction
- Manufactured from Chrome Vanadium

Ratchet Spanner Set

. Requires as little as 5° to move the fastener



487-280

RS Pro 12 pc Chrome Vanadium Steel Metric

HK\$2 283 20

3/8" Electronic Torque Angle Wrench

- Reversible interchangeable heads (supplied with ratchet head)
- 60 teeth/6° action

■ FACOM

722-7142

- · Automatic shut off
- Auto zero check on power up
- Operating temperature range: 5
 42°C
- Ranges programmable in nm, lbf.ft., lbf.in



• Professional, durable imperial combination ratchet spanners

Bahco 8 Piece Imperial Combination

- constructed from high performance alloy steel. $% \label{eq:constructed} % \label{eq:constructe$ The 12 point dynamic drive profile provides longer
- life to fasteners and with a small 5° action enables tightening the most cramped spaces



MPN: 1RZ/SH8

BAHCO

763-0771 Bahco 3/8 in Square Drive Electronic Torque Wrench, MPN: IZO-DAG-135

MPN: 8574-10

Dremometer Ds 3/4in 110-550 Nm

- Fasy adjustment with button at the end of the handle.
- Scale in Nm, lbf.in & lbf.ft
- · Lightweight Aluminium alloy construction · Lever mechanism for low wear & long life

GEDORE

Square drive and fulcrum are on the same axis maintaining accuracy



HK\$8.776.60

1/4 in Square Drive Slipping Torque Wrench, 3 25nm • A versatile range of adjustable, calibrated torque

Bahco 8 pc Alloy Steel Imperial Combination

- wrenches based on the proven 'slip free' principal that ensures a fastener cannot be over tightened. Incorporate a micrometer style fine adjustment with a positive
- locking system to ensure fast, easy and accurate setting Non length dependent and automatic resetting after the wrench
- slips free eliminates the possibility of over tightening
- Accuracy and repeatability of ±6% minimum in accordance with ISO6789:2003
- · Robust design with stainless steel head, and coated Aluminium handle
- Standards: ISO6789:2003



26

MHH Engineering ¼ in Square Drive Slipping Torque MPN: 011017 Wrench, 3 -> 25nm

Dial Torque Wrench

 Meets the requirements of the USA Government Specification. GGG-W-00686c with calibration certified and traceable to the US National Institute of Standards and Technology

772-4356 Gedore ¾ in Square Drive Mechanical Torque Wrench 110 -> 550nm

- Accuracy ±4% in both directions over a range from 20 to 100% of full scale
- Patented torque beam design will withstand up to 20% overload without losing calibration
- Overall length means the operator does not have to exceed 125lbs. input force at normal torque range 75Nm
- . Large easy to read dials, protected by a metal guard. enable easy torque readings in SI or Imperial units
- Narrow head design enables access into restricted work areas
- Supplied in storage box



1/2in Air Impact Wrench

- · A general purpose impact wrench with forward
- and reverse mode and comfort grip. Maximum Torque 540Nm, Pin clutch hamme
- mechanism. Aluminium construction. Rear exhaust
- 4 forward operation impact settings, Sound level 96.6BA, Average Air Consumption: 3.6cfm/101.7 l/min
- Single handed direction change, Excellent balance,
- Variable speed positive action trigger
- Forward and reverse independent power regulator
- Weight 2.4kg



Grit

739-8379 RS Pro ½ in Standard, Air Impact Wrench, 2.4kg

Flexible J cloth with aluminium oxide abrasive

. Suitable for polishing and de-rusting metals

Supplied in packs of different grit sizes

Can be used with oil, paraffin, grease or water

Al Oxide Abrasive Cloth, 25mm W 100

Bahco Square Drive Mechanical Torque Wrench, 20 MPN: 7852-200 → 200nm 14 x 18mm 667-2409

Stanley ½ in Square Drive Mechanical Torque Wrench, MPN: 6121NMF

9 Piece Hex Ball Key Set

- . Ball driver allows screws to be tightened
- Chrome finish
- · Plastic coated for comfort





Norton Aluminium Oxide Fine Abrasive Cloth Roll 100 MPN: 63642531815 Grit, 25m x 25mm

Bear-Tex(Tm) Grey Medium Handpad

Sheet size 150 x 230mm



779-166

Norton Medium Abrasive Hand Pad, Silicon Carbide, MPN: 66261039803 230mm x 150mm Bear-Tex

HK\$162.05

HK\$2,018.80 Emery Cloth, 230X280mm, 60 Grit

- · Extremely strong backing · Tearable cloth
- For dry sanding polishing, de-rusting, de-burring metal etc



NORTON

Flexovit 60 Aluminium Oxide, Silicon Carbide Emery MPN: 63642558249 Cloth, 280 x 230mm

- . Elliptical shape doesn't block your view of the work area
- Tensioned and ready for use
- Easy to grip tensioning lever for fast and safe blade changes
- Tapered front for hard to reach applications



5387	Rahco 300 mm Hacksaw with Ri-metal Blade

Banco 300 mm Hacksaw with Bi-metal Blade and Ergonomic Handle, 24 TPI MPN: 325

HK\$287.21

Visit hken.rs-online.com to order today!

HK\$2,754.00

HK\$4.979.88

Interchangeable Head Torque Wrench

For all assembly jobs, especially suited where access

with ratchet head, for suitable heads see Bacho Interchangeable Torque Wrench Heads range.

Standards: DIN/ISO 6789.1993, EN26789.1994

with conventional sockets is not possible. Not supplied

loosened at angles up to 25°

. Accuracy: ±3%, single direction

. Single torque scale for easy use

Interchangable heads





MPN: BP821



Ratchet 1/2"

- Rubber grip
- Power regulator Connection size: 10mm
- · Length: 256mm Torque: 0 67Nm
- Weight: 1.2kg · Swivel connection and air exhaus



763-0780 Bahco BP821 ½ in Air Ratchet Wrench, 150rpm,

- 3/4" Impact Wrench Maximum Torque 1350Nm
- · Pin clutch hammer mechanism
- · Aluminium construction · Rear exhaust through handle
- Sound level 108dBA
- 3 forward & 3 reverse operating impact settings · Rugged design
- · Single handed direction change
- Average Air Consumption: 10cfm/282 l/min

739-8373 RS Pro ¾ in Compact. Air Impact Wrench. 4.5kg

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

HK\$3,234.89

Bahco Ergonomic Hacksaw, 300mm







Adjustable Tension Mini Hacksaw.

- A high quality 'Eclispe', adjustable tension mini hacksaw which accepts standard 150mm blades.
- Designed for cutting metal, wood or plastic it features a plastic pistol grip handle for comfort and control



Bahco Hacksaw Blades

- · A fully hardened, high-alloyed, super high speed steel blade for
- sawing stainless steels, hard metals and other hard to cut materials Designed to cut a wide variety of materials
- from aluminium to stainless steel.
- Blade length 300mm



Blade

734-393

RS Pro 150 mm Hacksaw and Plastic Moulded Pistol Grip Handle, 32 TPI

Insulated Junior Hacksaw, 150mm L

. A 300mm hacksaw and a junior hacksaw which

are insulated around the blade fittings

HK\$69.90

484-7566 Bahco 300 mm HSS Hacksaw Blade, 24TPI

MPN: 3801-300-24-10P

75Pc Tap/Die Set

- High quality product made from carbon steel
- · Ideal for confined spaces . Supplied in a sturdy, blow moulded case
- · All taps and dies lock in place · Hand-over-hand turning eliminated





621-641 Sibille 150 mm Hacksaw and Insulated Handle, 32 TPI MPN: MS22JRS

Hacksaw Frame, 300mm

- Standard 90 degree for general use
- 45 degree angle for flush cuts · Low profile position for tight spaces
- Jab saw configuration for a variety of inside cuts
- Cushion grip handle for better control and comfort
- Magnetic blade storage inside frame



612-2724 Gear Wrench 75 pc Carbon Steel Tap & Die Set

MPN: 3887

MPN: L120 10M

MPN: 10723

L120 Hss Tap & Die Set, 10M, M3-M10

- All sets contain matching taps and dies All metric utilise 13/16in and 1in diecasts
- Imperial set utilises 1in and 1 ½in diecasts



HK\$1,970.54

Nicholson'

509-9471

. Two-component handle

319 Hacksaw Frame

· Comfortable Light-weight frame

Easy Blade Change Mechanism

High blade tension, retained after blade change

Nicholson 304 mm Hacksaw and Cushioned Rubber MPN: 80975 Grip Handle

Stm35 Tap & Die Set

DORMER


EVENTUS

- HSS-G tap, cutting die and holding tool as per DIN
- . 3-pc sets of all sizes, each with 1 x front, middle and bottom tap

499-356 EVENTUS 52 pc HSS M3 → M20 Tap & Die Set

224-4555 Dormer 19 pc HSS M3 → M10 Tap & Die Set

· Straight flute, profile and relief ground



40Piece Tap/Die Set Metric

High quality product made from carbon steel

Supplied in a sturdy, blow moulded case



HK\$6,105.32

HK\$3.060.70

Blade, 24 TPI

442-0515 Bahco 300 mm Hacksaw

RS Pro 300 mm Bi-metal Hacksaw

Dual position 90° & 55° blade angle for standard/flush cutting

 A high speed steel cutting edge, electron beam welded to a flexible alloy back. Cuts through virtually any type of steel and is unbreakable in normal use

185-3675 RS Pro 300 mm Bi-metal Hacksaw Blade, 24 TPI



HK\$45 00

Ideal for confined spaces.

· All taps and dies lock in place

· Hand-over-hand turning eliminated

612-2718 Gear Wrench 40 pc Carbon Steel Tap & Die Set

MPN: 3886

HK\$2.007.87

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



E515 Hss Unc St/Fl Tap Iso529 4-40 Set3

- Suitable for tapping repeatable tolerance threads in through or blind holes by hand or machine
- 7° cutting rake angle
- Bright finish



Air Riveter

- Aluminium construction, ergonomically
- designed, ightweight air riveter. 3/16in max capacity
- Mechanism 1870 Traction Power
- Minimum hose size 10mm/3/8in Sound level 76dBA
- Average air consumption 4cfm/113 l/min



DORMER

Dormer 3 pc #4 UNC HSS Straight Flute Tap Set 241-4265

RS Pro ¼in Rivet Gun, 3/16 in Maximum Rivet Size

Rethreader, 3 Piece Tap Set, M6 X 1.0mm

- Suitable for tapping repeatable tolerance threads in through or blind holes by hand or machine
- · 7° cutting rake angle
- · Bright finish



Electronic Multi Test Screwdriver

- Suitable for use on 70 250Vac/250Vdc (direct contact)
- Voltage test non-contact 70 10000Vac



241-4085

Dormer 3 pc M6 HSS Straight Flute Tap Set Taper Tap; MPN: E500 6.0 X 1.00 Plug Tap and Bottom Tap 3FL SET3

240Vac

25PC Hydraulic Puller Set

- · Heavy duty master set of gear pullers and bearing splitters
- 8 Ton maximum hydraulic ram and forged puller arms and bearing splitter
- · Replacement of gears, bearings, balancers easily effected For cars, trucks, off-road construction equipment and machinery
- Supplied complete with carrying case



Bosch Electronic Heat Gun. 200Va

451-8971 RS Pro Mains Test Screwdriver, 70 -> 250V AC/DC

- Continuously adjustable temperature and airflow
- Electronically and optically monitored Long life ceramic heating element
- 110V version comes without plug



349-7261 25 pc 8T Hydraulic Puller Set

Venturi Air Gun

- Venturi action nozzle multiplies air volume output, and makes gun completely safe, because - unlike conventional units - output air flows around the unit and not through it
- Manufactured from aluminium for longevity
- ¼in BSP Inlet





BOSCH

472-9323 Bosch +660°C max Heat Gun, 230V ac, 1400W, Type MPN: 0.601.944.742

Standard Heat Gun

- · Ideal for lighter duty intricate work
- . Hot, off, cold selector switch
- Max Temp 360°C 510 cu.ft/hr
- Supplied with"13dia x 10mm wide reflector, 13dia x 83mm wide reflector, precision reflector & reducing baffle



488-5568 RS Pro ¼in Blow Gun, 12bar

- 10mm Reversible Air Drill Aluminium construction reversible action 3/8in/10mm air drill. Ideal for drilling, reaming and honing.
- Rear exhaust through handle
- Side mounted forward/reverse shift
- · Triple planetary gear system · Jacobs keyless chuck
- · Powerful air motor
- · Positive trigger action Sound 87dBA
- Average air consumption 4cfm/113l/min Weight 1.1kgs



739-8395 RS Pro 10mm Yes Air Drill, ¼in, 1800rpm (APT401R)

HK\$770.88



HK\$296.04

Weller 6966C +360°C max Heat Gun, 230V ac, 250W, Type G - British 3-pin

MPN: 140696606

HK\$2,702,23

MPN: E515 NO.4 X

HK\$433.07

- Continuity test 0 50 MΩ
- . Polarity test +/- 1.2 to 36 Vdc
- Microwave leakage detection >5mW/cm²
- Safety barrier 16 MΩ resistor





10mm Staples For 753-3302 (Box Of

- Mains powered, lightweight, compact and well balanced flush front staple gun tacker
- Hand contoured handle for comfort
- Solid state electronic circuitry Trigger squeeze operation with on/off safety lock

183-9348 Arrow 506IP 10mm Stanles

Driver Kit (DCK255)

- One-pc solid steel base construction
- Jam-proof mech



HK\$105.91

3M™ Scotch-Brite™ Clean & Strip™ Disc

- Scotch-Brite[™] cleaning and stripping wheels for use in power tools Ideal for removal of rust and carbon deposits on steel,
- stripping paint and varnish, de-oxidation and cleaning of welds, sanding and cleaning of stone, concrete, etc.

456-2754 3M Nylon Grinding Disc, 100mm, 60 Grit

3M[™] 734 Wetory[™] Paper Sheets

Wet and dry sheet for impeccable finish on

metal, plastic, resin or polyester surfaces

long product life and good surface quality

Sharp, abrasive silicon carbide mineral ensures

Water resistant paper backing for easy handling

- Does not contaminate the work pc Fast and controlled work
- Coarse grade



18V XR Compact Combi Drill & Impact

 A professional 18V 2 pc power tool kit from DeWalt featuring the outstanding DCD995 brushless compact combi drill and the ever reliable DCF886 professional brushless impact driver. Both with DeWalt's XR Lithium Ion batteries for unrivalled power and run time.

- · Compact ergonomic design for controlled, comfortable handling
- New XR premium Lithium Ion technology for increased working · Lightweight, compact design enables use in confined,
- hard to access spaces for excellent handling
- Brushless Combi Drill with Hammer Action (DCD995)
- 13mm ratcheting keyless chuck for quick and easy bit changes
- 3 speed metal transmission for longer tool life



826-8021

Dewalt XR Brushless 18V Li-ion Keyless; Hex Cordless Drill Driver Kit. 5Ah (DCK255P2)

MPN: DCK255P2-GB

MPN: 506IP

HK\$6,061.56

HK\$274.32

18V Xr Li-Ion Grinder 2 X 4.0Ah

Diamond Cutting Wheel W/Mandrel,

A 22mm diameter diamond cutting wheel complete

472-3038 RS Pro Diamond Cutting Disc, 22mm

with mandrel for cutting hard materials

- . Steel cut spiral bevel gears
- · Intelligent trigger design
- Lock off switch for safety
- Keyless guard
- Ergonomic design

22mm Dia

· 3.2mm shaft diameter

· Quick change wheel release



769-4056 Dewalt 18V 7000rpm 125mm Disc Cordless Grinder MPN: DCG412M2-GB HK\$5,918.20

Nozzles - 1/4 in. & 1/2 in.

- · A high quality adjustable modular hose system
- Available in ¼ in, and ½ in, bore
- manufactured from acetal copolymer which is nonconductive and resistant to most organic chemicals
- The unique interlocking feature permits the user to construct hose systems to meet specific requirements. Individual parts are sold separately
- Applications in some specific strong acidic environments (i.e. 10% hydrochloric acid, 10% sulphuric, 10% nitric) or strong bases (i.e. pH 4.0) are not recommended



EXTREME Cobalt Bit Sets

Precision ground twist drill manufactured to DIN 338

temperatures when drilling arduous materials

- Right hand cutting helix, type N flute
- 5% cobalt alloyed High Speed Steel for stability at high
- Unique Extreme Cobalt tip improves efficiency and eliminates walking
- Finish Gold Ferrous



25 Piece Drill Bit Set, Hss, 1-13 mm

- · Precision ground for a faster drilling rate and lower feed pressure
- Self centring drill bits

BOSCH

• 135° point angle



678-3035 Dewalt HSCo 1 → 13 mm 29 pc Drill Set

MPN: DT4957-QZ

HK\$1.164.04

HK\$884.12

759-5788 Bosch HSS-G 1 -> 13 mm 25 pc Metal Drill Set

MPN: 2607018727

Dewalt HSS-G 1 13 mm 29 Piece **Jobber Drill Set**

- 29 pc HSS-G Drill Set
- HSS-G DIN 338 Jobber metal drill set.



10 Piece Hss-Co Drill Bit Set, 1-10mm

- · For the drilling and machining of higher tensile, tougher materials 135° split point for easy positioning, improved
- hole size. & higher quality



678-3054 Dewalt HSS-G 1 → 13 mm 29 pc Jobber Drill Set MPN: DT5929R-GB

Dewalt 10 Piece SDS Plus Drill Set

- The professional DeWalt DT7935B-QZ 10 pc EXTREME SDS Plus drill bit set. The innovative range is among the best in terms of speed, life, and durability.
- Featuring an optimised flute design allowing for effective debris removal. Also the new tip design provides better bit penetration.
- Superior carbide grade for long life
- Hardened body for extra strength and reduced breakage





759-5603 Bosch HSCo 1 -> 10 mm 10 pc Robust Line Metal MPN: 2607019925

Hsco Heavy Duty Jobber Drill Set 1-10mm

- Material: HSCo cobalt Steel
- Surface Treatment: Bronze. Right Hand Spiral

888-3667 Dewalt 10 pc SDS Plus Drill Set

MPN: DT7935B-QZ

HK\$711.88

794-7672 Dormer HSS-E 1 -> 10 mm 19 pc Jobber Drill Set

MPN: A295219

HK\$1,581.62

A190 HSS Drill Set No209, 91Pc, 1-10mm

- Straight shank, right-hand cutting jobber drills to BS 328/DIN ISO235 standard
- · Supplied in cased sets with numbered drill slots



19 Pcs HSS Ground Point Drill Bit Set

- Milled from solid Steel for excellent strength
- High Speed Steel (HSS) construction for metal cutting Internal holder for drill bits with size markings for
- quick identification of the right or missing parts Holder fans out automatically



DORMER

Ground flute

• Sizes increase in 0.5mm increments

Manufactured to DIN338 standard

• Ideal for general workshop applications

 Heavy duty steel case with moulded rigid insert for secure storage of drill bits

695-305 Dormer HSS 1 -> 10 mm 91 pc Jobber Drill Set

170 pcs, Jobber Drill Set, HSS-Tin Coated

MPN: A190 209

HK\$3 122 71

848-3598 Makita HSS 1 -> 10 mm 19 pc Ground Point Drill Set MPN: P-19906

HSS Ground Flute Jobber Drill. 9.5mm Dia

- Perfect for general purpose workshop and maintenance drilling work
- High Speed Steel (HSS) construction, ideal for use with power tools
- Black finish for corrosion and wear protection





507-1732 BS Pro HSS 1 -> 10 mm 170 nc. lobber Drill Set

Dino-Lite

343-0296 Volkel HSS 9.5mm Jobber Drill Bit, 125 mm Plain



30

Visit hken.rs-online.com to order today!

MPN: FN5100-7836-6


3M Silicon Carbide Very Fine Sanding Sheet, 800 Grit, $\,$ MPN: A02007 230mm x 280mm

Manual Toggle Press · Manual toggle press designed for light/medium duty work such as forming, swaging, riveting, marking, piercing and assembly. Constructed from malleable iron, machined on the base mounting

before going 'on-centre' for quick return and light operation, or 'over-centre' in order to hold work under pressure. Cost effective: makes dedicated tool fitting to a number of presses economical, eliminating the need for expensive

faces for accurate alignment of tools. An adjustable bolt at the

rear of the frame allows the toggle mechanism to be stopped





254-844 RS Pro 600kgf Manual Toggle Machine Press

- for coolants fluids and air applications
- All components are fully interchangeable and



623-5022 RS Pro ¼in Nozzle

HK\$1 444 54

HK\$30.29

31

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Hss E Cobalt 8.0mm

- Precision ground twist drill bit manufactured to DIN 338
- Heat and wear resistance properties
- Right hand cutting helix, type N flute
- 5% cobalt alloyed High Speed Steel
- · Unique tip improves efficiency and eliminates walking



Hammer Capable Keyless Chuck 1/4"

- With this keyless spindle, it is possible to convert a ¼" power screwdriver into a hole cutter.
- . The capacity of the spindle is 8 mm



Dewalt EXTREME HSCo 8mm Drill Bit, 117 mm

MPN: DT4912-QZ

MPN: 2.607.018.366

HK\$78.53

251-7184 CK Keyless 1/4 in Power Tool Chuck

MPN:T2463

HK\$52 15

8 Piece Bosch Masonry Drill Set, 3-10mm

- Tungsten Carbide tipped masonry drill
- · Rolled flute for rigidity
- . For use with hammer drills 8 nc set
- 3 10mm dia in 1mm increments



Std Reciprocate Saw Blade, 14Tpi 150mm L

- · Constant tooth pitch blades, similar to hacksaw blades
- Fits the following manufacturers' machines: AEG; Bosch; B&D; Holz-Her; Flex; Fein; Hitachi; Makita; Metabo; Milford; Milwaukee; Rockwell; Skil





349-9150 Bosch 3 -> 10 mm 8 pc Masonry Drill Set

• Up to 4X faster than conventional HSS Drills

Cleaner, more accurate, burr-free holes

. Unique metal tip starts cutting on contact

eliminating walking (3.2mm and above)

due to recessed cutting wings

3 flat shank (5.0mm and above)

Extreme 2(Tm) Hss Drill Bit, 6.5mm Dia

229-4083 Bahco 150mm Cutting Length bimetal Reciprocating MPN: 3840-150-14-ST-5P HK\$216.56 Saw Blade, 14 Teeth Per Inch



G-Clamp Bench Vice

- · Lightweight portable mini vice for engineering and
- automotive, and home workshop applications Cast iron vice construction
- · Steel iaws
- . 360° rotating vice head



Metric Cutter W/Morse Taper Spindle

Longer life than standard HSS/M2 steel cutters

High quality M42 Cobalt Steel cutters for use with Magnetic drilling/

milling machines or drilling machines with a Morse Taper spindle

Dewalt EXTREME 2 HSS-R 6.5mm Drill Bit, 101 mm MPN: DT5049-QZ

752-2428 RS Pro Bench Vice x 30mm 65mm x 60mm

Bench Top Mounting Base

- This combination comprises the Panavise vice head (stock no.120-0138) and the Panavise suction pad base (stock no.120-0122).
- . The vice head has nylon jaws and can be rotated through 360° about its axis



G&1 HALL LTD

G&J Hall M42 Cobalt Steel Magnetic Drilling Hole MPN: 18Y102

150mm W

283-8166 Panavise Bench Vice 63.5mm x 57.1mm, 1.3kg **Engineers Vice, 205mm Jaw Opening**

- The body and sliding jaw are manufactured from high grade grey cast iron. The steel main screw engages with a long barrelled "unbreakable" nut
- · Finished in stove enamelled blue · Detachable fibre grips are available for
- clamping softer materials and finishe





Record Bench Vice x 90mm 150mm x 205mm, 31.8kg

HK\$2,754.00

Welders Angle Clamp, 2X90mm

· Cast jaws and base with copper plated screw

35Hx110Lmm



Lever Action Barrel Pump, 35L/Min

- . Choice of two barrel pumps, designed for use with 40 gallon
- metal drums, which will pump up to Hypoid 90Viscosity
- Lever action pump (RS 672-425) incorporates 84cm galvanised steel suction tube, discharge hose optional extra
- Rotary action pump (RS 672-419) incorporates 96cm steel suction tube and comes with M24 x 4mm retention adaptor



227-7218 Bessey & Sohn 90mm Welders Angle Clamp

 Variable Clamps will grip sheet or tube at angles from 25° to 280° with the main angles of 90°, 60°, 45° and 30° marked for quick reference

Magnetic Variable Clamp



HK\$1.890.00

MPN: WSM 9

MPN: E952

MPN: 1-83-069

PRESSOL

672-425 Pressol 13042, Hydraulic Hand Pump

MPN: 13042

Stainless Steel Foul Water Pump, 400L/ Min

- Manufactured from 304 stainless steel, making them ideal for use in conditions where contamination or rust is unacceptable
- Must operate totally submerged in the liquid to allow motor cooling
- Thermal overload motor, insulation class F, serial mechanical seal made of graphite and aluminium, lubricated in oil sump and protected by V-ring sand-guard
- Self-sealing Vortex system impeller in cast stainless steel
- · Automatic float switch
- · Free passage of 40mm solids



HK\$6,620.00

HK\$2,101.35



511-257 Eclipse 25 -> 280° Magnetic Variable

Multi -Angle Base vice . Made of durable cast iron

- · Infinite and lockable positioning achieved with a swivel ball design
- · Easily attatched to most work surfaces with integral screw clamp Removalble jaw pads protect surfaces from marring and damage



Workshop/Tradesman

 A combination set which is ideal for workshop use, particularly with sheet metal work applications.,All heads are manufactured from cast iron castings, the rule is tempered steel.,Rule: 300mm/12in. steel rule with engraved markings, paint filled. Sub-divided 1/64in./1mm on the channel side, 1/32in./0.5mm on the plain side.. Square head: Includes 45° mitre face, spirit level and 40mm long scribe., Mitre head: Locates centres in cylindrical surfaces., Protractor head: 0 - 180° scale in both directions graduated every degree. Incorporates a spirit level on rule plain

214-5199 W Robinson And Sons Submersible Water Pump, 4001 /min 230V



667-7189 Stanley 70mm Multi-Angle Vice Clamp

Tft Computer Cupboard

Slide out keyboard tray with lock for security and controlled access

Comprehensive Service Engineers Tool

. A comprehensive service engineers tool kit containing a range of 100 high quality tools in a heavy duty ABS tool case.

The kit provides the electrical and electronic engineer with

the majority of the tools they require in their work

- Lockable TFT monitor casing with vents to avoid over heating Galvanised Steel shelf inside a lockable cupboard for safe and secure PC housing
- Powder coated finished in RAL 5010 Blue & RA



HK\$5,178,12

24in Digital Inclinometer

 An accurate 2 vial spirit level fitted with an electronic digital inclinometer which can be used for conventional measurement of horizontal and vertical as well as measurement of angles and gradients. An audible chime can be selected that indicates plumb and level.

249-3987 RS Pro 12in Combination Square, Steel



- Display automatically inverts for taking overhead measurements
- LCD display operates through 0 to 360°
- · Data hold button
- User display calibration possible
- Tough acrylic vials 0.5mm/m accuracy
- Anodised ribbed aluminium construction Vinyl storage case protects unit during transit



263-9329 RS Pro 24in Inclinometer, User Calibrated

HK\$3,146.01



663-847 RS Pro Tool Kit

HK\$6 023 00

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Bott Blue Computer Workstation Galvanised Steel MPN: 16912308.11v Material, Dim. 1550 x 650 x 550mm

Stanley FatMax® XL Torpedo

- · This torpedo level is handy, tough, magnetic and super-precise
- Precision engineered and super-accurate
- Lifetime accuracy warranty
- Magnified centre vial is 20% larger than standard, making it clearer to read
- . Super strong rare earth magnets give it 2 x the magnetic pull of conventional magnetic levels
- The perfect tools for many jobs
- 180° rotating vial allows you to duplicate angles, and
- the pipe groove is ideal for rounded surfaces



so you can accurately measure objects with ease. Clear LCD display

Stainless Steel construction

RS Digital Caliper

Electronic digital caliper with a hardened stainless steel

for inside, outside, depth and step. This handy tool is

available in both metric and metric conversion models

frame and jaws, enabling accurate measurement of objects

- Origin setting
- Offsetable zero Switchable On/Off
- Thumbwheel for fine adjustment
- · Knurled locking screw
- · Supplied with: SR44 Coin Cell Battery

724-3737 Stanley 229mm Magnetic Torpedo Spirit Level MPN: 0-43-609

Precision Shaft Level

 Professional range of precision shaft levels generally used to check the setting of the horizontal level of machine tool slide ways



841-2518 RS Pro 150mm Digital Caliper ,Metric & Imperial

Fat Max (long reach)

- 8m (26ft)
- 32mm (1 ½in.) wide blade, Mylar coated for durability
- Graduated Imperial/Metric
- High impact ABS case with rubber non-slip grip



HK\$#N/A



RS Pro 150mm Precision Shaft Level Inclinometer, User Calibrated 785-7897

364-4928 Stanley FatMax 8m Tape Measure, Metric & Imperial MPN: 0-33-726

• Bulls eye level which has a single vial which operates in horizontal plane. Ideal for permanent attachment to mobile equipment



HK\$2,123,48

Stanley Tylon Tape Measure

- Professional Stanley tylon coated tape measure with a matt finish blade.
- Tylon coated blade
- Shock-resistant case whihe will withstand shocks and knocks.
- Ergonomically cushioned grip



HK\$95.80



Hold function

667-3913 RS Pro 25mm Bulls Eye Spirit Level

Digital Level/Inclinometer

Quick and accurate measurement of gradient

• Selectable acoustic signal to indicate 0° or 90°

• Choice of measurement units: degrees °, percentage %, or in/ft

Battery not supplied, for a suitabe battery see RS 394-9059


776-9784 Stanley Tylon 5m Tape Measure, Metric & Imperial MPN: 1-30-696

- Stanley FatMax® XL High quality tape with Class II accuracy.
- Blade Armor coating on the first 150mm reduces
- the risk of breaking the tape by 95% Cushion grip provides sturdy, slip-resistant hold
- Huge standout of almost 4 metres for easy one person measuring
- · Wide 32mm blade makes reading the numbers easy
- Mvlar® coated blade is up to 10 times more resistant to abrasion than normal lacquered blades
- Specially designed hook grabs on side, top or bottom for versatility
- Belt Clip



Plastigauges

- · This provides a simple but accurate method for measurement of running/static clearance between hidden surfaces, such as big end or mains bearings, pipe flanges, head gasket,
- high spots, housings, injection moulding tools etc. Can highlight, clearance, lobing, ovality on shafts
- Volumetric measurement takes surface roughness into account
- Calibration card supplied
- Clearance measurement 0.001in. to 0.020in.
- (0.025 to 0.5mm) can be taken.





Stanley FatMax 10m Tape Measure, Metric & Imperial MPN: 5-33-896

Self Adhesive Measuring Tape

- 1.2m steel measuring tape
- White power coated finish
- Self-adhesive backed





34

222-4444 RS Pro Clearance Gauge, 0.025 → 0.175 mm

706-8145 RS Pro 1.2m Tape Measure, Metric & Imperial

HK\$369.94

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Laser Distance Estimator (414D)

- Laser distance estimator with simple one handed
- measurement. Powered by 2 x AAA batteries.
- Measures up to 50 m (165 ft) with accuracy of 2 mm (0.08 in)
- . Bright laser for visibilty at long distances · Addition & subtraction function
- · Pythagoras function indirectly measures height
- through two other measurements
- Easy & quick calculation of area (square feet/meters) & volume
- . Automatic shut-off feature to extend battery life
- Up to five measurements stored . Two-line display with display hold
- Supplied with 2 x AAA batteries, user's manual (CD), quick reference guide, vinyl carrying pouch & lanyard



764-9621 FLUKE Distance Meter FLUKE 414D, 50 m MPN: FLUKE-414D HK\$1,118.00

MW40M Counter Measuring Wheel

- Gear driven counter with tough plastic housing 5 digit counter with manual reset button
- · Heavy duty metal folding handle with rubber hand grip
- · Folding wheel mount
- . Diecast Aluminium wheel, wear resistant tread
- · Folding kick stand
- Accuracy ±1% ±1 digit



487-1531 Stanley Distance Meter MW40M, 10000 m

RS Electronic Micrometers

877-1791 RS Pro Micrometer Depth

steel blades and mild steel cases

· Feeler gauges sets which have hardened ground

· Electronic micrometers are tools designed for engineers and alike, to accurately measure thickness of materials and objects. The LCD display and metric/inch conversion makes it easy to read and use

General Workshop Grade - Steel Blade

449-9640 RS Pro CE3112 Steel Feeler Gauge, 0.04 → 1 mm,

- Resolution 0.001mm/0.0005"
- LCD display
- · Metric/Inch Conversion
- Supplied in fitted case



MPN: 1-77-174

Wave Led 5D Light Grey Eu/Gb

- 3.5 Dioptre magnification.
- Plu-in 18 V power supply. · Parallel, three-pivot arm.
- 3D Feature



LUXO

Luxo Wave LED LED Bench Magnifier, 5dioptre, Table MPN: WAL026067 Clamp 2 x 6W

- Hastings Triplet Lens, Double 10X 15X
- Each magnifier has a multiple lens configuration which gives a high quality image
- Available as single, double or triple magnifier
- Supplied in a storage pouch





RS Pro Double Lens Magnifier, 10, 15 x Magnification,

- Led Handheld Magnifier With Stand, 4X Rugged rubberised coating for impact and drop protection
- · Comfortable grip for long working · Large magnifying area
- . Light provided by 6 individual white LEDs for excellent illumination
- 2 Way lighting system for 5 smaller LEDs for all round illumination or on





RS Pro Illuminated Handheld Magnifier, 4 x

- **Led Headband Magnifier Kit**
- Four interchangeable binocular magnifying lenses Detachable flexible head spotlight with latching pushbutton switch
- Three high-brightness white LED light source
- Powered by three AAA cells (not supplied)
- Adjustable headband



HK\$141.37



HK\$589.15

Double Light Stereomicroscope 20-40-80X

- field eyepcs with the 2x and 4x occulars make possible the range of 20x to 80x magnification
- Illumination with dimmer
- The height adjustable trinocular head allows for observations of larger items (63 to 100mm)





718-7325 Bresser 58-03100 Microscope, x20 -> 80 HK\$4 568 44

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



HK\$5.049.60













HK\$158.76











MPN: 58-03100













RS Pro Grease Gun

- RS Pro manually operated grease gun with
- heavy duty head and variable stroke. Aluminium die cast head with bulk loader
- Rugged and robust Zinc handle
- Delivers 1 gm/stroke
- Cartridge, suction or filler pump loading
- Complete with 150 mm bent steel extension Capacity: 500 gms bulk/400 gms cartridge





200-9425 RS Pro x10 Surface Contact Magnifier with 19mm

· Ridges on bottom of lens which minimizes the risk of scratching

1.8X Segment Magnifier

. Lens Material: PXM with Cera-Tec Coating.

Magnification: 1.8x.

Mount: Matte Edge.

■ESCHENBACH

Lens Size: 65 x 36 x 46 mm.

· Lens Type: Aspheric Surface

HK\$921.48

786-5283 10000psi Diecast Aluminium Manual Grease Gun, 1 g

R5

Stainless 'D' Shackle

- · Stainless steel shackles with screw pin, for securing loads or plant.
- Note: Stainless Steel Shackles have not been proof tested. and should be tested and certified before use in lifting systems. Working load supplied as a guide only

· Fitted with extra luggage straps to secure goods when loaded

312-3522 RS Pro Shackle, D-Shackle, 0.75T

9.6V Cordless Rotary Tool Kit

4 collet chucks (1mm, 2.35mm, 3mm and 3.2mm)

polishing, cleaning, cutting and grinding

· Attractive aluminium carry and storage case

Spare 9.6V battery ordered separately

· 100Various accessories for sanding, drilling, engraving,

Un to 60 minutes use between charges

· Suitable for compact storage

Ideal for storing in a car

784-6030

• 10000 - 25000rpm

. LED snot light feature



HK\$417.23

HK\$252.50

HK\$1,872.00

HK\$729.03

Light Duty Folding Sack Barrow HK\$435.23 MPN: 1426

- 780-2856 Eschenbach x1.8 Surface Contact Magnifier Lightweight aluminium/steel sack truck · Collanses and extends in just a few seconds
- A round glass lens, daylight lamp with flexible joints and a quick positioning handle. Allows the user to

Round Magnifier Lamp with Sun Cap

- quickly push the magnifer out of the way or pull the magnifier closer to the workpc for detalled working Energy saving 22W bulb and electronic ballast
- for longer life and reduced costs · Low heat emission bulb and shadow free lighting
- for clear and comfortable working
- Protective sun cap
- With a 1.5m cable and table clamp with cone holder is ideal for mobile working and can quickly and easily be moved from desk to desk



RS Pro Longreach Bench Magnifier, 3dioptre, Table Clamp Mount, 22W



- · Choice of different thread sizes
- Each kit contains 150 grease nipples: 50
- each of H1-straight; H2-45°; H3-90°
- . Supplied in storage box

36

Made from steel which is Zinc passivated



RS Pro Grease Gun Nipple Kit Contains H1 Straight 6x1 mm (x50); H2-45 6x1 mm (x50); H3-90 6x1 mm

613-1223

RS Pro RC09/UK Miniature Cordless Rotary Tool Kit, UK Plug

RS Pro Foldable Flatbed Platform Truck, 1125 x 600 x 600mm, 200kg Load

• Variable speed 9.6V Cordless Rotary Tool Kit with 100 accessories.

A720 Hsco Ss Micro Drill Din1899

.15mm

- · HSCo drill for small diameter drilling in most
- materials up to x2.5 diameter
- All drills supplied on 1mm shank Manufactured to DIN1899 Standards





198-4606 A720 0.15MM, Cobalt PCB Drill Bit 0.15mm MPN: A720 0.15MM

Light Weight Effective Crop & Bend Tool

- . A high quality, lightweight hand tool, similar to component lead bending tool 545-086 but having the additional facility of cropping the leads to a desired length, Both operations (cropping and bending) are carried out simultaneously and the length of cut each side is independently adjustable
- Overall dimensions (mm): W. 76 H. 145 D. 140



150mm Reverse Action Tweezers

- Reverse action tweezers, recommended for
- holding objects during welding operations.
- · Stainless steel, non-magnetic, resistant to acids. • Fibre resting plates (29SA: straight)



MPN: 30 SA


MPN: 5-060

TOOLS & STORAGE


545-109 RS Pro Bending, Cutting Hand-Held Tool

Printed Circuit Board Holder pcsa-4

- ESD Safe.
- 2 x Adjustable subdivisions
- · Various sizes
- Foam Rubber







HK\$790 43

6-Piece Set Esd-Tweezers

- Small extremely hard precision machined tips for unrivalled strength and durability
- Chrome Nickel high grade Steel construction for

446-7514 Erem by Weller 150 mm Anti-Magnetic Stainless

- excellent durability, strength and handling Stainless and Anti-magnetic (SA)
- Acid resistant

Erem

- Matt finish Marked with the

O BENNSTEIN



HK\$251.75

HK\$900.00

HK\$229.87

idealtek sa

· Heavy duty steel construction

· Spring protector

. Both ratchet and free run operating

. Brass coupling with 360° rotation

• Temperature range -5°C to +60°C

Supplied with wall and ceiling bracket

787-0339 PCSA-4, 520 x 410mm PCB Work Holder

. Movable stopper to adjust remaining hose length

Polyurethane Auto-Return Air Hose, 10M

MPN: PCSA-4

HK\$2,464.00

Bernstein 6 pc Steel Tweezer Set with Various

- **Standard Tweezers** Temperature resistance +300°C
- Non-magnetic
- Acid resistant alloy





788-3732 RS Pro Blue 2 m, 10 m PUR Air Hose, -5 to +60°C

Heavy Duty Blade For Brass And Cast

Iron

- · Manufactured from high speed steel Heat treated to a hardness of 64 RC (Rockwell)
- Supplied in bags of ten





No.00

Erem by Weller 120 mm Anti-Magnetic Stainless Steel Straight; Pointed; Inside Serrated Tweezers Anti-Acid

Precision Strongthick Tweezers, Ven

- Manufactured from high grade anti-acid, anti-magnetic stainless steel
- 10 point styles available



MPN: 00DSA



198-7273 Noga S Blade Deburring Tool for S20

3M Hookit Disc 255P Dia 150 P240 · C-weight paper backing gives good mineral support

- . Longer product life and sustained cutting action
- 3M Hookit fixing system
- . Can be attached and reattached as many times as necessary
- · Enhanced antiloading coating to extend product working life





MPN: S 20



HK\$203.09

RS Pro 120 mm Anti-Magnetic Stainless Steel Strong Thick Tweezers Anti-Acid

Strong Tip Precision Tweezer, 120mm

- . ESD safe for secure use in electronics assembly High quality Swiss workmanship
- · Anti-acid, anti-magnetic stainless steel for durable performance



HINDSTROM

476-8249 Bahco 120 mm Anti-Magnetic Stainless Steel Flat MPN:TL 00-SA SL Tweezers ESD Anti-Acid

HK\$9744

Visit hken.rs-online.com to order today!

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

806-4800 3M 150mm Very Fine Aluminium Oxide Deburring & MPN: 255P HOOKIT DISC 150 P240 6 Holi

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

HK\$390.00

HK\$211.15

HK\$257.50

Precision Tweezers

- · Low carbon austenitic steel
- Non-magnetizable
- Good corrosion resistance to most chemicals, salts and acids
- . Generally used where corrosion resistance and toughness are primary requirements
- · Ideally suited for use in moderately aggressive chemical environment



Precision Cutter

- Very high quality drop forged steel pliers
- and cutters for precision work Manufactured with carefully aligned edges
- · All types incorporate return springs and plastic covered handles to ensure maximum ease of use



(C) ideal-tek sa

Heat stabilized

666-0992 Idealtek 140 mm Anti-Magnetic Low Carbon Austenitic Steel Extra Fine Tweezers Anti-Acic

MPN: SS.SA

- 160mm Cable Cutter • Can cut Copper/Aluminium cables
- The forged surfaces are phosphated and the head mirror polished

Flush Type Cable Cutters, 115mm Overall Length,



· Good heat capability

. Good chemical resistance (oils, grease, fuels, non polar solvents): not resistant to strong acids, alkalis and hot water or steam

Precision Esd Plastic Tips Tweeezers

Very high rigidity, excellent tensile and flexural

strength, fatique and creep resistance Low friction, self lubricating properties,

excellent wear and abrasion resistance



Tweezer Set

666-1083 Idealtek 130 mm Anti-Magnetic Stainless Steel; Plastic Tipped Fine Tweezers ESD

MPN: 259CFSA

254-232 Cable Cutter

MPN: 2233D 160

MPN: 2101G-180

Ergonomic Cutters

- · Chrome-vanadium steel iaws
- Ergonomically designed non-slip hand grips Unique integral return spring with on/off function
- giving option of approximate 15° return
- To ISO 5749



Straight fine point: 115mm, sharp serrated jaws Rounded point: 115mm, blunt tapered jaws

· Long crossover point: 165mm, flat point, self-locking jaws Bent fine point: 150mm, bent pointed jaws

• General purpose nickel plated steel tweezers

supplied as a 6-pc set in a handy vinyl wallet.

· Crossover fine point: 115mm, self-locking jaws . Stamp tweezer: 115mm, blunt 'spoon' nose jaws



Available in small (10 - 16mm) or large (19 - 32mm) sizes

618-8386 RS Pro 6 pc Nickel Plated Steel Tweezer Set



Wire Spool Racks Durham

- · For storing and dispensing reels of wire
- . Supplied with 4 adjustable height position hanging rods
- Powder coated 2 tone grev finish
- Clip together assembly no tools required
- Extension units available to create double height rack by stacking two racks together





612-5206 RS Pro 19 -> 32mm Chain Rivet Extractor

Rivet Extractor Large

303-4602 RS Pro Steel Cable Storage Rack, 943 x 152.4 x 663.6mm 4 Shelves

Ultra Small Smd Tip Cutter, 145mm L

400-6103 Tip Type Cable Cutters, 144mm Overall Length,

- Ultra sharp cutting edges hardened to 60 HRC Relieved head for good accessibility
- · Long slim jaws for extra reach
- Flush cutting

MODETROM

• For replacement springs see RS 228-8088



HK\$1.664.04

MPN: RX8237

Adjustable Cable Rack

- For storing and dispensing reels of wire
- Supplied with 4 adjustable height position hanging rods Powder coated brown/sandstone finish
- Clip-together assembly no tools required





RS Pro Steel Cable Dispenser, 985 x 896 x 990mm 4 Shelves

HK\$1,648.32

HK\$1.019.90

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



Automatic Wire Stripper, 1-3.2mm Strip

- Simple-to-use stripper which cuts and strips insulation from range of wire sizes in one operation.
- Single squeeze of handles opens and closes the synchronised iaws and strips insulation cleanly from conductor.
- Suitable for use with PVC, silicone rubber and others



RS Ratchet Crimper

- · All RS crimp tools are compatible with some the
- RS range of red, yellow, and blue terminals. Range Compatibility/Tooling Detail
- Tool has no adjustment facility and is not suitable for calibration
- Note: Unsuitable for un-insulated terminals, or mini vellow size



RS Pro Automatic Wire StripperFor Use WithPVC Wire, 165mm Overall Length

3 Action Cable Stripper, 4.5-29mm Strip

- · Professional heavy-duty cable strippers with unique spiral-cutting facility
- Rotary, linear or spiral cut
- . These tools embody unique spiral-strip selector for hard-to-strip insulations like butyl, rubber etc
- The PTFE blade housing, combined with an ultra sharp blade, greatly reduces friction for smoother stripping



HK\$400.00



- Specially contoured comfort grips reduce operator fatigue
- Special Lock Lid Design for easy storage





RS Pro ROT29RTGRS01/001 Cable Stripper 4.5 -> 29mm For Use With Round Wire 262-0151

- Solid Metric Cable, T-Stripper, 6Sq.mm Two knife blade strippers for use on metric cables
- The precision ground blades ensure a clean, precise cut Lightweight, with cushioned plastic grips,
- · All steel construction

243-106

243-257

Corrosion resistant; spring loaded for automatic opening



RS Manual Wire Stripper

- · Two high quality wire strippers featuring light weight corrosion resistant frames.
- Single-step wire stripping action
- Spring lever mechanism reduces operator fatigue





Ideal Industries 45-120-341 Cable Stripper For Use MPN: 45-120-341 HK\$145.86

RS Automatic Wire Stripper

- Professional fully automatic self adjusting wires stripper
- for use with round, oval and fat wire and cables Precision carbon steel laminated stripping blades
- Compact pistol grip design for increased

NEW SWINGO wire stripper

designed for smooth, effortless cutting.

· Very easy blade change. • Stripping length: 3 2 18 mm.

• Weight: 136 g

= FACOM

The New Swingo wire stripper can be used for

cutting or stripping all PVC wires, with a mechanism

· Adjustable stripping depth for different applications.

. Jaw force can be adjusted to suit temperature conditions

• Single-strand wire: 1.5 mm²/Multi-strand wire: 10 mm².

control and a smooth stripping action Adjustable sliding wire stop to preset exact stripping lengths

RS Pro Automatic Wire Stripper 10 → 24AWG For Use With Flat, Round Wire

- · Shielded cutter for safety
- · Constructed from high grade polymers and Carbon Steel for durability and long tool life



· Self adjusting with hardened steel blades.

- · Integral wire cutter (for single wires), stripping
- Replacement stripping jaws are available (RS 613-050)





RS Pro Automatic Wire Stripper 0.2 → 6mm For Use With Round Wire, 170mm Overall Length

Automatic Wire Stripper

- Professional TE Connectivity hand operated wire stripper with retractable jaw. For use with PVC, THHN and THHW Wires.
- . 3 seperate thickness adjustment Thin, Normal and Thick
- Strip wire ends up to 16mm
- Simultaneously strip ribbon cable
- Overal Dimensions 193 x 103 mm



782-3276 TE Connectivity 734185-1 Cable Stripper 28 →

MPN: 734185-1





HK\$1.058.00

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Facom 793936 Cable Stripper 0.02 → 10mm² For Use With Multicore, Single Core Wire

MPN: 793936





Wire Strippers

- Wire strippers with knife blades to ensure clean, accurate stripping











Automatic (pistol style) Wire Stripper

length adjustment and jaw tension control.










HK\$963.05









TOOLS & STORAGE

Precision Balance Es-303Ha. 300G/0.001G

- Stainless Steel plate for easy clean and durability
- High precision strain gauge load cell
 Large, easy to read LCD display with blue backlight
- · Parts counting function

3000G/0.1G Easy 2 button operation

Parts counting function

Auto-calibration function

Auto-zero tracking

 Leveling bubble and adjustable feet for fine adjustment and accurate settings of the sc

Electronic Balance Es-3000A,

High precision strain gauge load cell

Large, easy to read LCD display

Sealed panels for added protection

Stainless Steel platform for easy clean and durability



HK\$2,354.10

Standard Organiser Case

- Seal tight lid and compartment latch keeps
- heavy components in place Moulded comfortable grip handle





RS Pro Weighing Scale, Bench, 300g Capacity Type

Stanley 25 Cell Grey, Transparent PP, Adjustable Compartment Box, 81mm x 457mm x 330mm

MPN: 1-92-762

RS Ultrasonic Cleaning Tank

cleaning and removal of dirt, grease and corrosion

High quality Ultrasonic Cleaning Tank for the

from both mechanical and electronic parts.

. Removes Dirt. Grease. Corrosion and can be used on Electronic & Mechanical parts

Degas mode rapidly removes air from the fluid

Tank, lid and housing made from stainless steel

· Delicate mode which is less aggressive at half power Full-power mode for a powerful deep clean Temperature and Timing mode

after changing for maximum cleaning

Ball Jointed Articulated Mirror

- Designed for working in awkward and confined spaces Double ball joint hinged stem with a screw-on mirror head
- and a screw-on magnet attached to the base of the stem
- Chrome-plated mirror head & stem





RS Pro Weighing Scale, Bench, 3000g Capacity Type G - British 3-pin

544-998 RS Pro Inspection Mirror Probe, Adjustable

HK\$426.16

HK\$112.05

Hanging Weigh Scales, 50Kg

- Adjusting program (CAL)
- . Stainless steel snap link with safety catch and 15 mm aperture
- . Up to 200 kg weighing range
- TÜV certification
- Tare function
- Data hold function for easy reading of weighing results
- Stainless steel S-hook with 25 mm aperture
- 12 mm LCD



RS Video Inspection Camera Kit

- · Professional and high quality video boroscope that makes it easy to inspect hard to reach and hard to see areas and equipment. Excellent for automotive applications, i.e. internal inspections and reading stamped identifications etc.
- 1/9in VGA CMOS Sensor with 640 x 480 Pixel Resolution
- Lens Outer Diameter 8.0mm
- Flexible Gooseneck Outer Diameter 6.5mm
- Water Proof IP67
- Upside Down Screen Function
- Conveniently Powered by AA Batteries



HK\$1.097.07

KERN

700-7064 Kern Weighing Scale, Hanging, 50kg Capacity

Kern Weighing Scale, Pocket, 320G Capacity

700-6957 Kern Weighing Scale, Pocket, 320g Capacity

 30kg pocket spring balance calibrated in lbs and kgs with brassed scale and tinned hook and ring

Pocket Spring Balance W/Hook & Ring,

- Balance protection provided by robust hinged cover
- Electronic pocket balance with lid
- Tare function

KERN

30Kg

• Weighpan dimensions: 80mm x 70mm



MPN: HCB 50 K 100

images & videos wirelessly Rotatable camera head enables you to run

inspection 360° without dead angle Waterproof-Weatherproof-Shockproof

RS Pro Wireless Endoscope

· Wireless solution lets you record or view

- flexible gooseneck and camera.
- Shaft can be exposed to water IP67
- Four LED's with brightness control, illuminates dark areas to be inspected
- . Extendable gooseneck max, 30 meters
- · Detachable monitor Powered by 4 x AA battery (excluded)
- Monitor plays the captured images and
- recorded videos independently.
- . 2.4G RF wireless connection between screen & main unit
- · Recordable function, with Micro SD slot



913-1560

RS Pro 8mm Probe Inspection Camera, 88cm Probe Length, LED Illumination

RS Pro 8mm Probe Video Recording Inspection Camera Kit, 880mm Probe Length, LED Illumination

HK\$2,508.80



288-4793 CK Spring Balance, Metric Scale, 30kg Range

MPN:T6202 066

MPN: CM 320-1N





Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

41

855-5915 RS Pro UT8061 Ultrasonic Cleaning Tank, 300W, 6L with Lid

HK\$6,395.56

Coloured Steel Kick-Steps

- Available in black, red, blue and light grey
- . The step/stool provides easy step up access preventing excessive stretching.
- Retractable spring mounted castors for easy
- and safe access without bending . Steel constructed with anti-slip rubber treads and base surround
- . Rubber base ring locks to the floor preventing
- slide, roll or tipping over
- High quality steel
- Overall height (compressed) 400mm
- Load capacity 150k





Hop Up Platform

- · Lightweight work plaform ideal for low level jobs. Steel locking hinges
- · Lightweight yet durable
- · Compact when closed
- · Easy to store & transport







HK\$490.86

HK\$525.40



HK\$1,919.13



Choose quality, performance and value without compromise.

Decisions have consequences. Making the right choices can improve the efficiency and productivity of your entire organisation.

Because every decision matters, every part matters. That's why RS Pro gives you everything that matters - quality, performance, choice and exceptional value for money.





000





Find out more hken.rs-online.com/RSPro



CONSUMABLES & SAFETY

MPN: 2500.10.055.0

CONSUMABLES & SAFETY

Energise to Hold

- These RS electro-permanent magnets are energised to hold and de-energised to release.
- · Typical applications include: machine mechanisms, door guard locking and remote hold/release requirements.
- Optimum performance when used with RS armature plates (available separately): please see stock no 739-3211 etc.
- Energise to release version available on example 739-3220

Thermostatic Tubular Heater 1Ft 40W

RS Pro Access Control Door Magnet, 1000N DC, 24V

815-9298 40W Tubular Heater, Floor Mounted, Wall Mounted MPN: COT1

- 12 and 24 vdc versions have a 2 pole connector
- . 12 and 24 vdc versions are IP20 rated
- 240Vac versions have a Din 43650 connector

· Reversible left or right hand cable entry

. Optional interlinking kit for stacking purposes (see RS stock No. 815-9309)

· Discreet mounting brackets for walls or floors

. Body diameter 57 mm

· 230Vac mains operated IPX4 rated

• 240Vac versions are IP54 rated



150X30mm

• Length 3m Width 150 mm

• Depth 30mm

· Material 304 Stainless Stee



ш....

HK\$577.83

CABLOFIL

770-7060 Wire Cable Tray, 304 Stainless Steel 3m x 150 mm x 30mm

Lightweight Energy Chain, 119X35mm

Secure fit of interior separation even when Energy Chain® is open

lgus 2500, e-chain Black Igumid GLW Cable Lightweight Chain Trunking, W119 mm x D35r L1m, 55 mm Min. Bend Radius

Cable Basket Tray Stainless 304

· Snap-open mechanism opens left or right

Easy opening and closing

Hinged crossbar can be swivelled more than 180°

MPN: CF30150I304I

Ip67 Liquid Tight Pa Conduit, 20mm

· Halogen free

10M L

Offer resistance against chemicals and oils

Non Flame propagating to EN50086

UV resistant



9Kw Portable Fan Heater 3 Phase

- Multistage temperature control with up to 3 heating stages
- · Integrated room thermostat for consistent warmth
- Overheat protection
- · Fan motor with thermal protection
- Easy transportable and easy to use



HK\$447.23

Adaptaflex PAFS Polyamide 6 Flexible Conduit Black 21mm IP40, IP65, IP66, IP67, IP68, IP69K 10m

839-5283 RS Pro 9kW Fan Heater, Portable

Damper Actuator Modulating, 5Nm, 24VAC/DC

- Minimum life of 60000 operations
- · Stall torque technology requires no end switches
- Adjustable U-clamp accepts round or square shafts
- Visible position indicator · Pushbutton manual override
- · Direction change switch
- IP54 rated
- 150s motor run time



504-1220 Modulating Damper Actuator, 5nm, 24 V AC/DC

MPN: LM24A-SR

Standard Weight Pa6 Conduit 42mm 10M

- Highly flexible
- High impact strength and recovers if crushed
- Temperature range: -40°C to +120°C (-20°C to +100°C if moving)
- Llovds Register type approval UL listed/UL recognised
- Low fire hazard (LFH) UL 94 V2 flame retardancy
- · Halogen, sulphur and phosph

FLEXICAN

Flexicon FPAS Nylon Flexible Conduit Black 42mm IP66, IP67, IP68, IP69K 10m

MPN: FPAS42B-10M

2 Part Lightweight Flexible Conduit 25mm

- Trouble free retro fitting
- Can be opened and closed time after time in longitudinal direction. · Easy installation
- PMA fitting available
- · Also applicable for repairs
- · Self extinguishing
- · Choice of material: lightweight polypropylene



762-1556 PMA PPCOF PP Divisible, Flexible Conduit Black

MPN: PPCOF-23B

HK\$1,389,89

HK\$1.055.00



1 0

Consort Dado Trunking, 100X50mm 3M

- Single Three compartment conversion is possible for segregation of power, data and telecommunication with the optional dividers, they clip into any of the three divider bases
- Clip-in fully segregated 1 and 2 gang socket mounting boxes can be positioned



White Moulded 1 Gang Rcd Socket, 13A

- · Switched Sockets White Plastic Moulded
- Single or 2 gang sockets, available with passive circuitry.
 Standards: BS7288; BS1363
- Power Breaker RCDs
- Providing protection against electrocution
- Double pole switching on all types
- Trip Current 30mA
- . All terminals are in-line with captive screws for ease of installation
- loss of earth and neutral and reversed supply polarity



MPN: CT105

HK\$1,144.50

Trunking 75X75mm Closed Slot 2X2M Noryl

Schneider Electric Consort White uPVC Cable Trunking Dado Trunking, L3m

- · Limited Fire Hazard electrical trunking
- Self-extinguishing Noryl Extra™ to UL94-V0 flammability rating
- · Halogen free
- Very low smoke

Schneider

315-1460

- · Black in colour
- · Available in 1 or 2 metre lengths




803-7417

Betaduct Black Noryl Closed slot Cable Closed Slot Trunking Slotted Panel Trunking, W75 mm x D75mm, L2m

Blk PVC Closed Slot Trunking25X20mm 1M L

- · Ideal for use in cabinets and control panels
- Snap-on lid
- Closed slots, height (H), width (W) and pitch (P) as shown
- Pre-punched fixing slots to DIN 43659 for ease of chassis mounting



ΛBL

Bs Din Rail Mounting Modular Socket

- · Available in various world socket standards
- · Quickly connected
- · Colour Grev
- Power loss 0.6W per pole



HK\$168.32

HK\$68.12



547-701

Betaduct Black PVC Closed slot Cable Closed Slot Trunking Slotted Panel Trunking, W25 mm x D20mm, L1m

RS Pro Isolated DC-DC Converter, Vin 19 → 36 V dc,

HK\$129.34

ABB 1 Gang Unswitched Electrical Socket, Type G - MPN: M1363 British, 13A, DIN Rail Mount. IP20. IP30

RS Pro 25W Single Output Enclosed Regulated Isolated DC-DC Converter High reliability

- Wide 2:1 input voltage range
- · Regulated outputs
- · Easy installation screw terminals
- Adjustable output voltage EMC meets EN 55022 Class B
- LED power-on indicator
- · Short circuit, overload and overvoltage protection
- 1.5kV input/output isolation



ΛBL

Junction Box Grey Masterseal+

- 16 terminal junction box
- Each terminal block accepts four 2.5mm² cables
- . Knock out cable entry on each side
- 250Vac



Hyblade Axial Plate Fan 450mm 230V

- HYBLADE® impeller construction consists of an aluminium supporting structure and a cladding or sleeve made of fibreglass-reinforced plastic in black
- IP54 protected S1 operation mode
- Ball bearing motor



CONSUMABLES & SAFETY

705-1709

IP66 Junction Box M20 Knock out, 4 Terminal, 95 x MPN: K56506GRY 95 x 65mm. Grev

- **Emergency Spotlights** Optional' - Switch for testing emergency mode
- Powered by 2 x 6V 12Ah batteries (not supplied)
- Battery cut-off prevents deep discharge
- LED indication of battery charge status • Alarm output contacts (0.1A max.)
- · Supplied with full instructions



HK\$189.54

ebmpapst

767-3790 490 W, 650 W Plate Fan, 450mm, 230V

Simply Silent Round Extract Fan Round shaped fascia

- Near-silent fan and airflow
- . Long life fan motor ball bearings
- · Optimised fan impeller design and flow straighteners
- · Simple installation
- Compliant with Part F and Part L building regulations
- IPX4 rated, suitable for installation in bathr



MPN: W4E450-DO09-21 HK\$3,146.50



Emergency Light Fitting 2 x 21 W Halogen 315 x 310

Fan Speed Controller 230Vac 5 Amp

- General purpose high power fan speed controller
- Separate on/off switch and variable speed control
- Internal adjustable preset for minimum speed (factory pre-set to 20%)
- Suitable for 2 or 3-wire control



HK\$1.531.83

HK\$802 90

Xpelair

829-8832 Xpelair 92961AW Simply Silent for Extraction

MPN: 92961AW

MPN: FTR 1207

Thermostat Ftr 1207

- Thermostats to protect against freezing, in a plastic housing for use in damp environments.
- The FTR-E3121 is an electro-mechanical frost monitor, whereas the FTR 1207 is an electronic thermostat with indoor and outdoor settings.
- Settings on front panel

EBERLE



HK\$622 93

HK\$1,568.33

HK\$2,760,30

ebmpapst

328-9098 Fan Speed Controller, Variable, 230V, 5A

High Velocity Cooling Fan Free Standing

- High Velocity Cooling Fan
- · Features and Benefits Quality high velocity 3-speed floor fans
- Rugged chrome plated metal frame and grille for commercial use
- Plastic feet provide stability on any surface
- Lightweight aluminium fan impellers
- · Fan can be tilted backwards from vertical to act well as an office air circulator

· Compact design for use in confined spaces

Galvanised steel housing with Class 1 earth

. Outlet quide vanes straighten air flow



MPN: REE 50

Ip65 230V 130W 6000K Led Floodlight

509-0761 Mechanical HVAC Thermostat, Eberle FTR 1207,

- Finish Black
- . LED colour 6000K day light Die-cast aluminium casing
- Class I
- IP44 rated
- Average life 25000 hours • 120 degree PIR sensor, up to 8 metre range
- Comes with 300 mm cable





320W

700-1439

RS Pro, Floor, Heavy Duty Fan, 5100m³/h, 450mm Blade diameter, 3 Speed , 230V, With Plug: Type G - British 3-pin

Centrifugal In-Line Duct Fan, Xid315

Maintenance free motor, totally enclosed with thermal protection

On/Off and variable speed controller with mains indicating light

HK\$457.01

Knightsbridge FLS LED Floodlight, 130 W, 11600 lm, MPN: FLS130BK

Ip65 230V 70W 6000K Led Floodlight

Black • Finish Black

• LED colour day light Die-cast aluminium casing



 IP65 rated Average life 25000 hours Comes with 300 mm cable





876-5152 Knightsbridge FLS LED Floodlight, 70 W, 6700 lm, MPN: FLS70BK

Visit hken.rs-online.com to order today!

· Twin earth terminal

Detects pulsating default currents to protect electronic equipment

PowerBreaker

Power Breaker 13A, BS Standard fixing, Passive, Single Gang RCD Socket, Polycarbonate, Surface Mount, Switched

MPN: K21WP-C



- Black Material PVC
- Screwed terminal connection type
- · Child safety protection





- 824-5655 ABL Sursum 1 Gang PVC Electrical Socket, NEMA MPN: UL12500 5-15R 15A Panel Mount 1P44





Bs1363 Panel Mount Socket lp54 Black

- Screwed terminal connection type · Child safety protection
- Cover lid IP54 rated

Material PVC





ABL Sursum 1 Gang PVC Electrical Socket, Type G - MPN: BS13630 British, 13A, Panel Mount, IP54



184-4889 In Line Duct Fan, 315mm






Xpelair

MPN: 90106AA

HK\$2,430.40





Anti-Corrosion Fluorescent Fitting

- IP66, dust tight and water jet proof for stay clean operation
- · Prismatic diffuser for optimum light distribution and glare reduction
- Glass reinforced (GRP) body
- · Polyurethane gasket
- UV stabilised prismatic acrylic diffuser
- Stainless steel clips (supplied)



FAT-N

18 W Fluorescent, Ceiling Light, Batten Tubular, 2 Lamp, Anti-corrosive, 665 x 145 x 101 mm

MPN:TFC6218S

LED Mains Strip Light • Ultra-slim, low profile, linkable, low power LED strip lighting

- available as a direct replacement for existing T4 fluorescent lighting.
- Low power consumption Up to 10 years continuous operation
- Cool running
- · Integral on/off switch
- · Internal fuse protection
- . Easily "daisy chained" together using link cables (available separately, see Note)



720-3827 RS Pro 12 W LED Strip Light, T4, 230V ac, Cool

HK\$351.87

Output

340-0239 IP66 Orange 3P Industrial Power Plug, Rated At 13A, MPN: 56P313EO

HK\$98.80

HK\$925.29

Adjustable Arm Long, Machine Task Light, 12V . This RS branded task light features an IP65 rated, totally

- enclosed lamp head, which provides protection against dust, coolants and swarf. The halogen machine light comes with a built-in adjusting handle and the On/Off switch on the head. This Task light is suitable for most industrial uses like factories, assembly shops and workshops.
- High power halogen machine lights for industrial use, ideal for use in fixed positions
- Die cast head protected to IP65
- Reinforced glass cover
- Fitted with anti-glare louvre
- On/off switch on head along with adjusting handle
- Fitted with a 1.8 metre lead without plug



433-3051

RS Pro Halogen Machine Light, 24 Volts, 70 W, Adjustable Arm, 830mm Reach, 830mm Arm Length

HK\$1.076.88

RCD Safety Adaptor

- 13A RCD safety adaptor offering the user added protection against electrocution
- Double pole switching isolates both live and neutral when contacts trip
- This RCD adaptor will continuously monitor the power supply to an electrical appliance and will cut the power

within 40 milliseconds if an earth current fault is detected



RCD Plug 2 Pole ,Tripping Time 40ms, Tripping Current 30mA,Rated At 13A,240V ac

HK\$200.29

Premier Open Reels - B\$1363

- Professional range of JOJO cable reels that are made and
- tested to the highest standards and flash tested at 4000V. Due to the characteristics and design of the cable reels, it makes them ideal for daily, rigorous use. Suitable applications would include power tools, vacuum cleaners and lighting.
- Open reels with metallic stand and handgrip
- Integral thermal cut-out for safety
- Flash tested to 4kV PVC cable to BS6500
- · Current rating 13/16A fully unwound

Schneider

470-8219

50m Extension Reel Type G - British,4 Socket ,Unwound Current Rating 13A,240V

MPN: JJR45013

13A Plug


- Unique screwed ring secures to socket outlet maintaining IP66 rating
- Fitted with 13A fuse



Schneider

200W and 320W, Universal Input, Single

- High efficiency, long life and high reliability Built-in constant current limiting circuit, suitable
- for battery charging SP-200 series only
- Built-in fan with speed control Remote ON-OFF control, SP-200 series (optional), SP-240 (built in)
- LED indicator for power on
- · Easy installation screw terminals
- · Adjustable output voltage
- . Short circuit, over-load, over-voltage and





644-8127 RS Pro 201.6W, 1 Output, Embedded Switch Mode Power Supply (SMPS), 24V dc, 8.4A



3000W Single Output Power Supply RSP-3000 Series

- AC input 180 to 264Vac
- AC input active surge current limiting High efficiency up to 90%
- Built-in active PFC function, PF>0.95
- Protections: Short circuit, Overload, Over
- voltage. Over temperature. Fan alarm
- Forced air cooling by built-in DC with fan speed control function
- Output voltage can be trimmed between 20
- and 110% of the rated output voltage
- High power density 15.6W/in³
- . Current sharing up to 3 units Alarm signal output (relay contact and TTL signal)
- Built-in 12V 0.1A auxiliary output for remote control
- Built-in remote ON-OFF control
- Built-in remote sense function

RS Pro 3000W, 1 Output, Embedded Switch Mode Power Supply (SMPS), 24V dc, 125A

HK\$5,974.65

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



CONSUMABLES & SAFETY

Cold Room Cont 30A & 8A/2Hp Ir Rtc

Carel MasterCella PID Temperature Controller, 200 x 240mm, 2 Output Relay, 115 -> 230V ac Supply Voltage

Incoloy Sheathed Water Heater, 3Kw

• 3 phase, 4-wire, 415V or single phase 240Vac

· Hoseproof polypropylene terminal enclosure

• 2 1//4 in. BSP threaded brass heads

which can be rotated in any position

· Fitted with thermostat and jointing gasket

- . Compliant with HACCP 9%3/EU
- . IP65 rated panel for humid environments
- · Complete cold room control

CAREL

813-4271

11In

- Manage the end defrost completely and independently. Manage the condenser fans using the auxiliary output
- Signal the high temperature alarms and the need for m



MPN: MD33D5EB00

Plug

Heavy duty anodized aluminum body with textured grips

Stanley Fatmax 70 Lum Torch R/Ch Eu

- Specially designed reflector provides a strong focused beam
- Shatter resistant lens · Hi-visibility vellow bands
- Weather resistant
- Wrist band included



STANLEY

679-6029

Stanley FatMax FatMax 1 x NiMH, LED Torch

- The H7R.2 is brighter, smarter, more durable and more comfortable
- At Low power setting (20 lumen) the H7R.2





RS Pro 3 kW BSP Thread Tank Heater, Incoloy Heating Element, Thermostat Included, 220V ac

- Tikka Headtorch Blue Victoria · Headlamp keeps the hands free
- Two lighting modes adapt to each situation (mode
- favouring burn time and mode favouring brightness)
- · Push-button for easy, quick lighting mode selection . Phosphorescent reflector allows the lamp to be located in the dark



HK\$1,974,70

HK\$484.61

LEDLENSER.

3Rd Generation 2 Cell D Led Flashlight

- Low power 143 lumens, 20 hour runtime
- Multi-mode electronic switch located near the head of the light



MPN: 7298 - H7R 2

MPN: ST23016L

MPN: 907660

PETZL

812-5400 Petzl TIKKA E93HNE, 1 x AAA, LED Head Torch,

- Atex Led Headtorch, Zone 0 High Power LED spot beam (approx 22°) Peak luminous
- intensity at 1m 493 lux, at 2.5m 67 lux
- Extra wide angle fringe beam (approx 100°) Peak luminous
- Intensity at 1m 32 lux, at 2.5m 8 lux . Zones 0. 1 and 2. Gas groups IIA, IIB, IIC

· High impact thermoplastic



872-4868 MAGLITE ST230 ST23016 2 x D, LED Rotating

Stainless Steel Folding Bracket

- · Good anti-corrosive properties
- Locking device for open position with pull release





Advanced focus System[™]

· Recalculated reflector lens

Dynamic tactical tail cap switch

· Matte black "frozen black" texture

. Light output: 280 lumen max., 25 lumen min. . Maximum visible beam range 220 metres

769-2741

Wolf Safety HT-650, 3 x AA, LED Head Torch, ATEX. MPN: HT-650

MPN: E93HNE

HK\$1.128.40

497-9310 Stainless Steel Folding Bracket, 305 x 165mm

Ball Spring Plungers Ideal for applications where a pre-defined positional stop is required or positioning a workpc against a datum face

 Threaded body has a screwdriver slot Available in either a black oxide finish or stainless steel. Both have a retained hardened steel ball

Black oxide supplied 10 per bag, stainless steel 5 per bag



LEDLENSER

853-1745 Led Lenser TT 9804, 3 x AAA, LED Torch, Aircraft MPN: 9804

Led Lenser Tt Police Tactical Torch

HK\$479.49

478-567


RS Pro Stainless Steel M4 Spring Plunger, 9.8mm














HK\$1.011.63

HK\$694.30

792-4228 Led Lenser 7298 - H7R.2, Lithium Ion, LED Head Torch Rechargeable, Dimmable, Aircraft Grade





• Eco (super low) 58 lumens, 69 hour runtime





· Budget alternative to gas springs





HK\$1,722.95

Adjustable Eccentric Latch W/ Catchplate

- · Eccentric latch complete with catchplate
- Adjustable hatch clamp with security lock
- Good anti-corrosive properties
- · Stainless steel construction
- Suitable for food, chemical and other 'clean' industries



Wypall X70 Cloths, Quarter Fold Pack

- High Velocity Cooling Fan
- Features and Benefits
- Quality high velocity 3-speed floor fans
- Rugged chrome plated metal frame and grille for commercial use
- · Plastic feet provide stability on any surface
- Lightweight aluminium fan impellers
- Fan can be tilted backwards from vertical to act well as an office air circulator



Kimberly Clark Bag of 76 White WYPALL X70 Multi-purpose Wipes for Various Applications MPN: 8387

Unex Brass (Bolt), Stainless Steel Hose Clip, 11mm MPN: 9930 Band Width with Thumb Hex Head

Locking Pin Type S/Steel Toggle Latch

Stainless Steel Electro Polished Toggle Latch, Lockable, Lock not included, 75 x 26 x 15mm

- · Assembly rivets and compression springs made from stainless steel 18//8
- Suitable for screw fixing, using M3.5 screws or welding
- Supplied with dimensions template for marking out
- Operating tension 30kgf
- · Latch to catch distance 48mm



Unex Hexagon Head Hose Clip, 14-19mm Dia

- 11mm wide A2 grade stainless steel (304 S 15) band & CZ131 brass screw
- Corrosion resistant and suitable for use in laboratories, R&D
- facilities, dispensing & vending equipment and engine test areas

 Capable of sealing flexible hose onto thin-wall glass tube



186-1553	Stainless Steel Toggle Latch, Lockable, Lock not included, Spring Loaded, 30kgf Op. Tension, 57.5 x	MPN: 40013 IB	

Stainless Steel Toggle Latch

- · Wide positioning tolerance created by the spring mechanism
- Failsafe design prevents over extension of links
- Operating tension is 20 kgf when distance between Catch fixing. hole centres and the furthest Latch fixing hole centre is 63.2 mm
- Maximum operating tension is 30Kgf



Znpt Ms Worm-Drive Hose Clip.

- Standard worm-drive hose clips to BS5315 available in either BZP steel or A2 grade 18//8 stainless steel
- Clips are marked with BS kitemark and appropriate BS size number
- Clips are 13mm wide, except for 12-20mm sizes which are 10mm wide
- 7mm slotted hexagon

25-35mm



Dino-Lite

HI-GRIP Steel Worm Drive Hose Clip, 13mm Band MPN: HGZ35BP

HK\$34.55

HK\$90.00

Macor Glass Ceramic Rod Stock,

Stainless Steel Toggle Latch, Spring Loaded, 30kgf Op. Tension, 53 x 35 x 17mm

- 100X20mm • For the manufacture of precision components
- utilising ordinary metalworking tools
- No post firing required
- Non-wetting, 0% porosity and no deformation
- Max no load temperature: 1000°C • Continuous operating temperature: 800°C
- · Machining tolerances approach 0.013mm



Unex Screw Slotted Hose Clip, 9.6-14mmdia 11mm wide A2 grade stainless steel (304)

- S 15) band & CZ131 brass screw Corrosion resistant and suitable for use in laboratories, R&D
- facilities, dispensing & vending equipment and engine test areas
- Capable of sealing flexible hose onto thin-wall glass tu



Machinable Glass Ceramic Rod, 100mm x 20mm MPN: MROD 20/100

Wypall L40 Large Roll Blue X 1Roll

- Industrial Workplace Wipers & Cloths
- · A variety of high quality wipers and cloths for all
- industrial purposes, both light and heavy duty. · Wipers: Disposable
- Cloths: Re-usable




104 Piece Zinc Plated Pipe Clip Kit

Available in bright zinc plated steel or A2 grade 18/8 stainless steel

288-4103 Unex Brass (Bolt), Stainless Steel Hose Clip, 11mm MPN: 9939
Rand Width with Slotted Screw Head

- Supplied with TPE or PVC liners to prevent
- chafing of pipe, cable, etc.
- Temperature range -30°C to 60°C
- Available in individual sizes, or as a kit of 104 assorted clips in BZP steel



Kimberly Clark Roll of 750 Blue WYPALL L40 Multi- MPN: 7426

365-2294 JCS 104 pc Steel P-Clip Kit, Black Rubber Coating , 5 MPN: PCZRAB1 HK\$895.78

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Var Press Gasspring, 240mm L 10mm

- Custom design, sized to your application
- · Self contained unit and maintenance free
- . Safe to use with easy positional control
- Custom force setting with either fixed or adjust-vourself option
- Over 2,500 differernt combinations
- BS EN ISO 9001 Registered Company



Sealing Strip, PVC&Epdm, Wire Insert, 1-2.

- · Sponge Rubber/Steel Wire Insert
- insert. Applications include providing edge protection for sheet material e.g. door panels. May also be used to reduce noise and wear resulting from vibration




Camloc

234-455	Camloc Steel Gas Spring, 150 -> 1200N	MPN: SWV1080800027

S/Steel Ball & Socket Joint, M8X1.25mm

- · Ball joints for gas springs
- · Manufactured from grade 303 stainless steel
- · Easy installation
- · Maintenance free





Sealing Strip, PVC, Wire Insert, 1-2, 9X6.

- Black PVC with steel wire insert.
- Provides edge protection to sheet material and reduces noise and wear resulting from vibration.



Camloc

346-9597 Camloc Stainless Steel M8 x 1.25 Ball & Socket Joint MPN: 104333R

- **Ball and Socket Joints** Made to DIN71802 with zinc passivated finish
- · Induction hardened balls are wear resistant
- . Security clips retain ball studs in sockets . Static pull values for radial and axial loads
- · Supplied with locknut



- · Provides edge protection to sheet material and reduces noise and wear resulting from vibration.
- Temperature range -40°C to +90°C



689-417 RS Pro Steel M8 Ball & Socket Joint, 39.5mm x

- · Quick fit, two pc, flush fitting Low gloss black ABS plastic
- Suitable for lifting and pulling applications
- Panel thickness 1 1.8 mm



Sponge Rubber/Black PVC

- . Manufactured from PVC with embedded steel insert.
- bonded to sponge rubber sealing section (EPDM)
- Sealing pressure increases with closing pressure Can be used in unfinished rough edges reducing overall cost

619-1512 RS Pro PVC Black Sealing Strip, 20m x 12mm x 9mm

Panel thickness 1-4mm



HK\$1,298,29

HK\$561.76

southco

Screws supplied

227-0891







MPN: P1-31-RS

60±5 Shore A

- reduces noise/wear resulting from vibration.
- Material EPDM
- · Panel thickness 1.5 to 2mm





619-1635 RS Pro EPDM Rubber Sealing Strip, 15mm x 6.8mm



RS Pro Stainless Steel Concealed Fixings Handle, 129mm x 30mm x 9mm 120mm

Black soft sponge rubber sealing strip with steel wire





HK\$911.30

HK\$461.89



Temperature range -40°C to +90°C















Two-Part Panel Flush Handle, 123mm L






HK\$62.00











Sponge Rubber/Steel Wire Insert

- Black soft sponge rubber sealing strip with steel wire insert.
- Applications include providing edge protection for sheet material e.g. door panels. May also be used to reduce noise and wear resulting from vibration



Ambersil Food Grade 32 Hydraulic Oil

- Fully synthetic, premium hydraulic oil
- Excellent resistance to water (ASTM D 1401)
- Good anti-corrosion properties
- Excellent materials compatibility • Wide temperature range: -50°C to +230°C
- Triple zero foam tendency (ASTM D 892)



HK\$1,686.18

619-1736 RS Pro Rubber Black Sealing Strip, 22mm x 10mm

Ambersil Hydraulic Fluid 6150009580, 5 L, ISO

MPN: 6150009580

304S/Steel Piano Hinge, 1020X60X2mm

Stainless Steel piano hinges without predrilled fixing holes



Calcium Silicate Plate, 300X295X6mm

- · Mechanically strong with good impact strength
- Will withstand thermal cycling without cracking/breaking (Should be dried by heating @ 150°C for up to 24hr.)
- Can be machined to a good finish without chipping or breaking using standard tools



PINET

347-8563 Stainless Steel Hinge, 1020mm x 60mm x 2mm

248-4630 Duratec 750 Calcium Silicate Thermal Insulating

MPN: DTEC 295/300/6

HK\$642.82

Bench Top Zero Volt Ioniser, 220Vac

- Steady state DC ionisation and patented Sense Feedback balancing
- Compact size
- · Rapid access maintenance
- Automatic balancing of ionisation system
- Equipped with audible and visual indicators for "Balance" and "Maintenance Required"
- Data acquisition ready



No Tool Circuit Breaker Lockout

- Panduit PSL Series Lockouts
- Panduit PSL series of lockout devices are designed for various applications. The compact and universal design of this series allows the lockouts to be fitted to a wide range of equipment. Constructed of rugged nylon and stainless steel that provides strength, durability, security and corrosion resistance



EMIT

684-2920 220V ac 1 Fan Bench Top Ioniser, 24.1 x 15.2 x 7.9cm MPN: 50670

847-9776

PANDUIT

1 Lock Nylon, Stainless Steel Circuit Breaker Lockout, MPN: PSLCBNT 11.18 (Thick) mm, 15.24 (Tall) mm Attachment Point

HK\$201.96

Wristband/Heel Grounder Test Station

- Essential for all electronic assembly areas
- · Ideal for multi operator use Requires a PP3 battery
- Supports ESD S20.20 and EN 61340-5-1 ESD control programme compliance



S/Steel Small Springload Folddown Handle

· Lie flat polythene grip handle





0.9Mx1M

· Switchboard matting

Tested to 15 kV rms

Slip-resistant fine fluted surface

. Made from extremely hard wearing rubber

733-996 Wrist & Foot ESD Test Meter **Elec Switchboard Safety Matting,**

Provides safety for operatives against electrical shocks

For use in front of switchboards and high voltage equipment

HK\$2,589.70

750-294 RS Pro Stainless Steel Carrying Handle

Plastic Strap Handle, Max Load 25Kg

- Max Load =25kg
- Captive screws included
- · Rear fixing
- Metal, plastic construction



50

471-6248 Black Rubber Anti-Slip Electrical Safety Mat, 1m x MPN: SM010031

HK\$1,361,72

750-187 RS Pro Plastic Carrying Handle

HK\$176.34

HK\$265.90

Thermoplastic, Metric Threads water absorption (1.5% max.)

- Resistant to most chemicals, UV light and
- Temperature range -20°C to +110°C (short term withstand +170°C)
- · Zinc plated steel, Brass or Stainless steel inserts



Esf130 Pcb Holder, 160X235mm 360Dea

- PCB Holder for placing components
- Max size 160x235mm
- Rotated through 360° in increments of 15°
- Spring clamp



702-7636 RS Pro Thermoplastic Knob. M6 x 20

Selfadhesive Writeon Label 'Serviced

- Self-adhesive vinyl cloth labels
- Pre-titled legends with write-on space · Use spirit based or ball-point pens, pencils or typewriter
- · Radius corners

Bv'

• Each label 38 x 15 mm



HK\$131.51

HK\$103.53


HK\$4,611.89

Weller

Edge Holding Pcb Support, 7.9mm H

162-8766 160 x 235mm PCB Work Holder, 12.9 x 6.4 x 3.5in MPN:T0051502599

- Can be quickly released by hand
- Material: Nylon 66
- Colour: Natural



MPN: EHCBS-5-01

HK\$1.054.48

450-6170 RS Pro Pre-Printed Adhesive Label. Quantity: 140

Liquid Dispenser, Dx250

Universal power supply with snap-on plug for worldwide use

- 2-line LCD dot marix display
- Digital timing from 0.008 to 99.999 seconds • +/- 0.001% timing repeat tolerances
- Adjustable vacuum driven 'suck back' to control tailing & waste



Touchntuff Medium Green Gloves, 100/ Bag

EHCBS-5-01, 7.9mm High Nylon Edge-Holding Locking PCB Support Pillar with 4mm PCB Hole and 4.75mm Chassis Hole

· Nitrile material

Richco

663-3283

- . Longer resistance time to a range of chemicals · 4x puncture resistance of similar latex gloves
- 3 x resistance to similar neoprene gloves
- Risk free Type I allergies contains no rubber · Easy to apply
- Strong grip in wet or dry conditions



METCAL

612-4130 Metcal DX-250 Material Dispenser

- **Bead Chain** Chrome plated brass bead chain
- 3.2mm bead x300mm long chain Supplied with either 2 clip ends 506-7323 or joiner ends 506-7339



MPN: DX-250

Ansell

261-6736 Ansell Nitrile Disposable Gloves, Size: 7.5 - M Green MPN: 92-600/075 Powder-Free x 100

- **3M Protective Coverall 4510**
- · Protects against dusts and liquid splashes Elasticated waist, ankles and wrists
- Two way zipper with storm flap
- · Low linting properties · Anti static coating on both sides



HK\$46.84

HK\$201.40

506-7339 RS Pro Brass Chrome Plated Chain

A1 S/Steel Aerotight (R) Stiff Nut, M3

- A1 grade type 303 stainless steel
- All-metal construction
- Allows use up to 300°C
- . Stay in position whether tightened or not Reuseable





770-3646 92 → 100cm Men's White Anti-Static, Dust Protection, Nuclear Resistant, Waterproof PE, PP Coverall

Safety Trainer, Krypton Series These DeWALT Krypton safety trainers are lightweight

- and ideal for light, clean industrial use. Steel toe cap
- Comfortable, anti-bacterial inner soles
- EVA/Rubber Outsole Non-metallic midsole protection
- SBP SRA Safety Rating



	M3, A1	

260-5815 5.5mm Plain Stainless Steel Aerotight Locking Nut,

HK\$153.76

797-5465 Dewalt Krypton Safety Trainers - UK 7, Steel Toe

MPN: Krypton/7

MPN: 4510 M

HK\$#N/A

Visit hken.rs-online.com to order today!

Visit hken.rs-online.com to order today!



Fahrenheit Goggles

- Soft PVC crystal frame with a wide support area all around the face to enhance comfort.
- Specially designed to fit with prescription glasses,
- dust mask or respiratory half-mask Aerodynamic shape with cylindrical lens
- for 180° of distortion-free vision
- · The benefit of DX coating is a lens that is anti-scratch, antimist, anti-static and has some resistance to chemical attack
- Meet the requirement of EN166:2001

Classic Line Spectacles

Optical class 1 lens for highest optical

Lightweight (22g) for maximum comfort

Adjustable lens angle, Wrap around style

Meeting the requirement of EN166: 2001,

Associated standards: EN170, EN172

clarity and extended wear time

Inclinable soft flexible temples



Ansell

863-4052

Ansell Latex Disposable Gloves, Size: 9.5 - XL Natural MPN: 69-210/095 Powdered x 1000

HK\$1,100.00

666-7707 Clear Polycarbonate (PC) Anti-Mist Vented Safety Goggles, Scratch Resistant, UV Protection

Strong polycarbonate lens, Anti scratch, anti fog coating

MPN: 71360-000001

MPN: 2820

Vyflex Seamless PVC Gauntlet, Size 10

- · Exceptional fit
- Fine knit seamless line
- · Abrasion resistance · Anatomically shaped
- · Good protection against oil, acids and other chemicals
- Reusable
- · Medium grip levels
- Latex free



BM Polyco Blue Chemical Resistant PVC Reusable MPN: P93/10 Gloves, Size: 10 - XL \times 2

3M E-A-RSoff™ Earplugs, 250Pairs

• These E-A-RSoft[™] earplugs from 3M reduce exposure

· Tapered shape that conforms quickly to most ear canals

to hazardous levels of noise and loud sounds.

• Extremely soft foam helps provide low pressure

· Suitable for all frequencies, including low frequency

inside the ear canal for increased comfort

3M™ 1100/1110 Earplugs

Tapered shape adjusts to most ear canals

· Brightly coloured for high visibility and spot safety checks

Soft disposable earplugs produced in

polyurethane for extra comfort

· Produced in hypoallergenic material

Tested to EN352-2:2002 and CE marked

· Produced in soft, slow-expanding

polyurethane foam for extra comfort



740-1450 3M 2820 Safety Spectacles, Anti-Mist, Clear

Style Hc600 Safety Helmet, White

- CE Certified to EN397, +/- 30°C, LD, 440V a.c, VDE +1000V a.c
- Robust ABS shell
- 8 Point Terylene head harness with comfortable terry towelling sweatband
- · Lightweight only 350g





HK\$66.62

3M E-A-R"

358-4141 Disposable Yellow Polyurethane Ear Plugs, 36dB, 250 Pairs

MPN: ES-01-001

378-7968 White ABS Helmet

MPN: 2007843

HK\$174.70

3M 8810 Dust/Mist Respirator FFP2 • Excellent comfort, Weight 8g

- Maintenance free and exempt from maintenance requirements of COSHH
- Assigned protection factor 10 x OEL (Nominal
- Protection Factor 12 x OEL)
- Meets the requirements of EN 149:2001 FFP2
- Suitable for use under COSHH, CAW, CLAW and IRF



Disposable Orange Polyurethane Ear Plugs, 37dB, MPN: 1100

179-3618 3M 8810 FFP2 Disposable Respirator, Adjustable

MPN: 8810

HK\$283 39

- DeWALT Protector eye protection with a lightweight, streamlined design, with rubber-tipped temples, offering a secure, comfortable fit. Available in Clear, Indoor/Outdoor and Sun versions.
- · Polycarbonate lens
- · Impact resistant Unisex design
- · Class 1 optical
- DeWALT In/Outdoor lens: EN170 5-1.7; DeWALT Sun lens: EN170 5-3.1; Meet the requirement of EN166-1F



518-6121 Dewalt Safety Spectacles, , Clear

MPN: PROTECTOR

HK\$72.62

Visit hken.rs-online.com to order today!

Crusader Filter Canisters

- Filters feature a water resistant, glass fibre medium
- Capable of withstanding the extra load imposed by water aerosols

Ammonia, Gas, Particulates, Solvents, Sulphur Dioxide Filter For Use With Respirator

3M™ Low Maintenance Full Face Mask,

Available in small 6700S, medium 6800S or large 6900S sizes

· Four strap harness assembly for comfort and reliable fit

286-7142 3M 6800 Full Mask Reusable Respirator

. These gas and vapour filters employ a counter-

of weight and therefore improve comfort.

balanced, streamlined design to minimise the feeling

6000 Series Gas & Vapour ABEK2 Filters

These 3M[™] 6000 Series Gas and Vapour Filters are the 6099 Class

inorganic and acid gases, and ammonia derivatives and particulates.

Ammonia, Gas, Particulates, Vapour Filter For Use With 6000 Series Full Face Mask, 7000 Series Full

ABEK2 (P3R) filters designed specifically for organic vapours,

· The positioning of the filters ensures an excellent field of vision. Meets the requirements of EN14387:2004 +A1:2008

Organic Vapour/Inorganic/Acid Gas

inorganic, acid gases and ammonia concentrations of up to 10

WEL or 1000ppm, whichever is the lower and protection of

up to 10 'WEL for particulates (assigned protection factor).

Four-point strap adjustment ensures excellent fit with

Meets the requirements of EN 405:2002 FFABEK1P3

maximum comfort and minimum pressure

Integral filters

· This respirator provides protection against organic vapours,

and Ammonia Respirator 4279

- Deploy a unique, asymmetric parallel pleat
- configuration for greater dust holding capacity Meets the requirements of EN 141, EN 143, DIN 3161 Gas Filter prEN 141, CE0086



3M 8710 Dust Respirator FFP1

- · Respiratory protection against fine dusts
- Typically applications, sawmills, engineering, quarrying, pharmaceuticals, paint manufacture construction, laboratories, agrochemical
- Convex shape with twin strap design, foam nose seal and aluminium nose clip for good face seal over a range of face sizes
- Maintenance free and exempt from
- Weight 7g
- Suitable for use under COSHH, CAW, CLAW and IRR



3M 8710E FFP1 Disposable Respirator, Adjustable MPN: 8710E Nose Clips

CONSUMABLES & SAFETY

HK\$181.74

- Tough shell and cup design for secure feel and multi-shift capability
- filtration with low breathing resistance



HK\$459.78

- · Maintenance free, disposable half mask
- record-keeping or maintenance
- · Face seal is soft to ensure a comfortable fit
- Mask is lightweight for increased comfort over long periods of wear
- Two inhalation valves coupled with large carbon
- Meet the requirement of EN 405:2001+A1:2009



Organic Vapour/Particulate Respirator

- Four-point strap adjustment
- Maintenance free and exempt from maintenance



711-766 3M 4251 Half Mask Reusable Respirator MPN: 4251 HK\$207.68



- resistance and prevents heat build-up
- Fully adjustable head cradle



Excellent comfort

maintenance requirements of COSHH

Meet the requirement of EN 149:2001 FFP1



3M 8835 FFP3 Disposable Respirator

- 3M Advanced Electret Filter Material offers effective
- FFP3 easy identification with red colour-coded valve print





3M 8835 FFP3 Disposable Respirator, Valved

HK\$1,220.97 **Organic Vapour/Particulate Respirator** 4251

- · Easy to use with no assembly requirements,
- filters help by reducing breathing resistance





· Parabolic exhalation valve reduces breathing

- Facepc constructed from non-allergenic compound
- requirements of COSHH, if disposed of within one month Meets the requirements of EN 405:2001 FFA2P3. Suitable for use under COSHH, CAW, CLAW and IRR



766-176 3M 4255 Half Mask Reusable Respirator





287-2649 3M 4279 Half Mask Reusable Respirator

MPN: 4279

MPN: 6800

MPN: 6099

HK\$329 51

HK\$738.25



HK\$261.51



 Lightweight Silicone facepc

6000 Series

• Dual filter design for balanced weight

distribution and greater comfort

Utilises 2000/6000 series filters

. Meets the requirements of EN136: Class 1

· Comfortable fit and easy adjustment

2000 Series Particulate Filters

- Particulate of up to 10 x WEL (APF). 3M 2125 (rs.766-233)
- Particulates of up to 10 x WEL, with ozone protection up to 10 x WEL and relief from organic vapour/acid gas below WEL (APF). 3M 2128 (rs.766-233)
- Protection against concentration of particulates of up to 20 x WEL for half masks and 40 x WEL for full face masks (APF), 3M 2135 (rs. 548-8843)
- Particulates of up to 20 x WEL for half masks and 40 x WEL for full face masks (APF). Ozone protection up to 10 x WEL and relief from organic vapours/acid gas below OEL. 3M 2138 (rs.358-4365)

3M 8812 Valved Dust Respirator FFP1

Convex shape with twin strap design, foam nose seal and

steel nose clip for good face seal over a range of face sizes

. 3M cool flow valve and collapse-resistant shell offer comfort

and durability particularly in hot and humid conditions

Assigned Protection Factor 4; Nominal Protection Factor 4

3M 8812 FFP1 Disposable Respirator, Valved Adjustable Nose Clips

Suitable for use under COSHH, CAW, CLAW and IRR

Maintenance free and exempt from

Weight 12g

Supplied in box of 10

maintenance requirements of COSHH

Dust, Mist Filter For Use With 6000 & 7000 Series MPN: 2125 Half & Full Face Mask

 Standards EN 143 Assigned protection factor as detailed in BS4275:1997 (APF)



lock, set-back time, temp, offset and °C/F

Weller

Additional tools supported

Push-button temp, setting

343-8600 Weller WDD81V, Soldering Station, 230V, UK Plug, MPN:T0053256399 +50°C to +450°C

Cordless Soldering Iron 15W

Desoldering Station WDD-81V

An external dry compressed air source (58 to

Additional functions can be programmed using

optional Calibration Box WCB-1 including: temp.

87 PSI) is required to generate vacuum

Microprocessor controlled single output rework station for

repair/rework of PCB's with through-hole components.

- Separation from mains supply eliminates voltage spikes/surges and absence of earth allows use on isolated/floating components
- Nominal power equivalent to 35W irons
- Rechargeable unit with built-in nickel-cadmium batteries
- Safety lock for power switch
- Operating temperature 350°C reached within 7 seconds
- Two light fittings mounted on tip holder provide illumination of soldering area
- Charging units RS Stock No's 337-5212 (13A RS1363) and 215-5225 (2 Pin Euro) available separately
- Supplied with Standard tip, cleaning
- sponge, spare lamp, screwdriver

Cordless for field portability

Auto shut-off when cap is replaced

lead free solder & tip wrench

Develops 900F for standard duty applications

Supplied with Conical tip 0.4mm, 3 batteries.

Long lasting nickel plated copper conical shape tip



545-008 RS Pro Battery Soldering Iron, 15W, UK Plug

Weller Battery Powered Soldering Iron

Super fast heat up - to working temperature within 15 seconds

HK\$1.098.79

HK\$278.58

Low Maintenance Half Mask

- · Lightweight and comfortable, this low maintenance design eliminates the need to carry spares, with the low cost facepc simply being replaced if damaged. Used with twin lightweight filters (not included), one on each side of the facepc, which are attached by a 3M bayonet.
- Hypoallergenic facepc
- Well-balanced for comfort
- Utilises 3M 2000//6000 series filters
- Meets the requirements of EN 140; 1998



HK\$164.80

619-8478 Weller 4.5V Battery Soldering Iron, 6W MPN: BP650EU

- **RS Pro Shim Kit, Stainless Steel**
- . Exact thickness clearly marked on each shim
- 0.4, 0.5, 0.7 & 1.0mm) 10 of shim thickness (2.0mm) and sizes 50x50mm, 75x75mm & 100x100mm
- · Replacement shims available (sold separately)



Pyropen Self-Igniting Iron WSTA4

- Functions as a soldering iron and hot air tool Ignition by internal piezo igniter
- Gas level sight glass
- Soldering temperature: 300

 500°C Hot Air temperature: 650°C
- Supplied with hot blow nozzle, 3mm chisel tip & heat shrink reflector kit



660-416 Weller Gas Soldering Iron

MPN: WSTA4

HK\$1,858.56

1.7m Desoldering Braid, Width 1.25mm

- · Finely woven pure copper braid, quickly removes excess material during hand soldering rework.
- Braid is rigid to prevent unwanted flexing, absorbent and will not unravel when bit pressure is placed upon it
- Flux is a synthetic, non-corrosive medium which will not attack joints
- Ideal for component extraction, solder bridge removal and improving appearance



Antex 690Sd 50W Digital Station Uk Plug

· Digital soldering station

FSD safe

- · Temperature set via fascia buttons
- Temperature controlled between 65°C and 450°C
- Accurate temperature stability
- Two memory settings
- Lockable settings
- · Bit temperature offset



200-7700 Antex Electronics 690SD, Soldering Station, 230V, UK MPN: UD82070 Plug. +65°C to +450°C

HK\$3,323,93

HK\$3,756,71

Empty Flux Dispensing Pen Thin Felt

561-022 Electrolube 1.7m Desoldering Braid, Width 1.25mm MPN: ERDSB01

· Empty flux pens

ELECTROLUBE

- Excellent for fine and accurate application of flux
- No flux evaporatio · Flux can be refilled
- FSD safe
- Suitable for: Fluxes, Alcohol, Fluoric Lube,

Primers, Flux inhibitors, Water



Mfr-1160 X1 H6 Iron Ssc Tip Solder Kit

- Single output system with SmartHeat® technology
- High power output at a fixed temperature provides high throughput with excellent yields
- Ergonomic handpc
- . Handpc accepts SSC solder tips
- Station Ambient Operating Temperature: 10 2 40°C



CONSUMABLES & SAFETY

idealtek sa

852-6193 Idealtek BON-102B, 8 ml Solder Flux Dispenser

Tin-Ag-Cu Alloy Lead Free Solder, 0.7mm

- · Resin based SAC305 Lead-free solder wire . Leaves low level of clear flux residue
- . Wets well to all PCB and component finishes
- Ideal for all lead-free applications
- . Utilising a synthetically refined resin





METCAL

672-2696 Metcal MFR-1160, Soldering Station, 240V, Type F - Schuko plug, Type G - British 3-pin, +302°C to +471°C MPN: MFR-1160

Wsd 811 Soldering Station 230V Uk

Low voltage for maximum safety

- Ideal for use in electrostatic protected environments
- No requirement for ground monitoring
- Precise temperature accuracy · No calibration required



RS Pro 0.7mm Wire Solder, +217 → +219°C Melting Point, 0.5% Copper, 96.5% Tin, 3% Silver, 250g

60/40 Tin-Lead Multicrsolder, 1.22mm, 250G

- This alloy is suitable for high quality work requiring a low melting temperature.
- 5 cores of Ersin® flux
- Conforms to BS441 Type 1, DTD599A and DIN8516



Soldering Station AT90DH

Large LCD display, with backlight

Weller

Soldering Iron heats from room temperature to 350°C

798-9339 Weller WSD81I, Soldering Station, 230V, Type F - Schuko plug, Type G - British 3-pin, +50°C to +450°C

RS Pro AT90DH, Soldering Station, 220V, Type F -Schuko plug, Type G - British 3-pin, +100°C to +500°C

Built in 'sleep mode' function



MPN:T0053294399



619-5615

Multicore 1.22mm Wire Solder, +183 → +188°C Melting Point, 40% Lead, 60% Tin, 250g

WSW SAC LO - Lead-free Solder Wire

industry's increasingly stringent quality requirements. . WSW SAC L0 lead-free solder wire with Sn3.0Ag0.5Cu alloy

WSW SAC L0 solders have been developed to meet the electronics

- L0 Halogen-free flux
- For a long life of the soldering tips
- Fast and homogeneous wetting of the soldering tip · Reduced Fe leaching
- . Application: For use in hand soldering and

automatic solder feed applications



HK\$171.05




MPN: 291340

Weller


Weller 0.8mm Wire Solder, +217 °C, +221 °C Melting MPN:T0051388799 Point, 0.5% Copper, 96.5% Tin, 3% Silver, 250g

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Visit hken.rs-online.com to order today!



Kit containing 20 of shim thickness (0.05, 0.1, 0.2, 0.25,



MPN: 6200









382-8019 Shim stock precision pre cut kit

Visit hken.rs-online.com to order today!



Soldering System W/Shp-Sm 100-

- Soldering station with soldering handpc for use with $\ensuremath{\mathsf{S}}$ series tip cartridge (RS 860-9422, RS 860-9462)
- Curie Heat Technology operating at 470 KHz
- Extremely compact
- No calibration or operator training requir



FM-206 Hakko 3-port Rework Station

- Hakko FM206, Soldering Station, 24V, UK Plug, +200°C to +550°C
- This multi-purpose rework station from Hakko effectively combines the triple functions of soldering, desoldering and SMD rework into one convenient unit.
- The station includes Soldering Iron, desoldering and hot air rework interchangable tools for maximum versatility of operation.
- The unit's graphic LCD display enables easy operation and viewing



Thermaltronics TMT-2000S, Soldering Station, 100 -> MPN:TMT-2000S-SM 240V ac, 8 Pin

⊕HAK(O

766-0432 EM206-20

HK\$17 228 18

Weller WHS-40 Soldering Station

- · Entry level soldering station ideal for engineers who require soldering temperature control combined with low cost.
- Analog temperature control
- Temperature adjustable via rotary potentiometer
- · The soldering tip is equipped with an electroplated protective coating



RS 80W Soldering Station ST-80

- · Automatic standby and shutdown for safety and efficiency
- Set and lock required temperature
- Display temperature in °C or F
- · Pre-set frequently used temperatures using buttons 1, 2 and 3 to switch quickly between
- New design featuring LCD display screen for clarity
- Dual-core wire heater for fast heating
- Soldering Tips are available separately. This ST-80 soldering





278-8550 Weller WHS40, Soldering Station, 230V, UK Plug, MPN:T0056806399 +200°C to +450°C HK\$1,474.16

885-6117

RS Pro ST-80, Soldering Station, 240V, Type C - EuroPlug, Type G - British 3-pin, +150°C to +480°C

HK\$1.738.74

Weller WTCP 51 Magnastat Soldering Station

- Magnastat' controlled variable temperature station
- Supply 220V IN/24V OUT

Weller

- · Temperature determined by tip selection
- Temperature accuracy +10% of nominal temperature
- Antistatic Tip earthed via mains lead
- Safety transformed class II 230V/24V 50Hz
- · Burn proof soldering iron lead



Soldering Tip 3mm

- Powered by gas, this iron has an autonomy of 3 hours per filling and a heat up time of approximately 30 seconds. It is fully autonomous, thanks to its ignition button.
- Temperature range between 200 and 500 °C is controlled by increasing and decreasing the gas flow. Power supplied: 80 W.
- This set is supplied with a carry case, a 3 mm tip, a hot air nozzle and a gas recharge kit



Weller

• This latest WSD 81iSE model Soldering Station from Weller

pulls together three ever-popular products into one highly

Unit; WP65 Soldering Iron; WDH10 Soldering Iron Holder

different tools and provides exact temperature accuracy.

effective and efficient soldering kit: the PUD 81i Power Supply

WSD 81iSE Soldering Station

. The kit is highly cost efficient with features such as the PUD 81i's Automatic Energy Saving Mode

 The kit has been designed to protect workers and provides optimum safety with no use of high-frequency technology; it is ideal for use in ESD protected areas. . The WP65 Soldering Iron is a 65W dry cleaning iron that offers simple and quick tool changes; is compatible with many

which helps to reduce production costs.

In addition, no calibration is required for

this easy to operate soldering kit

Weller WTCP51, Soldering Station, 230V, UK Plug, MPN:T0053220399 +316°C to +480°C

COOPER

Cooper Tools 2 mm Straight Hoof Soldering Iron Tip For Use With WSTA3 Soldering Iron MPN: WPT3

Antex Soldering Iron Sponge, 140X100X10mm

A cellulose sponge supplied as a flat sheet, approx. 140'100'10mm which may be cut in the dry state to size and then moistened with water





518-999 Antex Electronics Soldering Stand Sponge

MPN: Y023150

Weller

56

815-7353 Weller WSD 81iSE, Soldering Station, 230V, Euro MPN:T0053296399 & UK Plug

HK\$3,756,71

Lead Free Desoldering Wick, 2.8mmx1.5Mx10

- More efficient than conventional de-soldering braids
- · Non-corrosive, ultra high purity no-clean flux
- · Will not leave ionic contamination on the boards
- Can also be used with tin/lead solders



HK\$29.73

Chemtronics

508-6368 Chemtronics 1.5m Lead Free Desoldering Braid,

MPN: SW14045

HK\$484.55

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Abeco 3 Speed Desoldering Pump W/

- Nozzle can be cut at an angle for the most
- ergonomic position for the job Totally temperature resistant and can be placed on the solder to be removed, even in direct contact with the desoldering iron
- · Easy to clean using the needle supplied or simply by rolling the tip of the nozzle between the fingers
- . Model no. 2009 has 3 suction strengths to suit different needs

Abeco Standard Aluminium Anti-Static Desoldering MPN: 2009 Pump with Silicone Rubber Nozzle

Weller WD1000, Soldering Station, 230V, UK Plug, MPN: T0053402399

Aluminium body & silicone nozzle

ABECO

203-7795

· Spare nozzles are available separately

WD1000 Soldering Station

Big LCD display allows clear information

. Three fixed temperatures can be assigned

Supplied with WD1 Power Unit, WSP80

soldering iron, WDH10 bench holder

Weller

510-2022

iron

display and simple handling

with the temperature buttons

Microprocessor controlled power unit, developed for

industrial production technology including repair and

laboratory areas in a modern ergonomic design. Top

behaviour when under stress is achieved by fast and

precise measured recording in the closed control loop.

· Available with either BS1363 type or Aus/NZ mains plug

temperature accuracy and optimised dynamic temperature

The following settings are possible without any accessory unit:-

BP860CEU battery-powered soldering

 Fast heat-up cordless soldering iron, power 6 watts position I (380 °C) or 8 watts position II (480 °C). · Reaches its operating temperature in less than 30 seconds

Supplied with 2 tips: conical 0.8 mm (BP10EU) and

solder wire, tip changing tool and storage box

537-218 Weller Battery Soldering Iron, 11W

screwdriver 1.8 mm (BP11EU), 4 AA batteries, lead-free

. Up to 180 soldering operations.

Powered by 4 AA batteries.

custom designed calibration function, programmable temperature decrease, interlock functions, remote ID for ISO applications



Weller 200mm Miniature Metal Anti-**Static Desoldering Pump**

- Manual Desoldering pump
- Strong vacuum
- 200mm length Metal housing
- Antistatic



Weller

Weller 200mm Miniature Metal Anti-Static

Chisel Tip For Antex Cs/Tcs Iron, 2.3mm

· Replacement Antex soldering iron tips





Antex Electronics 2.3 mm Straight Chisel Soldering Iron Tip For Use With Antex CS/TCS Series Soldering

Pro li Tip For Piezo Ignition Iron, 1mm

- · Adjustable temperature control
- Internal piezo crystal ignition
- · Ergonomic close coupled tip to grip cool handle
- Anti-static

HK\$4 321 93



ANTEX

409-4699 Antex 1 mm Straight Conical Soldering Iron Tip

Replacement Soldering Iron Tip,

0550Md · Suitable for sheet metal processinginstallation work

- and soldering commutators and copper bus bars
- Proven in industries such as automotive, lead glazing



SD1000 Solder Dispenser

Single reel solder dispenser

Weller







756-0158

Ersa Straight Chisel Soldering Iron Tip For Use With RPN: 0550MD ERSA 550 Hammer Soldering Iron

HK\$7,867.28

Weller

660-624 Weller Solder Dispenser

MPN:T0051301799

MPN: BP865CEU

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.







MPN: 11188300



Fluke Industrial **Testing and Measurement Tools**

Safety Rugged **Accurate** Intuitive





TEST & MEASUREMENT

TEST & MEASUREMENT

Hioki 3554 Battery Tester 6V to 60V Lead

- Support of UPS batteries via simple, quick and accurate testing.
- Accurately measures battery internal resistance for correct battery condition diagnosis
- . Battery Tester for Checking and Recording Battery Resistance and Voltage
- · Suitable for testing all types of lead acid,
- Ni-Cd & Lithium-Ion batteries
- Batteries do not have to be disconnected from the charging system to carry out the battery condition tests

666-4934 Hioki 3554 Battery Tester 6V to 60V Lead Acid

RS Pro Colour Waterproof Bullet Camera CCTV Camera • 1/3" 960H SONY Super HAD CCD II

776-9368 Bullet Cctv Camera 700Tvl 4 - 9 mm Lens

Digital Stopwatch Black

. Accuracy within 1 second over 24 hours

Testo 435-2 Meter

. Large format backlit display

. Easy to use menu system

. MIN/MAX & display HOLD

Water resistant black case 65x63mm with cord LANyard

RS Pro Black Pocket Digital, Battery Operated Stopwatch, Dim. 65 (Dia.) x 64in

normal time, alarm and calendar Counts up to 40 minutes in 1/100 second and then to 24 hours in 1 second intervals Large 12mm and 10mm digit heights · 3 volt operating system with CR2032 lithium battery, offering increased reliability and accuracy . 5 years battery life under normal use

• 1/100 second LCD stopwatch with lap facility,

· 4 Terminal testing via specially designed test probes supports greater accuracy

HIOKI

 High Resolution • Sens-up (~ x512) 3D-DNR/WDR/HSBLC/D.zoom • Motion Detection/Privacy Masking Multi LANguage OSD Dimension: 26 dia. x 105mm

 4-9mm Manual Varifocal Lens Waterproof type



MPN: Hioki 3554

· Easy- to-read backlit display

. Multi-function 3-line display

• Data Logger (automatic and manual)

FLUKE 925 Anemometer

• Data storage can be customised - 2900 data points Minimum, Maximum and Average values

914-0006 Kestrel 0852HVG Anemometer, 40m/s Max Air Velocity

5200 Professional Environmental Meter

Evaporation Rate, Delta T, Air density, Relative air density (RAD), Heading (true & magnetic), Wind direction, Crosswind,

Headwind/tailwind Altitude Pressure trend Barometric pressure, Wet bulb temperature, Relative humidity in %, Heat stress index, Dewpoint, Density altitude, Wind chill, Air,

water and snow temperature F or °C. Current, average and

maximum air velocity. Waterproof (sealed to IP67) and floats

MPN: 0852HVG

HK\$3,041.64

Kestrel

• Probe Type: Impeller



FLUKE.

679-6772 FLUKE 925 Anemometer,

Diaital Anemometer

- . A cost effective instrument with vane probe head connected via a 1m coiled lead.
- Sensitive for low/high air velocity
- · Ergonomic design
- Measurement range of 0.3 to 45m/s Optional measurement parameters of m/s, Knots, ft/min, km/hr or mph



506-9650 RS Pro AVM-01 Anemometer, 45m/s Max Air Velocity

HK\$1 300 00

Kane 250 Combustion Gas Analyser

- O2, CO, CO2, CO/CO2 ratio and efficiency readings
- Multi fuel
- · Professional quality sensors (CO readings to 1ppm)
- · Detachable flue probe
- Real time clock · Infrared output to optional printer
- · Rubber sleeve with integral magnet



468-6018 KANE250/RS Combustion Gas Analyser

MPN: KANE250/RS



516-7108 Testo 435-2, with LCD - Backlit display

 Selectable profiles including and duct area input for channel measurement and indoor air quality (IAQ) long term measurement profile Volume flow and average function calculation

MPN: 0563 4352

HK\$4.696.50











Indoor Air Quality Meter, Testo 535

- Long-term monitoring via maximum/mean calculation
- 2 channel infrared sensor
- Long-term stability
- Tests stationary CO2 transducers in 'demand controlled' ventilating systems (DCV)
- . Monitors indoor air quality in open plan offices
- Measures the concentration of CO2 in ingoing and outgoing air ducts



Supply Single and dual outputs Dual range output . 30 W to 100 W output power

- Front and rear output terminals
- Over-voltage protection
- · Remote Sensing connections on the rear
- GPIB and RS-232 interfaces
- Save and recall functions for up to 5 values





Recorder

509-5766 Testo 535, with LCD display

CO2, temperature and humidity logger

· Compact and stand-alone: for fixed or portable use

on the CO2 level and hygrothermal criteria

Accurate: complies with the latest standards

. User-friendly: thanks to the comfort indicators based

(up to 1 million measurements)

concerning air quality monitoring

Ca1510 Temp/Humidity/Co2 Meter/

MPN: 0560 5350 HK\$4.999.50

KEYSIGHT

667-7397

Keysight Technologies E3648A Bench Power Supply, MPN: E3648A 2 Output $0 \rightarrow 20V$, $0 \rightarrow 8 \ V \ 2.5 \ A$, 5 A 40W

325-6004 ISO-TECH IPS303DD Bench Power Supply, 1 Output MPN: IPS303DD 0 → 30V 0 → 3A 90W

HK\$11,308,00

Ips303Dd Single Output Psu, 0-30V 0-3A

100W Programmable Dual Dc Power

- · Light and compact design
- Rugged
- Separate 3-digit LED voltage and current meters
- Supply voltage 100/120/220/240V 50/60 Hz, switchable
- Overload and reverse polarity protection
- Low ripple and noise



HK\$1.818.00

HK\$6.775.70



896-2170 CA1510, with LCD display

MPN: CA1510

HK\$3.752.09 ISO-TECH

lps303A Analogue Meter Psu, 30V 3A

· Low gas consumption for verification with its in-situ calibration kit

- · Compact analogue unit, easy to use and control
- · Coarse and fine controls for voltage and current
- · Overload, short circuit & reverse polarity
- protection, with low ripple and noise · Excellent output regulation

CV/CC priority

LabView driver

ISO-TECH

Adjustable slew rate

Series and parallel operation

OVP and OCP protections

· High efficiency and high power density

Standard interfaces LAN, USB, analog control

- Constant current/voltage operation
- · Can be connected in series or parallel
- Remote voltage and current setting capability



Multi-Range Dc Power Supply 30V 36A

• Constant power output for multi-range (V&I) operation

201-3424 RS Pro Bench Power Supply, 1 Output 0 -> 30V 0

U8000 Series Power Supplies

Low output noise: 1 mVrms (20 Hz to 20 MHz)

Save-and-recall function up to three memory states

· Security features: keypad lock and physical lock mechanism

Over Voltage and Over Current Protection

LCD display with backlight capability

Standby output for safety purposes

• Excellent load and line regulation

667-2585 Keysight Technologies U8002A Bench Power Supply, MPN: U8002A 1 Output 0 → 30V 0 → 5A 150W

EA-EL 9000B Series 3U Electronic Loads with Multi-function Controller

1 2kW to 7 2kW

- 0-80V, 0-200V, 0-360V, 0-500V, 0-750V DC 0-20A up to 0-510A depending on model
- FPGA controlled and programmable
- Isolated analog 0-5V/0-10V & USB interface on board
- Operation modes CV, CC, CP, CR, battery discharge mode


EA Elektro-Automatik Electronic Load EA-EL 9000 B EA-EL 9500-30 B 0 → 30 A 0 → 500V Maximum

- Integrated sequencer with default waveforms,
- memory, alarm manager, user profiles

ISO-TECH Bench Power Supply, 1 Output 0 -> 30V MPN: IPS 30-36 0 -> 36A 360VV

Power Supply, 18V, 5A Dc

- · Low noise, linear regulation · Wide voltage and current ranges
- 10 mV/10 mA programming resolution
- · Bright vacuum fluorescent displays
- 16 setup memories Ripple and noise (7 MHz) 1mVrms/3 mVp-p
- Constant voltage, constant current control modes





EA-PS 3000 series

- Current and voltage can be adjusted with a coarse and precision regulator
- Constant current and constant voltage operation
- · Temperature-controlled fan output
- Analogue interface for U/I



MPN: EA-EL 9500-30 B HK\$27.912.50

Tektronix

Tektronix PWS2185 Bench Power Supply, 1 Output 0 MPN: PWS2185 -> 18V dc 0 -> 5A

E

493-7984 EA Elektro-Automatik PS 3032-10B Bench Power

MPN: PS 3032-10B

HK\$4,473.67

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



FLUKE 715 Current/Voltage Calibrator

· Clear 5 digit LCD display

FLUKE

HK\$2,680.00

- Operating temperature -10 to +55°C Measure loop current (0-20mA, 4-20mA)
- · Measure voltage output process signals from PLCs, transmitters

The Druck DPI 620G incorporates system components which

provide simultaneous measurement and source capabilities

instruments including transmitters, transducers, gauges/

indicators, switches, proximity detectors, counters, RTDs,

DPI 620G-L (815-9995) Genii advanced modular calibrator;

modular calibrator with HART/Fieldbus communicator.

BATTERY, universal mains adaptor/charger IO620-PSU,

true rms measurement probe IO620-AC 300VAC, test

leads, calibration certificate, quick reference guide

Supplied with rechargeable lithium polymer battery IO620-

DPI 620G (800-3013) Genii advanced modular calibrator with

HART communicator: DPI 620G-FF (800-3016) Genii advanced

for the set-up, testing and calibration of most types of process

themocouples and value positioners. The models available are:

263-2700 FLUKE-715 Current & Voltage Calibrator 0 -> 24 mA MPN: FLUKE-715

Druck DPI620G-L Multi Function Calibrator 30V dc, MPN: DPI620G-L 300V ac 55mA 1000bar

· Source or simulate 24mA loop current

Multifunction Calibrator

Source voltage to 200mV or 10V



HK\$10.788.00

TEST & MEASUREMENT

ISO-TECH

RS-232 interface

Output On/Off control

· Constant voltage/current operation

. Key lock to avoid operational errors

Normal, +% & -% output operation key

· High efficiency and high power density

OVP, OCP & OPP protection

ISO-TECH IPS-603 Bench Power Supply, 1 Output 0 MPN: IPS-603 \rightarrow 60V 0 \rightarrow 3.5A 200W

EA-PS 9000 1U (µ-processor) Series

Ips-603 Programmable Switching Psu,

- u-processor controlled up to 16 bit resolution
- For laboratory, industry, R&D, automated testing Flexible auto-ranging output, constant U, I, P mode
- . Dot matrix LC-display, up to 5-digit display, memory/profile functions
- On-board isolated analogue interface
- (0-5V/0-10V), USB and Ethernet Suitable for master-slave parallel & serial operation

holts with insulated safety cover

- . Attractive and rugged 19" 1U rack format
- 500mm depth (483 x 44 x 522 mm including terminal) • IEC 320_C20 input receptacle, outlet 6 mm
- Input voltage 90-264 V[®] (3kW 195-264V[®] only), 50/60 Hz, active PFC



• 31/2 digit 2000 count LCD

· Portable instrument for calibrating process

devices and measuring process signals

Power and measurement of 2 wire loops

Adjustable 0 - 24mA current source, ±0.5% FS +1d

EA Elektro-Automatik EA-PS 9750-12 1U Bench Power Supply, 1 Output 750V dc 12A 3000W

Handheld Current/Voltage Calibrator

Adjustable -199.9mV to 199.9mVdc voltage source, ±0.25% FS +1d

MPN: EA-PS 9750-12 1U HK\$37,846.00

- **Pocket Size Current Simulator, 4-20Ma** Preset outputs 4, 12 and 20mA
 - Accuracy ±0.2mA Battery life 10 hours (typical) for alkaline batteries
 - · Low battery indication Overload indicator when the output current
 - delivered is less than the set level
 - Requires a PP3 battery



701-2814 ILC421 Current & Voltage Calibrator 0 -> 19.99 mA, MPN: ILC421

Time Electronic 1017 Multi Function Calibrator

Visit hken.rs-online.com to order today!

Voltage/Current/Resistance Calibrator DC voltage 10nV to 100V

- . DC current 100nA to 100mA Resistance 10MO to 10kO
- Accuracy 0.0005% (50 ppm)
- . 1 ppm setting resolution Noise <2 ppm (0.1 to 1Hz)
- Stability <5 ppm/day, <25 ppm/year
- · Deviation control voltage and current
- · Battery or mains

#

816-0181



MPN: 1017

ISO-TECH

180-7082 Multi Function Calibrator 20mA

4-20mA Digital Loop Calibrator UPS II

- A high quality, pocket size instrument for checking and simulating 2-wire transmitters and stroking valves. The nicroprocessor based electronics allows the device to be used in a wide range of industrial and process applications
- Outputs and reads mA
- Fixed current, auto step and auto ramp functions Readings/fixed steps in mA or % span

for correct seating and operation of a valve

 Simplified valve stroking with fixed outputs of 3.8, 4, 4.2, 12, 19, 20 and 21mA, enabling the user to check



HK\$17.163.81

HK\$1,727,10

Druck UNO-UPS-II-1841 Current Loop Calibrator MPN: UNO-UPS-II-1841 HK\$4,538.32



61





HK\$12.263.12

UPS-III Loop Calibrator

- Built in 24Vdc power supply loop
- mA and % displayed simultaneously, as linear or square root (flow)
- Measurement/generation 0 24mA DC
- Instrument accuracy 0.01% of the reading (over 1 year)
- Automatic PAS mode and ramp adjustable from 1 to 599 secs · Contacts test mode
- Predefined values for the quick testing of linear
- loops, flow loops and the control of valves · HART transmitter compatible



434-7000 Druck UPS-III Current Loop Calibrator 24mA

MPN: UPS-III

541-071

Calibrators

sourcing a temperature signal

for quick 25 % linearity checks

Linear ramp and 25 % step auto ramp

Dual inputs and backlit display for easy

Power down settings remembered at

based on 0 % and 100 % settings

interpretation of measurements

power up for easy restart of tests

HK\$7 205 79

FLUKE 789 Combined Multimeter and Loop Calibrator

- Combined digital multimeter and loop calibrator.
- Precision 1000V, 440mA digital Multimeter measures a.c. and d.c. volts, a.c. and d.c. current, resistance, continuity and frequency.
- d c mA current source/loop calibrator/20mA current source/simulator/% of scale readout
- True r.m.s. a.c. voltage measurement
- Frequency measurement to 20kHz
- Min./Max./Peak Hold/Hold/Relative modes
- 24V loop power supply
- . Manual Step, Auto Step, Auto Ramp
- 0% and 100% buttons to toggle between 4 and 20mA

DPI880 Multifunction Calibrator

. Simulates and reads 8 RTDs and 12 thermocouples

. Automatic detection of 2, 3 and 4 wire RTD's

· Programmable step, nudge and ramp outputs

· Simultaneous dual reading capability

Automatic switch test

· 24 V loop power supply

· Robust and weatherproof

• HART® loop resistor

· Large backlit display

- . 1200 Ohm drive capability on mA source
- HART mode setting with loop power incorporating 250 Ohm resistor
- Externally accessible battery
- Diode test and Continuity Beeper



447-7707 FLUKE 789 Current Loop Calibrator 1A

MPN: FLUKE-789

HK\$8,758.00

FLUKE.

805-2416 FLUKE-714B Multi Function Calibrator 30V 20mA

USB 8-Channel Data Acquisition Module

Advanced Modular Calibration System

Multi-function modular calibration system

Electrical, frequency and temperature calibration

with simultaneous measurement and source.

Modular pressure measurement and pressure

calibration functions – from 25 mbar to 1000 bar

Upto 100Bar pressure generation pneumatically

Upto 1000Bar pressure generation hydraulically

simply screw fit with no tools required

 Hart Configuration included as standard Large video-quality LCD touch-screen –

Weather-proof to IP65

Interchangeable pressure ranges – pressure modules

FLUKE 712B and 714B Temperature

Measure 4 to 20 mA signals while simultaneously

Configurable 0 % and 100 % source settings

· Hanging tool designed in and included with every unit

MPN: FLUKE-714B

Druck PM 620-13G Multi Function Calibrator Pressure MPN: PM 620-13G Module For Use With DPI 620 Series

- The DLP Design DLP-IO8 Data Acquisition Module is an easy-to-use data acquisition system for measuring voltages, controlling and monitoring processes, and acquiring temperature data. Each of the 8 available channels can be configured for any of the digital, analogue or temperature modes via single-byte commands.
- All operational power is taken from the host PC via the USB port. All models are highly reliable and excellent quality





532-7530 Druck DPI 880 Multi Function Calibrator 30V 55mA MPN: DPI 880

HK\$19,710.31

DLP

906-3855 DLP DESIGN INC DLP-IO8-G Data Acquisition, 8

MPN: DLP-IO8-G

HK\$386.76

Metrology Well, +50 ~ 660Oc.

- Temperature range between 50°C and 660°C
- Lightweight, portable, and fast
- Cool to 50°C in 15 minutes and heat to 660 °C in 15 minutes

· Compact, one-handed operation, simple to use, easy to carry

- Metrology performance in accuracy, stability, uniformity, and loading
- LCD display continuously shows many useful operating parameters including the block temperature, the current set-point, block stability, and heating and cooling status.
- Multiple sized sensor holes to accept a wide range of temperature sensor diameters





Saveris 2-T1 WiFi-Datalogger

- Data transfer by WiFi
- All measurement data always available,
- anywhere, on any instrument
- or by SMS, depending on choice of Cloud license)







537-066 FLUKE 9144/RSA Multi Function Calibrator 20mA MPN: 9144/RSA

HK\$38.117.40



Testo Saveris 2-T1 Data Logger, Maximum Temperature +50 °C, USB, Battery 4 x AA AlMn

MPN: 0572 2001

36

B 0



8 Channel Thermocouple Temp Data Logger

$\bullet\;$ Works with thermocouple types B, E, J, K, N, R, S and T

- Wide temperature range, with 20 bit vertical resolution
- · Built in cold junction compensation
- No power supply required, power is drawn from USB port
- Data can be displayed or exported in graphical and numerical format
- . Min/Max/Average or filtered values can be recorded and displayed
- Max/Min alarm limits can be set for each channel



492-5105 Pico Technology USB TC-08 Data Logger

MPN: USBTC-08

Humidity/Temp/Dew Point USB Data

- Logger Key Features
- Measures temperature (-35 °C to +80 °C), humidity (0% to 100%) and calculates dewpoint
- Easy to use software supplied with unit. Compatible with Windows 2000, XP, Vista and 7.
- . Export to Excel functionality
- · Battery powered



Lascar EL-USB-2 Data Logger, Maximum Temperature +80 °C, Maximum Humidity 100%RH, USB, Battery ½ AA

PicoLog 1000 Series Multichannel

- **Voltage Data Loggers** Unipolar analogue input channels
- · Independent software-configurable channels. ranges, scaling and control outputs
- up to 4 software configurable digital output lines • 3 sampling modes to meet most data logging needs:
- · REAL-TIME continuous provides averaged, timeaccurate readings with automatic measurements,
- STREAMING allows channel voltage readings to be logged continuously at 1 kS/s on any number of channels
- · BLOCK MODE captures at the full 1 MS/s sample rate of the logger for the duration of the 8k sample buffer.
- . Up to 1 MS/s sample rate



Pico Technology PicoLog 1216 Data Logger, Maximum Voltage Measurement 2.5V, USB 2.0, Mains

USB PT-104 4 channel Precision Temperature Data Logger for PC

- · Measures precision temperatures, resistance and voltage
- · High resolution and accuracy
- . USB and Ethernet interface
- Supports PoE (Power over Ethernet) For use with 2, 3 and 4 wire PT100 and PT1000 sensors
- Dimensions:184 x 135 x 36 mm



Pico Technology PT-104 Data Logger, Maximum Temperature +800 °C, Maximum Voltage Measurement 2.5 V. 115 mV 717-4038

MPN: PT-104

MPN: PicoLog 1216

HK\$5.130.00

(Elay

Data Acquisition Switch Unit +Lan

• The 34972A shares the features of the 34970A (686-2107) and additionally features a built-in USB memory port so that a USB flash drive can be used to upload BenchLink Data Logger configurations into the 34972A and collect data without being connected to a PC. Data can be logged directly to the USB flash drive, extending the instrument's memory, or be copied from internal memory for transfer to a computer in another location.



KEYSIGHT

702-7958 Keysight Technologies 34972A Data Acquisition, 20 MPN: 34972A channels , 3Msps, Digital Input

HK\$16.568.00

Humidity & Temperature Meter, Logging

- · Detachable sensing probe
- · Data hold and relative function
- Dual LCD display with bar graph indication
- Dew point readings
- Wet bulb reading
- MAX/MIN with time stamp USB interface (RS 712-6042)
- °C/F selectable





HK\$689.32

712-6042

RS Pro RS-1365 Data Logger, Maximum Temperature +60 °C, Maximum Humidity 99% RH, RS232, USB,

HK\$2 100 80

Greenlee GVIS 400Video Inspection Probe

- · Easy-to-use video fiber connector inspection system
- Eliminate the need for users to place their hands in the same position each time for effective focus control.
- To inspect the backplane connector, the user simply inserts the probe into the connector adapter.
- To focus, turn the entire probe ¼ to ½ turn for complete focus range. USB or WiFi streaming
- Connects with laptops, smartphones and tablets
- Greenlee GVIS application for analysis and reporting



111-0397 Greenlee Fibre OpticTest Equipment GVIS 400 <1 MPN: GVIS400HDP

Fi-100 Identifier, Fibre Kit

- The FI-100 Optical Fibre Identifier can quickly identify the direction of transmitted fibre and display the relative core power without interrupting the current service. The FI-100 detects modulations of 270 Hz, 1 kHz and 2 kHz with an audible tone and LED indication. There are four adapter heads available: Ø 0.25, Ø 0.9, Ø 2.0 and Ø 3.0.
- Low Insertion Loss: Non-intrusive low insertion
- loss prevents alarm conditions · Easy Operation: Identifies fibre with tone detect and a
- clear indication of signal transmission direction Versatile: Supports all common fibres including 250 μm, 900 μm, 2 mm and 3 mm and is able to sense light in bend insensitive fibres



111-0389 Greenlee Fibre Optic Test Equipment FI100, -50 -> MPN: FI100

HK\$4,345.20

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.












HK\$3,350.00





TEST & MEASUREMENT























Fibremaster Quad

- A fibre optic power meter and light source.
- 850, 1300//1310, 1490 and 1550 wavelength measurement capability
- Power measurement in dBm and mW, loss display in dB
- Auto Power Off · Fitted with FC 2.5mm fibre optic socket
- . Operates on standard 3xAAA batteries (not supplied)



Det24C Digital Earth Clamp, Bluetooth

- · Elliptical clamp shape improves access to
- earth cables and straps up to 50 mm Low maintenance flat jaw interface
- Measures ground resistance from 0.05 Ω to 1500 Ω
- . Measures true RMS ground leakage current from 0.5 mA rms to 35 A rms
- CAT IV 600V safety rati



BEAL NETWORK

702-3993

Ideal Networks FiberMaster Quad Fibre Optic Kit, MPN: 33-931

HK\$13.655.20

Megger.

910-6810 Megger 1007-331 Earth & Ground Resistance Tester MPN: 1007-331 1500Ω CAT IV 600V

HK\$13,144.23

Navitek Nt LAN Network Tester

- NaviTEK NT network testers are for troubleshooting and naintaining active and passive copper and fibre networks.
- They incorporate an improved graphical interface which enables network technicians to pinpoint and solve network connectivity issues faster than ever before.
- Tests can be saved as pdf reports and shared with colleagues and clients using the freely downloadable IDEAL AnyWare™ app.



FLUKE 1625-2 Earth Ground Tester Kit

- 3- and 4-pole Fall-of-Potential, earth resistance loop testing
- 4-nole Soil Resistivity testing Selective earth ground rod testing using 1 clamp
- Stakeless earth ground rod testing using 2 clamps
- IP56 rated for outdoor use

DET3TC 3 Pole Earth Tester

. Choice of 2 or 3 terminal measurements

Superior noise rejection to 40V pk-pk

Measures earth voltage 0 – 300V

Automatic P spike & C spike check

· Simple one button operation

Resistance range 0.01 to 2000 ohms auto ranging

- Rugged carrying case
- USB dat



BEAL HETWOOD

897-7157

Ideal Networks LAN Test Equipment Network Tester MPN: R153001
R.I45 Navitek NT

HK\$5 838 80

FLUKE

798-3974 FLUKE-1625-2 KIT Earth & Ground Resistance MPN: FLUKE-1625-2 KIT HK\$34,180.00

Linksprinter Model 300

- Diagnose and test Power over Ethernet (PoE), Link to the
- switch, DHCP, Gateway, and Internet connection · Get VLAN, switch name, and port information via
- CDP/LLDP/EDP for your managed switches Expert network troubleshooting techniques delivered to color gra



FLUKE Networks LAN Test Equipment Ethernet Tester, LSPRNTR-300

MPN: LSPRNTR-300 HK\$3,632.20

Megger.

514-4666 Megger DET3TC EARTH TESTER RC Earth & Ground MPN: DET3TC EARTH HK\$7,810.00
Resistance Tester 2000C CAT IV 100V TESTER RC

Meet the requirements of EN61010-1 CAT IV 150V & CAT III 300V

batteries, hard carry case, quick start guides, user guide on CD

Supplied with 2 earth test stakes, 3 connection leads, 8 x AA alkaline

IntelliTone™ Pro 200 LAN Toner and **Probe**

- IntelliTone™ Pro is the first toner and probe to offer digital and analog toning all in one tool.
- · Equipped with the most powerful cable location and verification
- technologies for any work environment even active networks. · IntelliTone digital signal processing rejects noise and false signals
- · SmartTone analog signal precisely isolates individual wire pairs . Tones safely and clearly on active networks
- · Tests for continuity
- Identifies and diagnoses 10/100/1 Gb Ethernet
- link connectivity with NIC/hub indication
- · Verifies twisted-pair installation with CableMap capability which identifies common cable miswire
- Supplied with IntelliTone 200 LAN Toner and 200 Probe, coax F connector adapter, 2 x RJ11 and 2 x RJ45 patch cables, test leads with alligator clips, 2 x LANyards, quick start guide, 2 x 9 volt batteries



- **DET14C & DET24C Earth Test Clamp**
- Ground resistance range: 0.050 Ω to 1500 Ω
- True RMS Ground leakage current range: 0.2 mA to 35 A
- Auto ranging & HOLD function 4 digit plus 6 digit backlit LCD display
- High and low resistance alarms
- 256 test results storage & recall
- Real time date & time stamping of results
- Oval clamp for easy access to earth cables & earth straps
- 37mm dia conductor & 50mm earth strap capacity
- · Low maintenance flat jaw interface
- . EN61010 Safety rating CATIV 600V

Megger.

705-9422 Megger 1000-761 DET14C Earth Clamp Earth & Ground Resistance Tester 1500Ω CAT IV 600V

LRCD220 Loop & RCD Tester

- . Built-in protective front cover
- Tough rubber armoured case
- Weatherproof to IP54
- · High current loop testing · Phase to phase loop testing
- Auto RCD testing
- 1000mA RCD test
- · Phase rotation • 110V, 230V and 415V operation
- · Backlit display



MPN: LRCD220

MFT1731 Onsite Inst. Tester And Software

- The new MFT1700 series from Megger tests low voltage electrical installations to BS7671.
- Providing all the tests required to complete the necessary electrical certification for industrial, commercial
- and domestic fixed wiring installations.
- The unique design allows it to be operated while mounted on the floor, a ladder-shelf, platform, and held or hung around the neck



Megger.

712-5749

Megger LRCD220 Loop Impedance & RCD Combined Tester, Loop Impedance Test Type 2 Wire

MIT 300 Series Insulation & Continuity

- A range of insulation testers that meet the relevant requirements of EN61557, BS7671, HD 384, IEC 364 and VDE 0413 for applications in all aspects of electrical contracting. building maintenance, testing, inspection and servicing.
- 20mm LCD display with true analogue response
- Tough rubber armoured case with self contained display cove that locks away underneath the instrument during use
- . Designed to hang comfortably around the neck for hands-free, or for bench use
- Automatic 200mA fast continuity test on connection to the circuit
- Lead resistance nulling on continuity allows for use of fused test probes
- · Automatic discharge of circuit under test
- . Safety input terminal interlock prevents unsafe connection of test leads
- Intelligent Safety System even if connected to a live circuit whilst on continuity setting the tester will remain safe and undamaged
- . Live voltage warning alerts the operator when a circuit voltage over 25V exists when insulation testing
- Safety lockout prevents the test from operating when the circuit voltage is > 50V

Megger.

516-7710 Megger MIT320, Insulation Tester 999mΩ CAT III MPN: MIT320

MIT480 Series Telecom Insulation &

- continuity test • 50V & 100V insulation testing
- 100Gohms insulation range
- · MIT481 additional features • 50V, 100V, 250V, 500V, 1000V insulation tests
- 200Gohms insulation range · Leakage current display
- kΩ resistance measureme
- . Timer, PI and DAR insulation tests Insulation limit alarms
- 0.1nF to 10uF Canacitance measurement . Cable length calculated from an adjustable cable capacitance reference (default 50nF/km)

Megger.

611-1279 Megger MIT481, Insulation Tester 200GΩ CAT IV MPN: MIT481

Chauvin Arnoux Insulation and Continuity Testers for Industrial

- · Measurement of insulation over a programmed duration
- PI and DAR ratios to determine the quality of the insulation
- . Storage in memory to compare the measurement histories Display 2 x 4000 counts + logarithmic bar graph
- Compact (211 x 108 x 60 mm) and lightweight (850 g) Protection to IP 54

Maintenance



914-2888 Chauvin Arnoux C.A 6526, Insulation Tester 200GΩ MPN: CA6526 CAT IV 600V

HK\$4,767.22

Megger.

117-6030 Megger 1008-130 Electrical Installation Tester

MPN: 1008-130 HK\$12 782 13

MIT1025 10kV Insulation Tester Uk/Euro

- 10 TΩ (5 kV)/20 TΩ (10 kV) max. insulation resistance • Timed IR plus PI and DAR diagnostic tests
- Operate with dead battery when on line power/mains
- Rapid charge Li-ion battery up to 6 hrs continuous testing (5 kV) Dedicated voltmeter function (30V to



Megger.

763-9264 Megger MIT1025, Insulation Tester 25TΩ CAT IV MPN: 1001-946 1001-945 HK\$43,530.00

MIT500 Series Industrial Insulation Testers - 5 and 10kV • 10 TΩ (5 kV)/20 TΩ (10 kV) max. insulation resistance

- Timed IR plus PI and DAR diagnostic tests · Operate with dead battery when on line power/mains
- Rapid charge Li-ion battery up to 6 hrs continuous testing (5 kV) · Dedicated voltmeter function (30V to 660V)
- · CATIV 600V safety rating Large LCD display with automatic backlight
- . Noise filter rejects up to 3 mA noise High altitude operation up to 3000 m

Megger.

763-9267 Megger MIT515, Insulation Tester 10TΩ CAT IV MPN: 1001-935 1001-937 HK\$28,000.00

FLUKE 1587 Insulation Multimeter The LinkSprinter Network Tester provides quick

- simple and affordable network connectivity testing and troubleshooting that solves problems fast. Diagnose and test Power over Ethernet (PoE), Link to the
- switch, DHCP, Gateway, and Internet connection Get VLAN, switch name, and port information via
- delivered to color graded LEDs



914-5420 FLUKE 1587, Insulation Tester 2GΩ CAT III 1000V,

MPN: FLUKE-1587



HK\$9,460.00

HK\$5.040.00





FLUKE Networks IntelliTone LANTest Equipment of MPN: MT-8200-60-KIT HK\$1,778.65

MPN: 1000-761 DET14C HK\$14,260.00 Earth Clamp

Megger TDR 1000/3

- AUTO set up for instant use
- Ultra fast pulse for near end fault identification
- Trace HOLD feature to allow comparison between cables
- · IP54 rating offers real life working
- · Designed for use on all metallic cable pairs . Backlit graphics monochrome LCD (256 x 128)
- Adjustable display contrast
- Resolution to 0.1 m
- For use on Telecom TNV-3 circuit, or 150V CAT IV power circuits
- Power blocking filter not required
- Environmental protection to IP54

Megger.

764-2825 Megger TDR1000/3 TDR Cable Fault Locator, 5000m MPN:TDR1000/3

HK\$12,790.00

Testo 750-3 Voltage Tester

- Clear LED Display
- Fibre optic technology for optimum voltage indication . Anti-slip ring or secure grip
- Ergonomic handle shape
- Measuring point illumination
- Integral torch



Current Clamp Meter 4/40A AC/DC

ICMA1 Current Clampmeter 300A AC/

Automatically detect DCA/ACA with AC True RMS reading mode

Inrush Current Measurement for monitoring motor start up current

6000 count large scale LCD display with backlit

AC/DC current measuring capability up to 300Amps

Measures AC and DC current into the low milliamp range up to 40A

812-8910 ICMA1 Clampmeter, Max Current 300A ac, 300A dc MPN: ICMA1

- Auto Zero DC for correct measurement every time
- High 1 mA current resolution for quick circuit
- comparison on sensor and control circuits
- Auto ranging Data Hold

10mA Resolution

ISO-TECH

1.5% basic DCA/ACA accuracy

· Auto power off function



HK\$752.91



Testo 750-3 Voltage Indicator Continuity Check CAT 3 MPN: 0590 7503 1000V CAT 4 600V

HK\$842.81

Backlit display

FLUKE

BEHA AM

790-1222 Amprobe LH41A Clampmeter, Max Current 40A ac, MPN: LH41A 40A dc CAT III 300V

HK\$3,795,58

C.A 773 IP2X Voltage Absence Tester (VAT) CAT IV 1000V

- The C.A 773 IP2X Voltage Tester is a VAT with digital display and LEDs for voltages up to 1000VAC/1400VDC with with audible extended continuity and phase rotation testing.
- The Voltage Tester also offers trip testing of RCDs rated 30 mA (or less), as well as lighting of the test probe/point of measurement and digital display of the resistance and voltage.
- 1000VAC/1400VDC
- · Single-pole phase test
- . Continuity andresistance test with audible and visual indication
- Two-pole phase sequence test with 2-wire method
- RCD trip testing and Detection of stray voltages
- Lighting of point of measurement. CAT IV 1000V
- IP65



Meter

Cm174 600A AC/DC Imaging Clamp

• Work safely - scan a panel or cabinet for hazards

· Verify problems, check load and validate hot spots

. Narrow jaw and built-in work lights help you access

using IGM without direct contact

difficult locations with lighting issues

896-2183 Chauvin Arnoux CA773 Voltage Indicator with RCD MPN: CA773 DDT/VAT HK\$1,587.42
Trio Test Continuity Check CAT IV 1000V IP2X

AVO DCM 300E Fully IEC1010-1 and IEC101-2-032 compliant for circuits up to 500V phase to phase or 300V phase to earth CAT III or 600V CAT II

669-3493 FLUKE 773 Clampmeter, 100mA DC

30mA and 300mA ranges for leakage current measurement

FLUKE 773, Ma Process Loop Clamp

• Measures mA signals for PLC and control system analogue I/O

Detachable clamp head with extension cable for measurements

Measure 4 to 20 mA signals from transmitters

Measurement spotlight illuminates the test point

without breaking the loop

- 0.01mA resolution on 30mA range 30A and 300A ranges for power measurements
- · Data hold facility
- Maximum conductor size 40mm diameter
- 3200 count LCD display with analogue bar graph

Megger.

247-0142 Megger DCM300E Clampmeter, Max Current 300A MPN: DCM300E ac CAT II 600V, CAT III 500V

MPN: FLUKE-773

HK\$5,510.00

HK\$10.828.00

≎FLIR

Advanced electrical feature

66

922-6220 FLIR Clampmeter CAT III 1000V, CAT IV 600V

MPN: CM174

HK\$4,333.04

DigiFlex MA400D-170 Ammeter with flexible sensor

- · Measurement range starts at 20 mA, is designed for work in residential conditions and can also be used to check electricity distribution points up to 400 A Ammeter with a flexible sensor for measuring curren
- on electrical conductors up to a diameter of 45mm Measure the requirements of IEC 61010 CAT IV 600V
- Supplied with 2 x 1.5V AAA batteries, 1 elastic strap
- and an operating manual in 5 LANguages





778-1040 Chauvin Arnoux MA400D-170 Clampmeter, Max Current 399.9A ac CAT IV 600V

MPN: P01120575Z

HK\$1,282,70

Testo 755 Voltage Tester

- · Automatic measurement parameter detection
- Certified to DIN EN 61243-3:2010
- Measurement result without any switching on or selection
- · Measuring point illumination
- · Exchangeable measuring tips IP64 Rated
- Measurment Category: CAT IV 600V, CAT III 1,000V



Testo 770-1 Clampmeter

Innovative clamp mechanism for easy operation in narrow spaces

Testo 755-1 Voltage Indicator Continuity Check CAT 3 MPN: 0590 7551 1000V, CAT 4 600V

- Extra functions such as inrush, power and μA measurement
- Auto AC/DC
- True RMS
- Voltage measuring range: 1 mV to 600V AC/DC
- . Current measuring range: 0.1 A to 400 A AC/DC
- . Display (counts): 4000



905-5891 Testo Clampmeter CAT 3 1000V, CAT 4 600V

FLUKE 355 True-RMS, 2000A AC/DC

- · 4000 count backlit display
- . True-RMS AC + DC current & voltage measurement
- True RMS crest factor = 2.4
- Motor inrush current measurement . Min/Max/Average recording mode
- Frequency Measurement
- Voltage AC/DC
- Resistance measurement
- · Continuity measurement with beeper . 58mm dia conductor jaw capacity
- Safety to EN61010 CAT IV 600V, CAT III 1000V



411-970

FLUKE 355 Clampmeter, Max Current 2000A ac, 2000A dc CAT III 1000V, CAT IV 600V

FLUKE 381 Remote Display True-rms AC/ **DC Clamp Meter**

- · Wireless technology allows the display to be carried up to 10m away from the point of measurement for added flexibility
- Removable magnetic backlit display can be
- conveniently mounted where it is easily seen . 1000 A ac and dc current measurement with fixed jaws
- . 2500 A ac current measurement with iFlex flexible current probe
- . 1000V ac (true rms) and dc voltage measurement Frequency, resistance and continuity measurement
- Display HOLD, Min, max, average and inrush recording
- Low pass filter for stable readings in noisy environments
- CAT IV 600V, CAT III 1000V safety rating

FLUKE

705-1923

FLUKE 381 Clampmeter, Max Current 2500A ac, 999.9A dc CAT III 1000V, CAT IV 600V

FLUKE 374 and 375

- FLUKE 374 and 375 Clamp Meters with high performances. · Large backlit display
- 600 A ac and dc current measurement with fixed jaws • 2500 A ac current measurement with optional
- iFlex flexible current probe
- . 600V ac (true rms) and dc voltage measurement Capacitance, resistance and continuity measurement Display HOLD, Min. max, average and inrush recording.
- CAT IV 600V, CAT III 1000V safety rating
- 375 additional feature 500mV dc measurement range to interface with other accessories
- · Frequency measurement
- . Low pass filter for stable readings in noisy environments



MPN: 0590 7701

MPN: FLUKE-355

MPN: FLUKE-381

HK\$1,169.06

FLUKE.

914-5436 Clampmeter CAT III 1000V, CAT IV 600V

MPN: FLUKE-374 HK\$2.988.00

Testo 745 Non-Contact Voltmeter

- Filter for high frequency interference signals
- Adiustable sensitivity
- · Visual and acoustic signal
- Waterproof and dustproof, IP67 rated Measuring point illumination





Testo 0590 7450 Non Contact Voltage Indicator, 12V MPN: 0590 7450

Magnetic Field Indicator/Solenoid

- . The tip of the Magnet Stick lights up when in the presence of a magnetic field. It responds to all kinds of magnetic fields from alternating current to direct current and permanent strong magnets...A small test magnet is housed in the cap of the Magnet Stick to check that it is working correctly.
- This unit uses a magnetic read switch sensor





HK\$6,648.00

HK\$4,108.00

375-5422 RS Pro Magnetic Field Indicator 0.3mT

Motor And Phase Rotation Indicator

- . Rotary field Indicator LED indication of the three phases
- · Contact free determination of the rotation
- direction of running motors Magnetic field detection to detect AC solenoid valve



Motor rotation Indicator – LED display of motor rotation direction



893-7919 RS Pro Phase Rotation Tester CAT IV 600V CAT IV 600V 60Hz 400V AC/DC, Model DT-9020

HK\$329.51

FLUKE 9040

- . Indication of the three phases via LCD
- Indication of the phase rotation direction via LCD . Swift determination of the phase sequence in three-phase networks
- Voltage and frequency range suitable for industrial systems
- LC-display with good visibility in bright areas (i.e. outdoor) Non-Fused test probes (500mA 1000V fast acting)



· Technical Specification

FLUKE 9040/UK Phase Rotation Tester CAT III 600V, CAT IV 300V LCD CAT III 600V, CAT IV 300V 400Hz 700V, Model 9040/UK HK\$2,310.00



Keysight U1730C Series Handheld LCR

- · 20.000 counts resolution
- · 0.2% basic accuracy
- Wide LCR ranges
- · Auto identification (Ai) automatically determines and displays component type and measurements
- Detailed component analysis
- IR-to-USB connectivity for data logging to PC



Complies with ISO 3819

- Manufactured from Pvrex® borosilicate glass
- · Excellent thermal performance
- High resistance to chemical attack
- White graduations and marking spot



KEYSIGHT

738-9489

Keysight Technologies U1731C LCR Meter, Maximum MPN: U1731C Capacitance Measurement 20mF, Maximum Resistance Measurement 200 $M\Omega$

HK\$2,398.00

461-1121 RS Pro Borosilicate Glass Beaker, 400mL

Barometer For Atmospheric Pressure

- · Simple to operate with clear LCD display
- · Readings in mb (millibars), hPa (hectopascals) and mmHg (millimeters of mercury)
- Altitude correction for pressure at sea level
- . Minimum and maximum readings
- Dimensions 106 x 67 x 30mm



Hotplate, Aluminium Plate, 700W, 325Degc

Low Form Beaker W/Wht Graduations.

- Hotplate with a robust aluminium/silicon alloy top plate for an excellent heat transmission
- The top plate has a thin ceramic coating
- for added chemical resistance
- The hotplate is equiped with a microprocessor control
- A 700W element gives rapid heating and ensures a temperature distribution across the whole surface of the plate
- Flashing "Hot" warning light
- · Accurate temperature control with LED setting scale
- Compact spacesaving design

Stuart



Castle

909-1932 Castle GA600 Barometer

Mr176 Imaging Moisture Meter • Thermal Image Resolution: 4800 pixels (80 x 60)

- Lepton® thermal imager powers IGM technology
- Review images and generate reports with free FLIR Tools software

Testo 622 Temp/Pressure/Rh Recorder

Precise measurement of temperature, humidity and pressure

In laboratories, the testo 622 Thermometer hygrometer

is suitable for monitoring ambient conditions during calibrations or when setting up experiments

- · Rugged design with intuitive menu system
- · Compact for convenient carriage and use



HK\$1,237.50

Tpx Measuring Cylinder Class A 10MI

Stuart US150 Hot Stirrer, 700W, Aluminium, Silicon MPN: US150

- PMP confers hardness, solidity, low density,
- Calibrated to ISO 6706 and DIN 12681, class A tolerances
- Steam sterilisation at 121°C does not affect accuracy



HK\$123.41

HK\$3,107,00

≎FLIR

922-6236 FLIR MR176 Moisture Meter

· Large, optimally legible display

MPN: MR176

MPN: GA690

HK\$8.674.77

891-9987 RS Pro PMP Laboratory Cylinder, 10ml

Pp 1-Mark Class B Bulb Type Pipette,

- Calibrated to meet class B tolerances
- Permanently marked with ring and inscriptions

777-0444 Testo 0560 6220 Thermohyarometer. +60°C

MPN: 0560 6220

HK\$3,000.00

Wireless Weather Station With Bluetooth

- Bluetooth technology enables monitoring/recording weather condition on smart phone or tablet as well as at weather station
- Displays indoor/outdoor temperature and humidity (outdoor sensor supplied), Forecast, Alerts and Moon Phase
- Clock function syncs with phone (for accuracy)
- and updates for time changes · iPhone 4s (or above) or Bluetooth v4 enabled smart device
- . Software iOS 5 (or above) or Android 4.3 (or above)



Oregon Scientific Weather Station Thermohygrometer MPN: BAR218HG

HK\$761.90



478-1781 RS Pro Pipette PP 10mL

- . A versatile, hand held luxmeter with detachable light cell capable of measuring daylight, tungsten, fluorescent and mercury light intensity in either lux or foot-candles.
- Display hold function
- 3 ranges/times covered
- Auto power down
- RS-232 serial interface
- · Zero adjustment
- Dual LCD display with contrast control



180-7133 RS-105 Light Meter, 50000lx

HK\$220.74

Visit hken.rs-online.com to order today!



pH Sensor Glas

- ecoLine pH electrode, glass shaft design
- Glass shaft design

JUMO

FLUKE.

65 mm x 27mm

Basic dc accuracy 0.5%

· Automatic shutdown

Rugged, durable design

CAT III 600V safety rated

FLUKE.

RS-232 Interface

FLUKE.

· Diode and continuity test with buzzer

· Small lightweight design for one-handed use

790-4097 FLUKE-101 Digital Multimeter 600V ac

. Extreme ease of use through soft key menu access, ideal for unskilled operators

such as Volts and Current simultaneously

· Dedicated current ranges to measure do

leakage current (i-Leakage mode) . Math Functions: dBm, dB, Min, Max

FLUKE 8808A Multimeter, 5.5 digit

• 5.5 digit resolution with 0.015% basic dc V accuracy,

· Patented split terminal jacks for 2x4 Ohms function

Safety Rating EN61010-1 CAT I 1000V, CAT II 600V

• Programming LANguages/Modes: Simplified ASCI, FLUKE 45

414-193 FLUKE 8808A Digital Multimeter, 10A ac 750V ac MPN: 8808A

for precise 4-wire low ohms measurements

· Dual display to measure different signal characteristics

. Large and clear Pass and Fail indication based on user defined limits

607-8526

- · Wire or cartridge-style conductive system Application: Drinking water monitoring and preparation, Swimming pools, Aguariums and Greenhouse technology, etc.

Jumo 201005/51-18-22-0000-00-120/000,000 Glass pH Analysis Electrode

FLUKE 87-V Multimeters, 10A ac 1000V

. Unique function for accurate voltage and frequency

measurements on adjustable speed motor drives

Built in thermometer that conveniently allows you to take

freeing your hands for other tasks (see RS 480-2406)

Large digit display with bright two level backlight makes

Withstands hazardous 8000Volt spikes caused by load

FLUKE 87V significantly easier to read than older models

second edition IEC and ANSI electrical safety standards

switching and faults on industrial circuits and complies with

FLUKE 101 Digital Multimeter, 130 mm x

. This small, lightweight digital multimeter fits comfortably in your

hand but is rugged enough to withstand daily use for years to come

Optional magnetic hanger for easy setup and viewing while

temperature readings without having to carry a separate instrument

and other electrically noisy equipment

480-2355 FLUKE 87V Digital Multimeter



MPN: 201005/51-18-22-

MPN: FLUKE-87V

MPN: FLUKE-101

Measure up to 1000Volts with 6.5 digits resolution

Keysight 34410A Multimeter, 6.5 digit The Keysight 34410A is a high performance, versatile digital

multimeter designed for accuracy, high speed and precise triggering. It is a 6.5 digit, dual-display multimeter featuring 10,000 readings per second at 5.5 digits, datalogging wizard, resistance and frequency, and added LAN, USB and GPIB connectivity. An enhanced model is also available - 34411A (501-310).



TEST & MEASUREMENT

- 0.0030% 1-year basic dcV accuracy
- 0.06% basic acV accuracy
- 10,000 readings/sec @ 5.5 digits to the PC • 1,000 readings/s @ 6.5 digits direct to PC
- . LAN, USB & GPIB standard
- DCV. ACV. DCI. ACI.
- 2-wire and 4-wire resistance measurement with offset allowing accurate results in the presence of voltages
- Frequency, Period, Continuity, and Diode Test
- Capacitance & Temperature measurements Data logger with 50 k reading non-volatile memory
- . LXI Class C Compliance provides LAN transfer rates of over 250,000 readings/s



HK\$3.518.00

KEYSIGHT

Keysight Technologies 34410A Digital Multimeter, MPN: 34410A 3A ac 750V ac

8845A & 8846A 6.5 Digit Precision Multimeter

- FLUKE 8845A and 8846A are 6.5 digit precision multimeters that are able to handle measurements on the bench or in a system. Both feature a unique graphical display that can reveal signal quality issues like drift, intermittant and stability by using the analytical functions. The 8846A increases basic Vdc accuracy to 0.0025% plus adds measurements like capacitance, RTD temperature and dB. The 8846A also includes a USB device port to connect standard USB memory storage devices. Both instruments include an RS-232, IEEE-488 and Ethernet interface as standard, with popular DMM emulation modes which make system integration a simple task.
- 6.5 Digit Resolution Graphical Display
- Basic V dc accuracy of up to 0.0025%
- 100uA to 10A Current

FLUKE.

- 10 Ohm to 1 Gohm Resistance
- 2x4 Wire Ohms measurement technique Frequency, Period, Capacitance & RTD Temperature measurements
- Analytical Modes; Trendplot[™], Histogram and Statistics
- . USB Device Port, for memory storage devices
- RS-232,IEEE-488 and LAN interface

HK\$338.00

HK\$6.383.20

615-9978 FLUKE 8846A Digital Multimeter, 10A ac 1000V ac MPN: 8846A

Keysight 34460A & 34461A Truevolt **Digital Multimeters**

Truevolt DMMs are designed by the team that created the Keysight 34401A, the world best-selling digital multimeter. The measurements, reliability and familiarity of the 34401A are integrated in the design of the Truevolt 34460A and 34461A. Truevolt technology starts with an analog-to-digital converter which enables a patented metrology-grade architecture. Using this architecture, Keysight delivers a beautifully engineered balance of measurement resolution, linearity and speed at a value price.

Bright 4.3in (109mm) high-resolution colour graphical display

- · Press and hold a key to display built-in help · Display operation can be customised to meet user needs
- Customised labels can be added
- · Quick insight with graphical views of measurement results

Intuitive menu-driven interface



Keysight Technologies 34461A Digital Multimeter, 10A ac 750V ac

MPN: 34461A







69



TEST & MEASUREMENT

Keysight Multimeter/Power Supply

- Keysight digital multimeter/power supply U3606B combines a full featured 5.5 digit digital multimeter with a 30W power supply in a single, compact unit. It is capable of powering up a DUT while the instrument user simultaneously measures voltage, current and more. Measurement capabilities include: sweep function (ramp and scan) to simplify device characterisation for multi-level DC bias testing such as DC motor testing, transistor gain test, relay control and margin tests; low resistance measurement for higher accuracy.
- Full-featured 5 digit DMM • 5 digit, 120,000 counts resolution
- 10 measurement functions and 8 built-in math functions
- 4-wire low resistance measurement with 0.001 $m\Omega$ resolution
- 0.025% DC voltage accuracy

- . 0.01% + 3mV load regulation
- Over voltage (OVP) and over current (OCP) load protection



Keysight Technologies U3606B Digital Multimeter, MPN: U3606B 3A ac 750V ac

- Hall effect sensing of a.c. and d.c. current
- Power LED warns of low battery by flashing
- 1.5m flying lead terminated with 4mm shrouded plugs
- 2-032 installation CAT III 300V
- Withstands overloads to 500A



FLUKE i30 Multimeter Current Clamp Adapter AC/ MPN: i30 DC, 30A dc 30A ac, 19mm 653-6763

FLUKE Multimeter Test Leads

- Individual Replacement Case and Accessories for the Combo Kits
- CAT III 1000V, CAT IV 600V



456-0427 FLUKE TL910 Electronic Test Lead Kit

FLUKE Multimeter Test Leads and Probes

70

- 1 pair (red. black) 1.5 meter test leads with 90° angle shrouded.
- Meets CAT IV 600V, CAT III 1000V, 10A rating, UL listed



HK\$288 00

FLUKE

468-7415 FLUKE TL76 Test Lead Kit, CAT III 1000V, CAT IV 600V MPN:TL76

Multimeter Lead Set in Pouch

 Practical lead sets supplied in a durable grey pouch with attractive yellow piping. Standard Set has a wide range of accessories for taking measurements in most situations. Fused Set has additional fused test probes complying with the requirement of GS38 safety guidance for use on high energy circuits whilst taking voltage measurements. Both sets comply with IEC1010-1 cat III 600V safety standard. Contents standard set: 2 x 1.2m silicone multimeter leads with shrouded 4mm terminations one end straight, one end right angled, (red and black), 2 x crocodile clips (red and black), 2 x long reach multimeter probes with removable 4mm tip exposure adaptors (red and black), 2 x spring loaded, grabber multimeter probes (red and black), additional items in fused sets. 2 x fused probes with only 4mm of exposed metal tip fitted with 1.25in ceramic fuses rated at 660V 500mA



731-5277 RS Pro Test Lead Kit. CAT III 600V

HK\$419.15

Metrahit 2A

- Analogue Multimeter METRA HIT 1A/2A

- Battery for resistance measurement: 1x mignon cell AA 1.5 V
- . Extended current measurement: up to 15 A AC/DC

- Accuracy: Class 2.5



HK\$2,328,23

HK\$8,535.00

GOSSEN METRAWATT

493-8094

Gossen Metrawatt METRAHit 2A Analogue Multimeter 15A 500V

MPN: M101A

- Memory storage through FLUKE Connect® measurements app
- Colour LCD screen
- . 10 hour+ rechargeable battery
- 15 measurement functions
- Rugged design, able to withstand a 3 m drop
- CAT III 1000V, CAT

FLUKE.

111-5340 FLUKE-279FC Digital Multimeter

MPN: FLUKE-279FC

Idm66Rt Multimeter With Rms Measurement

- Display: 6000 counts
- Electrical Specifications:
- . AC Function: AC V and AC A specifications
- are ac coupled, true R.M.S
- · Crest factor may be up to 3.0 as 4000 counts AC/DC Voltage up to 1000V
- AC/DC Current up to 10A
- Resistance
- Continuity

ISO-TECH

796-1696 IDM66RT Digital Multimeter, 10A ac 1000V ac

MPN: IDM66RT

HK\$768.00

Fc Wireless Digital Multimeter

- AC and DC voltage measurements to 1000V
- Continuity, resistance, diode test, capacitance
- IP54



FLUKE 787 ProcessMeter"

- FLUKE 787 ProcessMeter[™] combined loop calibrator and digital multimeter is a rugged instrument for troubleshooting and calibrating current loop applications
- Precision 1000V, 440mA digital multimeter measure a.c. and d.c. volts, a.c. and d.c. current, resistance, continuity and frequency.
- True r.m.s. a.c. voltage measurement to 1kHz
- Frequency to 20kHz
- Min./Max./Peak Hold/Hold/Relative modes . Diode test and Continuity Beener
- d.c. current source/loop calibrator/20mA current
- source/simulator/% of scale readout
- Manual Step, Auto Step, Auto Ramp
- Clear LCD with backlight; 4000 counts; 30000 counts for d.c. current
- · Externally accessible battery
- · Closed-case, software calibration
- Designed to meet 1000V IEC 1010 Cat III 1000V
- Supplied with protective vellow holster with Flex-Stand™. safety-designed test lead set, 9V alkaline battery (installed)



263-2643 FLUKE 787 Digital Multimeter, 1A ac 1000V ac

MPN: FLUKE-787 HK\$7.658.00

Digital Multimeters

- 6000 count LCD with 33 segment bargraph
- . True rms (a.c.) measurement
- EN61010-1 safety standard compliance to Cat IV 600V & Cat III 1000V
- Resistance, continuity and diode measurem Capacitance measurement up to 10000µF
- Frequency measurement up to 100kHz
- Min/Max/Average recording
- Display and Auto Hold
- Separate battery and fuses access without
- breaking the calibration seal

FLUKE.

HK\$4.338.00

394-4492 FLUKE 179 Digital Multimeter, 10A ac 1000V ac

MPN: FLUKE-179

FL179E Electrical Multimeter with Premium Test Lead Kit

- FLUKE 179E kit is supplied with FLUKE 179E multimeter, AC285 SureGrip™ alligator clip set, TP38 slim reach probe set and TL224 SureGrip™ 1.5 m silicone insulated test leads with banana plugs. Please refer to premium test lead kit information sheet for additional information.
- 6000 Count LCD with 33 segment bargraph
- True RMS measurement
- EN61010-1 safety standard compliance to Cat IV 600V & Cat III 1000V
- · Resistance, continuity and diode measurement
- . Capacitance measurement up to 10000uF . Frequency measurement up to 100 kHz
- Min/Max/Average recording
- Display and Auto Hold

FLUKE.



- · Measurement parameter detection and selection via the socket assignment
- True root mean square measurement TRMS
- Large, backlit display
- Measurement Category: CAT IV 600V, CAT III 1000V



FLUKE 115 Multimeter

 Displays True RMS voltage and current readings with 600 count resolution, continuity and capacitance, making it perfect for quick verifications and field service use.

463-6401 FLUKE 179 Multimeter Kit, 10A ac 1000V ac

- Large white LED backlight Current measurement 20A (30 seconds
- momentary: 10A continuous)
- Resistance, continuity, frequency and capacitance testing capability
- 11A, 1000V FAST fuse (FLUKE part no. 803293)
- CAT III 600V safety rated

FLUKE

616-1454 FLUKE 115 Digital Multimeter, 10A ac 600V ac

MPN: FLUKE-115 EUR HK\$1,568.00

Visit hken.rs-online.com to order today!



U1273Ax Digital Multimeter

• 30000 count resolution

FLUKE.

- · Peak detect records transients as fast as 250us Measure upto 1000V AC/DC
- Low Pass Filter · ZLOW provides both high and low impedance
- modes to eliminate stray voltages OLED display with a 2000:1 contrast ratio and 160° vie



Keysight Technologies U1273A Digital Multimeter, 10A ac 1000V ac

IDM66RT Digital Multimeter with ICMA1

Clampmeter and IT-1 IR Thermometer

- Save money when you buy this great value bundle. IDM66RT Digital Multimeter
- AC Function: AC V and AC A specifications are ac coupled, true R.M.S.

768-4447

- . Crest factor may be up to 3.0 as 4000 counts AC/DC Voltage up to 1000V
- AC/DC Current up to 10A Resistance, Continuity, Diode, Capacitance up to 10mF,
- Temperature up to 400°C, Frequency up to 100kHz ICMA1 Clampmeter . AC/DC current measuring capability up to 300Amps
- Automatically detect DCA/ACA with AC True RMS reading mode 10mA Resolution, 1.5% basic DCA/ACA accuracy
- Inrush Current Measurement for monitoring motor start up current
- IT-1 Infrared Thermometer • The IT-1 is an infrared thermometer with a three-inone function of °C/F convertible infrared temperature







- · Prevents incorrect settings
- IP64 Rated


905-5882 Testo 760-3 Digital Multimeter

MPN: 0590 7603

MPN: 66RTA1IT-1

MPN: U1273AX

HK\$1.803.44



Visit hken.rs-online.com to order today!

Full-featured 30W. DC power supply 30V/1 A. 100 mA/30V. 8V/3 A and 1000mV/3 A







- i30 30A High Resolution, High **Bandwidth Current Probe**
- Zero adjust knob to accommodate offsets
- Designed to meet EN61010-1, EN61010-






















- Basic analogue multimeter with robust plastic casing Broad scope of application thanks to a large
- number of measurement ranges
- Additional features 2 A





- Wireless Trms Thermal Multimeter Full-featured digital multimeter with integrated thermal camera

Diode









HK\$2,588.00



FLUKE 117 Multimeter

- · Ideal meter for demanding settings like commercial buildings, hospitals and schools
- VoltAlertTM Technology for intergrated
- non-contact voltage detection AutoVolt feature for automatic AC/DC voltage selection
- LoZ: Low input impedance to eliminate stray voltage
- Large white LED backlight
- True RMS
- Min/Max/Average to record signal fluctuations
- . Current measurement 20A (30 seconds momentary: 10A continuous)
- Resistance, continuity, frequency and capacitance testing capability
- 11A, 1000V FAST fuse (FLUKE part no. 803293)
- CAT III 600V safety rated

FLUKE

616-1460 FLUKE 117 Digital Multimeter, 10A ac 600V ac

MPN: FLUKE-117 EUR HK\$1,878.00

FLUKE 116 Multimeter

- Specifically designed for HVAC professionals, FLUKE 116 digital multimeter has everything you need in an HVAC meter.
- Built in thermometer and temperature probe
- included for HVAC applications
- . Microamps to test flame sensors
- LoZ: Low input impedance to eliminate stray voltage
- . Large white LED backlight
- . Min/Max/Average to record signal fluctuations
- · Resistance, continuity, frequency and capacitance testing capability
- . CAT III 600V safety rated



616-1476 FLUKE 116 Digital Multimeter, 600μA ac 600V ac MPN: FLUKE-116 EUR HK\$1,778.00

FLUKE 27 II & 28 II: Rugged IP67 **Industrial Multimeters** · IP67 rated multimeter for operating in harsh conditions with

- features and accuracy to troubleshoot most electrical problems
- . Designed to withstand 3 metre drop • -15° C to + 55°C extended operating temperature range
- Extended AC voltage bandwidth, 15Hz to 20 kHz
- Average responding voltage and current for measurements
- Easy to read large digit display with a bright, two-level backlight
- Backlit keypad buttons allows for easy visibility in low-lit areas
- Reversible holster for added protection when not in use
- . Withstands hazardous 8.000Volt spikes caused by load switching and faults on industrial circuits
- . Sleep mode for long battery life
- · Relative mode to remove test lead resistance
- from low ohms measurements
- Min/Max and average recording
- Auto and manual ranging for maximum flexibility · Resistance, continuity and diode test



KEYSIGHT

72

669-8322 FLUKE 27-II Digital Multimeter. 10A ac 1000V ac

MPN: FLUKE-27-II

HK\$4 638 00

HK\$2,278.00


Keysight U1241B Multimeters

Enable users to check more with wider measurement ranges.

- Autoranging with MIN/MAX recording and HOLD
- True RMS Vac and Aac measurement
- Resistance, capacitance, frequency, continuity, diode test
- . Type K thermocouple input temperature measurement: (Requires U1180A thermocouple adaptor)



Keysight Technologies U1241B Digital Multimeter, MPN: U1241B 10A ac 1000V ac MPN: U1241B





Keysight U1253B Multimeter, 50000 count, USB Interface

- Ultra bright (OLED) wide angle display with analogue bargraph 50,000 counts dual display:
- Auto ranging with MIN/MAX recording, peak & display HOLD
- True RMS AC+DC measurements
- Resistance, capacitance, frequency, continuity & diode test
- Type J & K thermocouple input temperature
- neasurement: (Requires thermocouple adaptor) · % scale of 4-20 mA for process loop applications
- dBm/dBV measurement. Duty cycle. & pulse width measurement
- . 20 MHz frequency counter & square wave generator
- Manual and automatic data logging internally to DMM and externally to PC
- Optical USB interface (U1173A Optical USB
- interface cable available separately)
- Complies with EN61010-1CAT IV 1000V safety rating

KEYSIGHT

Keysight Technologies U1253B Digital Multimeter, MPN: U1253B 10A ac 1000V ac

200MHz, 4-Channel, Digital Oscilloscope

- 10M depth of memory
- · VPO waveform display technology
- Waveform update rate 120.000wfm/sec
- 8 inch 800 x 480 TFT LCD display
- Maximum 1Mpts FFT Digital filter function
- Segmental waveform and waveform search functions
- I²C/SPI/UART/CAN/LIN serial bus trigger and



HK\$6.428.00

ISO-TECH

896-7752 ISO-TECH IDS-2204E Digital Oscilloscope, MPN: IDS-2204E 4 Ch. 200MHz HK\$12.625.34

500MHz, 4-Channel, Visual Persistence Dso

- Dual sampling mode
- 25k Points memory for each input channel
- VPO technology to display less-frequently occurred signals . 8 inch 800x600 high resolution TFT LCD display
- · Unique split screen system with independent
- setting for each input channel
- 3 input impedance selections







798-9694 ISO-TECH IDS-3504 Digital Oscilloscope, 4 Ch, MPN: IDS-3504

PC Oscilloscope 8-Bit, 250MHz, 256Mb

- Superspeed USB 3.0 interface 500 MHz spectrum analyzer
- Arbitrary waveform generator Advanced triggers
- 100 million x zoom
- Mask limit testing Serial bus decoding



786-5520

Pico Technology Picoscope 6402C Digital Oscilloscope, 4 Ch. 250MHz Colour

MPN: Picoscope 6402C

HK\$24 846 00

HK\$38,483.00



Tektronix^a

768-3365

6GHz S/A

Spectral Analysis

Tektronix^a

500MHz

KEYSIGHT

Oscilloscopes

Be small, light and portable.

pico

· Mixed-domain Analysis

Oscilloscope, 100MHz, 2Channel,

- Wave Inspector® controls for ease of navigation
- and automated search of waveform data
- FilterVuTM variable low-pass filter for removal of unwanted signal noise while capturing high-frequency events
- 29 automated measurements plus FFT analysis for simplified waveform analysis
- . Trigger modes: Edge: Pulse Width: Runt: Logic: Sutup and Hold: Rise/Fall Time; Video + (MSO only) automated Triggering, Decode &

Tektronix DPO2012B Digital Oscilloscope, 2 Ch,

Search on parallel buses and Multichannel Setup & Hold Triggering TekVPI® probe interface supports active, differential and current probes for automatic scaling and units

Mixed Domain Oscilloscope 1GHz,

. Wave Inspector® controls provide easy navigation of time-

. Selectable spectrum time to discover and analyze RF changes

· Complex design issues can be resolved quickly and efficiently

Tektronix, MDO4104B-6 Mixed Domain Oscilloscope, MPN: MDO4104B-6 HK\$234,998.00 4 Analogue. Ch., 1GHz

over time, including changes on a stopped acquisition

Oscilloscope, Infiniivision, 4+16Ch,

Triggering: Edge; Pulse Width; Pattern; Rise/Fall Time;

Keysight Technologies, MSOX3054A Mixed Signal Oscilloscope, 4 Analogue. Ch., 16 Digital. Ch., 500MHz

The PicoScope 5000 Series incorporates valuable high end features

advanced triggering, automatic frequency-domain measurements, math, X-Y mode, digital filtering and segmented memory.

Come with an easy-to-use software development kit (SDK) which

and save and print captured waveforms. PicoScope software is regularly updated and currently includes an autosetup function

enables users to view real-time signals, zoom in on a signal

together with more than 30 automated measureme

Be powered from USB only. The 4-channel models come

design, research, test, education, service and repair

with an external power supply. Field applications include

as standard. These include mask limit testing, serial decoding,

Nth Edge Burst; Runt; Setup & Hold; Video; USB

• Update rates up to 1,000,000 waveforms/sec

• Input Z 1-M Ω or 50- Ω user-selectable, with

PicoScope 5000 Series PC

Memory depth 2M points (standard)

InfiniiMax auto-probe interface

correlated data from time and frequency domains

· Time-correlated analog, digital and RF signal

acquisitions in a single instrument

waveforms derived from RF input

· Amplitude, frequency and phase vs. time

7 inch (180mm) widescreen TFT-LCD colour display



TBS1102B 200MHz Digital Storage

- · 2-channel models
- . Up to 2 GS/s sample rate on all channels
- · 2.5k point record length on all channels
- Advanced triggers including pulse and line-selectable video triggers
- 7 inch WVGA (800X480) Active TFT Color Display



Tektronix^{*}

Tektronix TBS1102B Digital Oscilloscope, 2 Ch, 800-2981 MPN:TBS1102B HK\$7,738.00

HK\$13,698.00

- 1GSa/sec maximum sample rate
- Maximum memory depth per channel
- 5Mpts (IDS-300)/1Mpts (IDS-200)
- point control, landscape and portrait display)
- . 30,000 consecutive waveform records logging function
- Temperature measurement and logging function (IDS-300 only)
- 00000
 - Dimensions 240.2 x 136 x 59.7 mm
 - Weight 1.5kg approximately



ISO-TECH IDS-307 Digital Oscilloscope, 2 Ch, DC to MPN: IDS-307 70 (-3 dB)MHz

- . 3 selectable ranges up to 2000A a.c.
- Voltage output of 2V full scale for each range



Oscilloscopes

- · Equivalent-time sampling (ETS) mode . Built-in arbitrary waveform generator
- · Advanced digital triggers Persistence display modes



70MHz, 2 Channel, Digital Oscilloscope Two input channels

- 7 inch 800 x 480 full touch panel capacitive LCD (multi-
- Built-in DMM 50.000 counts (IDS-300)/5000 counts (IDS-200)
- Built-in calculator, SMD resistance coding, colour coding
- and attenuator calculation application software

ISO-TECH

- · Flexible and lightweight

- Pluas directly into instruments with 4mm input sockets
- Conforms to EN61010-1 CAT III 600V

645-1842 FLUKE i2000 FLEX Current Probe & Clamp MPN: i2000 FLEX



- Simple, low cost solution
- · Fast real-time sampling rates



MPN: PICOSCOPE

778-1841 Pico Technology PicoScope 5443A Digital

MPN: PicoScope 5443A

HK\$15,400.00

MPN: MSOX3054A HK\$160.954.18

ADDRESS

🏂 🏰 🐧 👺 🚨 🐧



Visit hken.rs-online.com to order today!

- 200MHz, 150 MHz, 100 MHz, 70 MHz and 50 MHz bandwidth models

- (anytime replay of measurement results)




i2000 Flex 2000A a.c. Current Probe

- . a.c. coupled output (no d.c. offset)
- . Fits around conductors up to 178 mm diameter
- · Suitable for use with multimeters, recorders and data loggers

FLUKE.

PicoScope 2200A Series PC

- Benchtop performance in pocket-sized scope
- 2 channels



793-3654 Pico Technology PICOSCOPE 2204A, 2 Ch, 10MHz





HK\$3,338.00

73

HK\$1,313.73

HK\$1.758.00

PicoScope 3000D Series Oscilloscopes

- Choice of bandwidths (50,70,100 or 200 MHz models)
- 2 or 4 analog channels, depending on choice of model
- 16 digital channels
- Up to 1 GS/s real-time sampling
- Up to 512 MS buffer memory
- . Built-in function generator and arbitrary waveform generator
- · Hardware-accelerated update rates



846-3428 Pico Technology PicoScope 3406D PC Oscilloscope, MPN: PicoScope 3406D HK\$16,576.00

Keysight Clamp-on Current Probe

- The Keysight 1146B AC/DC clamp-on current probe provides accurate display and measurement of currents from 100mA to 100Arms, dc to 100kHz, without breaking into the circuit.
- A battery level indicator and overload indicator help ensure proper readings.
- The probe connects directly to a scope through a 2m coaxial cable with an insulated BNC.
- The 1146B is recomended for use with Keysight scopes: MSO/DSO 2000X: MSO/DSO 3000X: MSO/DSO 4000X: MSO/DSO 6000X; DSO 5000A (100MHz); DSO 5000A (300 - 500MHz): MSO/DSO 6000A (100MHz): MSO/DSO 6000A (300MHz - 1GHz): MSO/DSO 7000A/B (100MHz - 1GHz)



KEYSIGHT

818-6802 Keysight Technologies 1146B Current Probe & Clamp MPN: 1146B

HK\$5 748 00

Pico 25MHz 1400V Differential Probe TA057, 20:1/200:1

- Pico TA057 is 25MHz bandwidth active differential probe suitable for high common-mode voltage measurement applications up to ±1400V (DC + peak AC).
- Bandwidth DC to 25MHz (-3 dB)
- Attenuation ratio 20:½00:1 Accuracy ±2%
- Rise time 14ns
- Input impedance 4MΩ II 5.5pF each side to ground
- Differential range (20:1) ±140V (DC + peak AC) or 140VRMS Maximum differential (200:1) ±1400V (DC + peak AC) or 1000VRMS
- Common mode range ±1400V (DC + peak
- AC) or 1000VRMS (20:1 & 200:1)
- · Absolute maximum voltage (differential or common mode) ±1400V (DC + peak AC) or 1000VRMS CATIII (20:1 & 200:1)
- Maximum amplitude ±7V into 50kΩ load
- Offset (typical) <±5mV
- Noise (typical) 0.7mVRMS
- Source impedance (typical) 1Ω @ 1kHz, 8Ω @ 1MHz
- CMRR (typical) 80dB @ 50Hz; 60dB @ 20kHz



pico

74

898-6766 Pico Technology TA057 Oscilloscope Probe 25MHz MPN:TA057

HK\$3.038.83

Pico 200A/2000A AC/DC Current Probe **TA167, BNC Connector**

- Pico TA167 is a dual-range current probe capable of
- measuring AC and DC current signals up to 2000A





898-6804 Pico Technology TA167 Current Probe MPN:TA167 HK\$2,109.93

FLUKE.

Large backlit graphics display

Integral site location and description

codes for faster data processing

797-6011 FLUKE Pass/Fail PAT 6500, Class I, Class II Test Type MPN: FLUKE-6500-2 UK HK\$19,982.00

Pico 60 A AC/DC Current Probe TA018.

Pico TA018 current probe can measure currents from 10 mA up to 60

A with a switch-selectable high and low range, A simple pushbutton

is included for zero adjustment when measuring DC current.

Input ranges (DC): Low (1mV/10mA) 10mA to

Input ranges (AC RMS): Low (1mV/10mA) 10mA

to 20A; High (1mV/100mA): 100mA to 60A

Operating environment 0 to +50 °C, 70% RH

 Battery type 9 V DC NEDA 1604, 6F22, 006P Battery life 100 hours typical with alkaline

898-6817 Pico Technology TA018 Current Probe

20A; High (1mV/100mA) 100mA to 60A

AC frequency range up to 20kHz

Maximum conductor size 9mm

Dimensions 195 x 70 x 33 mm

Oc4USB Interface

. OC4USB: Optical USB interface cable

BC430: Battery charger/mains adapter

flexible AC current clamps (2000 A)

for identifying cables (8 colours)

FLUKE

Flexible AC current clamps: Set of 4x i2000flex

WC100 colour localisation set: 32 metal clips

493-5540 FLUKE Cable For Use With USB-IR

FLUKE 6500-2 Pat Tester Uk Version

With nowerful auto test canabilities and simplified.

perform per day without compromising results

Integral QWERTY keyboard for rapid data entry

· Pre-set, auto-test sequences for user convenience

controls, including 'one touch' test routines, FLUKE

6500-2 PAT Tester increases the number of tests you can

FLUKE 6500-2 is suitable for testing both 230V and 110V

appliances, the 6500-2 model runs all the required safety tests:

(PE current, touch current, substitute current), Can test 110V

appliances (earth bond, insulation) via the 110V adapter kit

Earth bond low (low/high current, Insulation 500V, 250V, Leakage

Memory for back-up data storage and USB port for transfer to PC

. Output connectors BNC

pico

BNC Connector

M7050-V902 Master Packet Secutestbase10

- 8 test sequences for fast testing of simple devices
- An universal, selectable test sequence
- A test sequence performed by single measurements Test current for protective conductor testing: 200 mA and 10 A
- Revolutionary data management and storage concept for automated test sequences and single measurements with memory for up to 50,000 data records
- Pioneering operating concept with double rotary switch, direct selection keys and softkeys



HK\$30.378.40



876-4982

Gossen Metrawatt SECUTEST BASE10 Portable MPN: M7050-V902

MPN: OCALISE

Roll Of 1000 Pass Labels

- . Test date and retest date recorded
- · Appliance number field
- Strong adhesive
- . 1000 x Green Pass Labels

SEAWARD

803-9841



Seaward 91B038 Portable Appliance Tester Label, For MPN: 91B038

HK\$459.40

Hioki 3333 Power HiTESTER Single Phase AC Power Mete

- Rear screw terminal block ensures a secure safe connection for the unit under test.
- Six selectable current ranges from 50mA up to 20A
- AC- true RMS measurement
- Selectable VT & CT ratio setting for transformer imeasurements
- Triple LFD display with user selectable

666-4925 Hioki 3333 Power Meter, Model 3333, Absolute

MPN: Hioki 3333 HK\$15,960.00

FLUKE-435-II Power Quality & Energy **Analyser**

- FLUKE 434 Series II and 435 Series II offer the best in power quality analysis and introduce, for the first time ever, the ability to monetarily quantify energy losses. The new FLUKE 434, 435 and 437 Series II models help locate, predict, prevent, and troubleshoo power quality problems in three-phase and single-phase power distribution systems. Additionally, FLUKE-patented energy loss algorithm, Unified Power Measurement, measures and quantifies energy losses due to harmonics and unbalance issues, allowing the user to pinpoint the origin of energy waste within a system.
- Energy loss calculator
- Power inverter efficiency
- 400 Hz measurement captures power quality measurements for avionic and military power systems (437 Series II only)
- PowerWave data capture, Waveform capture, Automatic Transient Mode, Fully Class-A compliant, Mains Signalling
- Highest safety rating in the industry (600V
- CAT IV/1000V CAT III rated)

- Logger function
- View graphs and generate reports
- Seven hours operating time on the supplied
- SD card storage, 8GB card supplied and max capacity is 32GB

Tektronix

796-7367 Tektronix PA1000 Power Quality Analyser, Display Type Graphic Display MPN: PA1000 HK\$18.698.00

- **DC Power Analyzer Mainframe** Output speeds up to 160ms per step voltage change
- Voltmeter accuracy up to 0.016% + 1.5mV, up to 18 bits
- Ammeter accuracy up to 0.03% + 15µA, up to 18 bits Arbitrary waveform generator function - bandwidth up to 4500Hz, output power up to 300W
- · Scope function digitizes voltage and current
- at 50kHz, 4096 pts, up to 18 bits Datalogger function - measurement interval from
- 1ms 60s, max 500M readings per datalog . 64MB of non-volatile data storage for datalog
- scope traces and instrument settings
- All capabilities accessed without programming
- Intuitive, dedicated physical controls for common functions



711-0012

Keysight Technologies N6705B DC Power Analyzer Power Quality Analyser, Absolute Maximum Power Measurement 600W

MPN: N6705B

HK\$64 048 00

FLUKE-435-II Power Quality Analyser, Absolute Maximum Power Measurement 6000W, Display

MPN: FLUKE-435-II

- Energy loss calculator
- Power inverter efficiency Troubleshoot in real-time
- Highest safety rating in the industry (600V)
- Automatic Trending
- · Logger function
- rechargeable Li-ion battery pack

752-5004

MPN: FLUKE-434-II HK\$63,598.00

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

to expand the measurement display upto 92MW combinations of 3 measurement variables Selectable Averaging mode to minimize display fluctuations RS232C interface for PC measurement and data management HIOKI

- Power Analyser 600V 20A Rohde & Schwarz Power Analyser HMC8015
- HMC8015 is the first compact tester for AC/DC load and standby current characterisation to enable measurements without extra requirements such as computers or remote infrastructure. It features a numerical and graphical display with 26 key parameters. Its performance and compliance protocols accord with IEC 62301, EN 50564 and EN 61000-3-2.
- · Clear display of all measured parameters
- Measurement accuracy
- . Everyday measurement functions



Rohde & Schwarz Power Quality Analyser, Absolute MPN: HMC8015 Maximum Power Measurement 12kW, Display

- Power Analyzer, 1-Phase, 0.05%
- · Full colour display with waveforms, harmonics and bar charts . Dual shunts for accurate measurements from as low as 40mA . Special measurement modes that simplify testing of lighting
- ballasts, inrush current and energy consumption • Full compliance testing for EnergyStarTM, IEC50564, IEC62301 and other standards aimed at lowering power consumption Harmonics, colour display, interfaces and software all included











- - Troubleshoot in real-time
 - · Measure all three phases and neutral
 - · Automatic Trending
 - System-Monitor

 - rechargeable Li-ion battery pack

FLUKE

752-5008





- CAT IV/1000V CAT III rated)
- Measure all three phases and neutral
- · System-Monitor
- · View graphs and generate reports Seven hours operating time on the supplied
- SD card storage, 8GB card supplied and max capacity is 32GB



FLUKE-434-II Power Quality Analyser, Absolute Maximum Power Measurement 6kVA, Display Type LCD













HK\$93 198 00



HK\$1,610,00

HK\$3.696.60

FLUKE 43B Power Quality Analyser

- FLUKE 43B Power Quality Analyser
- Voltage, current and power harmonics to
- the 51st, phase angle and THD
- . Sag and swell measurement down to one cycle, recorded over time Voltage, current and frequency measurement,
- and waveform display
- · Power measurements watts, power factor,
- displacement power factor, VA and Var · 20 measurement memory to save/recall
- screens and data with cursor readings
- Captures up to 40Voltage transients
- · Ohms, continuity and capacitance measuremen
- Temperature scaling for temperature accessories

FLUKE

413-0004 FLUKE-43B Power Quality Analyser, Absolute Maximum Power Measurement 1.56GW

MPN: FLUKE-43B/004 HK\$32,838.00

I5sPQ3 5 A current clamps . Set of three clamps specifically designed to

- measure low currents from 0 to 5 A.
- · This economical set is ideal for use with three phase measuring instruments.
- Accurate measurement without cutting off the circuit.
- . CAT III 600V compliant



FLUKE

611-3247

FLUKE i5s PQ3 Power Quality Analyser Clamp, Accessory Type Clamp, For Use With 434 Series, 435 Series

MPN: i5s PQ3

HK\$11.123.05

FLUKE 17XX i40s-EL Clamp-on Current **Transformers (3pk)**

- FLUKE i40s-EL Current Clamp-on Transformer is used for low current measurement, suitable for making measurements up to 40A and also measures accurately on 1A and 5A secondary current transformers.
- The i40s-EL iaw is capable of being clamped on current conductors up to 15mm in diameter



FLUKE

901-0015 FLUKE-17xx i40s-EL, 3 pack Energy Monitor Clamp, For Use With FLUKE 1730 Energy Logger FL®3 pack FLORE 17xx i40s-

Digital Manifold, Gauge 549

- Measures high side/low side pressure and indicates saturation and evaporation temperature
- · Fast and accurate determination of system parameters
- · 60 refrigerant profiles · Drop resistant

76

- Superior rugged housing construction
- Splash proof, protection to IP42



913-2623 Testo 0560 0550 Digital Pressure Meter 870psi, Model Testo 549 MPN: 0560 0550 HK\$1,910.36

Pm-80 Gas Press Digital Meter, 0-130Mbar

- Differential input 8mm tube connectors
- Water resistant (IP67 rated)
- Rugged case with protective rubber boot Magnetic attachment or tilt stand
- Push button "Zero" and "Hold" features
- Backlit digital display Auto power off after 12 minutes
- · 0-130 mbar measurement

digitron'

460-9780 Digitron PM-80 Digital Pressure Meter 130mbar, Model PM

MPN: PM-80

C9507/Is Comark Press Meter, 0To+/-

- IP67 rated to prevent dust and moisture ingress
- · Choice of 9 displayed scales . Min/Max and Hold functions
- Adjustable zero
- Transient reading averaging filter
- Auto switch off
- Accuracy: ±0.2 Operating temperature range: 0 to 50°C
- Dimensions (mm): 173 x 83 x 32



312-1122 Comark C9507IS Digital Pressure Meter 7bar, Model MPN: C9507IS

DPI705 Series Handheld Pressure Indicators

- . The DPI705 Series of handheld pressure indicators is a family of advanced new products combining new materials and technical innovation. It is designed for single-handed operation and offers an abundance of features to employ low-cost solutions to routine maintenance and system troubleshooting tasks.
- No warm-up time
- Ambient temperature F and °C reading of local condition ±3F (±1.5°C)
- 0.1% full scale (FS) accuracy
- Rugged, lightweight handheld design
- · Leak test, tare, max/min and filter
- · Standard 60 second leak test
- · Zero pressure correction
- Tare 0 to 100% FS zero offset capability
- Impact resistant, sealed to Type 12/IP54 High resolution LCD display
- Adjustable, high pressure alarm with visual and audible warning
- Power management features include low battery
- indicator and selectable 'auto off'
- Integral desk stand and hanger
- . Supplied with Carrying case with belt loop



787-4603

Druck DPI705R-11G Digital Pressure Meter 10bar, MPN: DPI705R-11G Model DPI705R

Dpi615Pc/Is Pressure Calibrator, 20 Bar

- Intrinsically safe
- Pressure/vacuum pump -850mbar to 20bar · Integral combined pressure/vacuum pump
- . Dual display simultaneously indicating input and output values
- . 4 to 20 mA loop test, Leak test, max/min and filter
- Ambient temperature measurement





532-7631 Druck I615SPC-13G Pressure Calibrator 20bar Gauge, MPN: I615SPC-13G HK\$54,001.18 Model DPI 615



Low Pressure Test Pump LTP1

- Dual source pneumatic pressure and vacuum
- Generating up to 3 bar pressure or -900 mbar vacuum

PV211 Pneumatic Pressure Hand Pump • The PV211 pneumatic hand pump is lightweight, easy to use

and generates pneumatic pressure in excess of 25 bar. It is

an ideal tool for calibration checks on pressure transmitters.

switches, indicators, recorders and controllers when used in

. Dual source of pneumatic pressure and vacuum

DPI104 Digital Pressure Indicators

 The Druck DPI104 series is a robust, reliable and simple-to-use micro-processor controlled, network capable digital pressure

gauge. It is an accurate and convenient replacement to standard

used in conjunction with a pneumatic or hydraulic hand pump.

functions, analog output and a pressure switch test function

analogue test gauges and can function as a master test gauge when

Features include 0.05% full scale accuracy, min/max, tare and alarm

Adjustable stroke for overpressure protection

Integral fine control and pressure release

Generates vacuum to 96%

0.05% FS Accuracy

· Pressure switch test

0-5V analogue output

RS232 interface

787-4647

· Adjustable mounting position

· Supplied with swivel adaptors

. Large easy to read 5 digit LCD display

Bar graph and % pressure indication

· Ideal replacement for analogue gauges

· Peak hold, max, min, tare and alarm functions

conjunction with the RS range of pressure indicator/calibrators

Druck PV210 Pressure Pump, Pressure Connection ¼ MPN: PV210 BSP, Pump Type Hand 587g 2bar

Druck PV211-P Pressure Pump, Pressure Connection MPN: PV211-P ¼ NPT, Pump Type Hand 1lb 25bar

- Fine volumetric pressure or vacuum adjustment
- Output pressure 3000 mbar • Output vacuum -900 mbar
- · Sensitivity 0.1 mbar
- Dimensions H. 170 x Dia. 46mm, Wt. 587g



Fast Response Probe For Thermometer

- For use with Testo 922/925/935 wide range thermometers
- Fast-action surface probe with sprung thermocouple strip
- Suitable for uneven surfaces
- Measurement range short-term to +500°C
- Thermocouple Type K



HK\$4.755.58

516-0618 Testo 0602 0393, Probe For Use With 922

MPN: 0602 0393

MPN: FM25

FM25 - 2 Channel RF Digital

- · Wireless signal from remote sensors to base station
- Selectable Temperature Unit °C or F
- Magnetic, wall mounting or free standing fixing base
- clips or alternative suction cups





Digitron FM25 Digital Thermometer, 2 Input Recording, PT100 Type Input 712-1110

- Type K Fine Wire Thermocouples



409-4908 RS Pro 1000mm Cable K Type Thermocouple 0.2mm x -50°C to +250°C

Counter Timer, 300MHz, 50Ps Resolution

- Graphical, multi-parameter timer/counter display
- · High resolution down to 50 ps single shot (time)
- Measurements to 12 digits/sec (frequency)
- Fast USB/GPIB bus transfer speeds Super fast measurements (250k/s) to internal memory



Druck DPI611 Hand-held Pressure Calibrator

Druck DPI104-18G Digital Positive Pressure Gauge Hydraulic, Pneumatic 200bar ¼ NPT, BSP ¼, Interface Type RS232

- . The Druck DPI611 hand-held pressure calibrator combines pressure generation, signal measurement and loop power This 4th generation family of instruments provides all the convenience and reliability of the 'Druck' but offers twice the performance in a product which is half the size.
- State-of-the-art analog and digital microelectronics, reducing size of PCA
- . Truly hand-held 50% smaller and 33% lighter than the DPI610
- . Generates 0 to 20 bar/300 psi within 30 seconds Creates 95% vacuum
- · Touch screen interface with application DASHBOARD, quick TASK and FAVOURITES storage
- · Fast, three-task set-up for any application · Calculates PASS/FAIL errors, documents results and interfaces with calibration software
- Rugged and waterproof materials/construction



Druck DPI611-13G Pressure Calibrator 20bar Gauge, MPN: DPI611-13G

MPN: DPI104-18G



712-1157 Tektronix FCA3100 Frequency Counter 300MHz

Afg21112 Function Generator 12MHzcounter

- Sine, Square, Triangular, Noise and Arbitrary waveforms
- 0.1Hz resolution of Sine, Square and Triangular waveforms
- 1% 2 99% adjustable duty cycle for Square waveform
- Amplitude, DC offset and other key setting information
- USB device interface for remote control and waveform editing

781-6843 Waveform Generator 12MHz

HK\$33 998 00

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

HK\$959.50

Thermometer


- · Both channels displayed simultaneously
- Remote sensors equipped with spring action
- · Audible and Visual Alarm with 15 minute delay






HK\$6,867.83

Fine Wire Type K Thermocouple, Pffe 1M















Tektronix^{*}







displayed simultaneously on the 3.5in LCD screen















MPN: FCA3100

77

HK\$11.098.00

Keysight 33500B Series Waveform

 Keysight 33500B Series waveform generators incorporate Trueform signal-generation technology, which combines the best of direct digital synthesis (DDS) and point-by-point architectures. It delivers increased performance at a price associated with DDS only. The 33500B models offer lower litter and lower harmonic distortion than alternative instruments in the same class. The jitter performance gives users the ability to place edges more accurately, helping reduce timing errors in circuit designs. Total harmonic distortion is less than 0.04% and non-harmonic spurs are less than 75dBc. This means clean signals that do not introduce noise, giving users greater accuracy. The litter rate, together with 8.4ns rise and fall times, enables users to set trigger points more accurately. The 16 bit resolution of the 33500B models facilitates output changes down to 1uV, providing users with the ability to test low-voltage circuits and designs.



- Waveform summing and combining capability
- Variable-bandwidth noise
- Waveform sequencing
- · Pseudo-random binary sequence pattern generation



Keysight Technologies 33511B Function Generator 20MHz Ethernet, GPIB, LAN, USB MPN: 33511B 763-9125

HK\$16.948.00

3MHz Function Generator & Freq Counter

- 6 Digit LED read out generator frequency
- · Duty cycle control
- · External voltage controlled frequency
- · Variable d.c. offset
- Built in 6 digit frequency counter with 150MHz range (external input)



ISO-TECH

Function Generator, 20MHz

 Keysight 33200A Series Function Generators The Keysight 33220A is a BenchVue enabled, 20MHz function/ arbitrary waveform generator which offers uncompromising performance for functions, pulses and arbitrary waveforms. It features direct digital synthesis (DDS) of sine and square ramp, triangle, noise and pulse generation with variable edge, and DC waveforms. AM, FM and PWM Modulation,

linear & logarithmic sweeps and burst are all standard

376-0200 ISO-TECH GFG-8216A Function Generator 3MHz



KEYSIGHT 667-2597

Keysight Technologies 33220A Function Generator MPN: 33220A 20MHz GPIB, LAN, USB

MPN: GFG-8216A

HK\$23.018.00

1 Channel Arbitrary Waveform Generator

- Up to 40MS/s sampling frequency
- · 64k point horizontal resolution 256k point non-volatile waveform memory
- · Storage for 100 waveforms and 9 set-ups
- . True variable clock architecture eliminates iitter
- . Extensive waveform creation and editing



78

387-4905 Aim-TTi TGA1241 Waveform Generator 16MHz

MPN:TGA1241

Keysight 33210A Function Generator

 The Keysight 33210A function/arbitrary waveform generator uses direct digital synthesis (DDS) technology to create a stable, accurate output signal with inherently clean, low distortion sine waves. The 33210A can generate variable-edge-time pulses up to 5MHz. Its variable period, pulse width and amplitude make it ideally suited to a wide variety of applications requiring a flexible pulse signal. Keysight IntuiLink software is supplied free with the



complex waveforms using PC applications such as Word and Excel via USB, GPIB or LAN. Alternatively, the LXI interface allows control of the AWG with a web browser. USB, GPIB and LAN (LXI) interfaces included · Graph mode for visual verification of signal settings

33210A, enabling users to easily create, edit and download

- · Direct digital synthesis of sine and square ramp, triangle, noise and pulse generation with variable edge, and DC waveforms
- AM, FM, and PWM Modulation, linear & logarithmic sweeps and burst are all standard

KEYSIGHT

Keysight Technologies 33210A Function Generator MPN: 33210A 10MHz GPIB, LAN, USB

Tektronix Arbitrary/Function Generators Series AFG1000

- · Entry-level arbitrary/function generators are designed to appeal to educational institutions wanting to fit out their laboratories with modern, flexible test instrumentation capable of high performance at an attractive price.
- 125 MS/s sampling rate and 14-bit vertical resolution enable great signal fidelity
- 1 mVn-n to 10Vn-n output amplitude over
- the whole frequency range Intuitive user interface shortens the learning
- curve for students and other users 2 to 8,192-point length of memory for user
- defined arbitrary waveforms
- 64-MByte internal non-volatile memory for arbitrary waveform storage
- Standard USB host/device for memory expansion and remote control
- Continuous, sweeping, burst and modulation modes
- Built-in 200 MHz counter with 6-digit resolution
- Menu and online help in English and Simplified Chinese

Tektronix^{*} 855-5078

Tektronix AFG1022 Waveform Generator 10 MHz, 12.5 MHz, 25 MHz

MPN: AFG1022



Datalog Personal Noise Exposure Meter

- Multiple file saving using on board Flash memory
- Dual channel measurements for Lp and Leg Simultaneous measurement of Lp, Leq, Apeak or Cpeak
- or Zpeak, Lep,d, LAE, Dose, Dose/Hour and Pa2H
- Channel Independent Frequency Weighting Selection 'A', 'C' or 'Z'



Castle

909-1926 Castle L Sound Level Meter 69 -> 143 dB

MPN: GA257L

SIm1352P Sound Level Meter

- Autoranging
- USB data interface
- Ranges from 30dB to 130dB between 31.5Hz and 8kHz
- 4 digit LCD display with a 0.1dB step
- · Datalogging capacity up to 32000 records Alarm setting facility ('over' and 'under' limits)
- MAX hold function
- Both a.c and dc signal output suitable for a frequency analyser, level recorder,FFT analalyser,graphic recorder,etc



HK\$7,487.50

ISO-TECH

743-4766 SLM 1352P Sound Level Meter 8kHz

MPN: SLM1352F



Checktemp Pocket Thermometer

- Temperature range -50 to +150 °C
- Resolution 0.1 °C
- CAL CHECK[™]
- · Ideal for spot checks

- Weight 50g



- Reading hold function
- °C or F display



ISO-TECH

697-3803 ISO-TECH SLM52N Sound Level Meter 8kHz 30 → 130 dR

· Manual data memory storage and recall of 99 sets of readings

Ndm1354 Personal Noise Dosemeter

individuals moving between areas of varying noise levels and

provide unsupervised exposure assessments of the working

environment by measuring accumulated noise exposure.

· The results obtained from such assessment can be used

to determine whether action needs to be taken to reduce

noise exposure, in accordance with the Health & Safety

at Work Act and Noise at Work Regulations 1989.

Measures personal accumulated noise exposure

in a period with the unit of % noise dose

70 to 140dBA sound level measurement

SIm52N Sound Level Meter

· 4 digit LCD display with analogue bargraph 30 to 130dB measurement in 5 ranges

0.1dB Resolution, 60dB Dynamic range

A and C Frequency weighting

· Fast/Slow time averaging

· Accurate and simple to use

· Clear LCD display

ISO-TECH

· The personal dose meter is designed to be carried by

697-3800 NDM 1354 Sound Level Meter 10kHz 70 -> 140 dB MPN: NDM1354

HK\$1,919.00

Ga 2002 General Purpose Vibration

- Small, lightweight reliable instrument providing all the fundamental vibration measurements in a single key stroke, at an economical price
- Integral mechanical and linear filters
- · Datalogging of 9 data points
- Acceleration, Velocity & Displacement parameters





Thermometer Type K Thermocouple Input

- 3 ½ digit backlit LCD display with maximum reading 1999 . Type K thermometer with single input measurement
- Readout in °C, F or Kelvin (K) MAX and display HOLD
- 60Vdc or 24 Vrms ac maximum input voltage
- on any combination of input pins
- Reading rate 2.5 times per second Auto Power Off
- · Input connector accepts standard miniature thermocouple
- connectors (flat blades spaced 7.9 mm centre-to-centre)
- Dimensions 162 x 76 x 38.5 mm
- Weight 210g




RS Pro RS41 Digital Thermometer, 1 Input Handheld,

Visit hken.rs-online.com to order today!

206-3722 RS Pro RS51 Digital Thermometer, 1 Input Handheld, K Type Input

- **FLUKE 54-II Thermometer**
- · Data logging up to 500 points of data with user adjustable recording interval
- Dual input
- Additional thermocouple types N, R, and S Real time clock captures the exact time of day when events occur
- Recall function allows logged data to be easily reviewed on the meter display
- You can transfer the contents of the thermometer's
- FLUKE 53-2B & 54-2B Compatible with FLUKE FVF- SC2
- FLUKEView software and USB lead RS 385-0599 IR communication port allows data to be exported to optional FLUKEView™ Temperature PC software





3Display Indoor/Outdoor **Thermometerclock**

- Large 3 channel LCD display
- Displays time, temperature (select indoor or outdoor) and Relative Humidity
- 3m external temperature sensor
- 0 °C 2 +40 °C (resolution 0.5 °C) ambient operating temperature
- °C/F selectable
- 12//24 hour time selectable



HK\$264.62

Visit hken.rs-online.com to order today!

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.



MPN: GA2002





736-1501 FLUKE 54 II Digital Thermometer, 2 Input Handheld, MPN: FLUKE-54-2 B E, J, K, N, R, S, TType Input








408-6109 RS Pro #2410WC Digital Thermometer, 3 Input LCD



TEST & MEASUREMENT









RS Pro RS51 Digital Thermometer

- SingleType K bead thermocouple supplied









Rs-1327K Ir Thermometer + Socket For

- · Pocket sized pistol grip
- . Built-in laser sighting
- . Backlit LCD display
- Auto HOLD
- MAX/MIN reading Adjustable emissivity
- High/Low audible and visible alarm (presettable)
- Data memory (50 measurements) and read function from LCD display
- Selectable C°/F



411-122 RS-1327K IR Thermometer

It-1 Infra-Red Thermometer

- Large scale LCD display infrared thermometer Single point laser sighting
- Integrated non-contact AC voltage detection
- 60VAC 2 600VAC with LCD indication Ultra bright white LED torch
- Single AAA size battery operation
- · Pocket clip designed for easy carrying





757-5129 RS Pro IT-1 IR Thermometer

Ti450 9Hz Thermal Imager

- Get 4x the pixel data with Super Resolution, which captures multiple images and combines them to create a 640 x 480 image
- Capture a clear, accurate image focused throughout the field of view with MultiSharp™ Focus
- · Get the context of the visual and infrared details all in one precisely
- blended or picture-in-picture image with IR-Fusion®technology
- · Monitor processes with video recording. video streaming and remote control
- Interchangeable smart lenses, 2x & 4x telephoto & wide angle (available seprately)



922-4826

Detector 320 x 240 pixels

FLUKE

80

1 handed, user friendly interface

FLUKE Ti450 Thermal Imaging Camera, Temperature MPN: FLK-Ti450 9HZ HK\$89,630.00 Measurement Range: -20 -> +1200 °C

FLUKE Ti400 Thermal Imaging Camera

Capture 5 additional measurements using the Wireless CNX

Detect and communicate your issues faster using the patented FLUKE IR Fusion technology featuring AutoBlend mode

System for more comprehensive analysis and reporting

· Faster communications with wireless imagery

transfers directly to PC, Apple iPhone or iPad

• Rugged, high resolution 640 x 480 capacitive LCD

· Capture additional digital pictures to show the location or

site details using the IR PhotoNotes Annotation feature

788-4662 FLUKE FLK-Ti400 9Hz Thermal Imaging Camera, Temperature Measurement Range: -20 → +1200 °C

touch screen provides fast menu navigation

· Standard and radiometric video recording

MPN: FLK-Ti400 9HZ HK\$83,288.00

≎FLIR

FLIR C2 Thermal Imaging Camera, Temperature Measurement Range: -10 -> +150 °C

Tis75 Thermal Imager, Manual Focus

Manual focus flexibility for quality images as close as 0.15 m (6 in)

Professional quality images at 320 x 240 resolution

· Exact location viewing with precisely blended IR-Fusion

Easy pinpointing of problems with built-in laser pointer

Easy-to-use user interface with one-touch image access

Flir One Thermal Imaging Camera For

• Visible camera: VGA 640 x 480 (used for FLIR® MSX® blending)

 Device compatibility: Apple products containing a lightning connector, including iPhone 6 and 6 plus, among others

Colour palettes (B/W, W/B, rainbow, contrast, arctic, hot/cold, iron)

FLIR ONE for iOS Thermal Imaging Camera, Temperature Measurement Range: -20 -> +120 °C

Features include FLIR ONE Panorama™, FLIR ONE TimeLapse™,

• Scene temperature range: -4°F to 248°F (-20°C to 120°C)

Operating temperature: 32°F to 95°F (0°C to 35°C)

. Sensitivity: ability to detect temperature

differences as small as 0.18°F (0.1°C)

. MSX blending (adds visible spectrum detail to thermal images and enhances resolution)

FLIR ONE Paint™, and FLIR ONE CloseUp™ functions

C2 Pocket-Sized Thermal Imaging

The world' first full-featured, pocket-sized thermal camera

Lightweight, slim profile fits comfortably in any work pocket

It is equipped to find structural defects, plumbing issues and to find hidden heat patterns that signal energy waste

designed for building industry experts and contractors.

FLIR C2 Compact Thermal Imaging System

FLUKE TIS75 Thermal Imaging Camera, Temperature MPN: FLK-TIS75 9HZ HK\$75,320.00 Measurement Range: -20 -> +550 °C

Excellent performance even when user needs

visual and infrared images or picture-in-picture

33% more inspection viewing area with the 3.5 in,

320x240 LCD (as compared to 3.0 in LCD screen)

Knowledge of power level – rechargeable

batteries with level indicator

FLUKE

Still image capture

\$FLIR

Camera

HK\$430.00

910-8043

a safe distance with a D:S of 504:1

MPN: FLIR C2

MPN: FLIR ONE for iOS HK\$2,326.64

TC7000 Intrinsically Safe Thermal Imager

- Scene temperature range: -4°F to 248°F (-20°C to 120°C) Operating temperature: 32°F to 95°F (0°C to 35°C)
- Visible camera: VGA 640 x 480 (used for FLIR® MSX® blending)
- . Sensitivity: ability to detect temperature
- differences as small as 0.18°F (0.1°C) Device compatibility: at least Android Version 4.4.2, GPS,
- Location, OTG USB, Flashlight, Microphone Capabilities
- Colour palettes (B/W, W/B, rainbow, contrast, arctic, hot/cold, iron)
- MSX blending (adds visible spectrum detail to
- thermal images and enhances resolution)
- Android version rs.883-7043

CorDEX

778-5124

CorDEXTC7000Thermal Imaging Camera,

MPN:TC7000

HK\$72,326,50

HK\$7.101.84



E60 Thermal Imaging Camera With WiFi

- Display: Touch screen, 3.5 in. LCD, 320 '240 pixels
- IR resolution: 320 ' 240 pixels
- MSX resolution: 320 ' 240 pixels Field of view (FOV): 25° ′ 19°
- . Image frequency: 60 Hz
- 2% accuracy
- Zoom: 2 x and 4 x digital zoom, including panning
- Interfaces: USB mini-B, USB-A, Bluetooth, Wi-Fi, composite video
- Battery operating time: Approx. 4 hours



922-4823

FLIR E60 Thermal Imaging Camera, Temperature Measurement Range: -20 to +650 °C

Testo 869 Thermal Image



Testo 869 Thermal Imaging Camera, Temperature Measurement Range: -20 → +280 °C

FLIR T420bx Infrared Camera with WiFi

resolution (320 '240), an ergonomic rotating optical block, and

• The FLIR T420bx Infrared Camera provides superior thermal

fast auto-focus to help the busiest technicians get the best

· Interfaces: USB mini, USB-A, Bluetooth, Wi-Fi, composite video

FLIR TG165 Imaging IR Thermometer

FLIR TG165 Imaging IR Thermometer easily finds unseen hot

and cold spots for instant troubleshooting. It can store images

and data to include in reports. Equipped with FLIR's exclusive Lepton® micro thermal camera, TG165 helps you identify heat

and data for reports. With a spot ratio of 24 to 1, you can take

accurate readings from safer distances. The TG165 is simple to

operate, featuring intuitive menu icons and dual laser pointers.

Download images fast over USB or from removable microSD

patterns, reliably measure temperature and store images

FLIR T420bx Thermal Imaging Camera, Temperature MPN: FLIRT420bx Measurement Range: -20 → +350 °C

images easier than ever, even from the toughest angles.

Display: Color LCD Touch screen, 3.5 in.

IR resolution: 320 ' 240 pixels

Thermal Sensitivity: < 0.045°C

Field of view (FOV): 25° ′ 19°

• Digital Zoom: 4X Continuous

• Temperature range: -20°C to +350°C

Battery operating time: Approx. 4 hours

. Image frequency: 60 Hz

\$FLIR

Frame Rate: 9 Hz

Spot size ratio: 24:1

Display Type: 2" TFT LCD

• Response Time: 150 ms

Measurement Resolution: 0.1°C/F

• Image Resolution: 4800 pixels (80 x 60)

Colour Palettes: 2 (Grey Scale, Hot Iron)

with Temperature and Emissivity

. Built to withstand a 2 m drop Pocket portable to fit a crowded tool bag

Saved Image Format: Bitmap (BMP) Image

• Temperature range: -25°C to +380°C, 14F to 716F



HK\$9.551.80

FLIR E4 Infrared Thermal Imaging

- FLIR E4 thermal imaging camera recognises problems instantly. Thermal images are enhanced with visible camera details such as numbers, signage, labels and other identifiable features. Reliable results are gained with FLIRs thermal accuracy (within 2% or +/- 2°C) and broad measurement range (-20°C 250°C). Stores hundreds of thermal, MSX and visible image JPEGs with all temperature data intact. Compact, rugged design and easy one-handed operation yet tough enough to stow with the rest of your tools.
- Display: 3" colour LCD
- IR resolution: 80 ' 60 pixels Field of view (FOV): 45° ′34°
- Image frequency: 9 Hz
- On-board 640 x 480 Digital Camera
- 2% accuracy
- · File format: Radiometric jpg
- . Battery operating time: Approx. 4 hours
- Simultaneous Storage of IR/Visual/MSX Images
- Variable emissivity and reflected temperature parameters for detection accuracy



848-1365 FLIR E4 Thermal Imaging Camera, Temperature Measurement Rance: -70 → +250 °C

MPN: FLIR E4

FLUKE 62 MAX and MAX+ Infrared

- Designed with your on-the-job needs in mind, the new FLUKE 62 MAX and 62 MAX+ infrared thermometers are small in size, extremely accurate and very easy to use. IP54 rated for dust and water resistance. Precise yet rugged enough to resist a 3 metre drop.
- Dust and water-resistant: IP54 rated for dust and water resistant
- Rugged: 3-meter (9.8-foot) drop tested
- Ergonomically designed: Completely redesigned for a more natural hand fit
- Small and lightweight; clips to your tool belt or
- belt loop or easily fits into your tool box
- Distance to spot: Precise laser technology makes for more accurate and repeatable measurements
- Dual lasers: The 62 MAX+ has dual rotating lasers to help you identify area to be measured. The measurement area is the spot between the dots



760-0389 FLUKE 62 MAX + IR Thermometer

MPN: FLUKE-62 MAX HK\$1,088.00

Refractometer

- · Easy and accurate dilution control
- · Simple to use and recalibrate





HK\$3,733.00

HK\$1,412,75

SFLIR

848-1331 FLIR TG165 IR Thermometer

MPN:TG165

Visit hken.rs-online.com to order today!

Visit hken.rs-online.com to order today! Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.

MPN: 0560 8690

HK\$83,734.00

· Spot Measurement mode



Thermometers

HK\$8.838.00









- Refractometer Prism Screen



RS Pro Mix Cutting Fluids Refractometer, 18% max,

Please visit the RS Website to view the latest prices for all quantities and full terms and conditions.