

The industrial sector includes various subsectors, including: Food and beverage, plastics and consumer goods, packaging, printing and papermaking, mining and aggregate, off-shore and offshore industries, transportation and automotive, chemicals and pharmaceuticals.

Common industry requirements

- Reducing downtime
- 2 Maintenance cost reduction
- 3 Energy management

Application & Solution

1 Reducing downtime:

Many test & measurement products are exposed to harsh environments, and the right choice of products may have effect on their performance and reliability.

Solution: Focus on High-Protection Sensor Products

RS operates a selection of products with IP67/69K (high-pressure washing) protection and/or stainless steel body, providing greater protection and reliability in flushing environments.

2 Maintenance cost reduction:

Having machinery fully operational in industry is paramount. The machinery's warranty often covers replacement parts over the intial lifespan, but once outside, the mix of usage of component brands across the production line creates a purchasing difficulties and additional maintenance cost.

Solution: Product Brand Consolidation

With the support of various key brands, RS can help you to consolidate the brands used within your machinery and offer advice and how machine reliability and productivity can be improved

3 Energy management:

Knowing how much electrical energy is used by different parts of your process will enable energy efficiency measures to be implemented.

Solution:Local Power Monitoring

RS has a range of kWh meters and power meters which can be easily retrofitted to provide a local indication of power usage. The range includes a variety of capabilities from simple local kWh measurement to power factor and ThD monitoring and full Ethernet remote data access.

Key technology

Sensor products

RS has a large inventory of sensors and converters for a wide range of industrial applications. RS products cover a wide range of applications including proximity, ultrasonic, photoelectric, laser, optical fiber, temperature, pressure, fluid, vision, weight, etc.



































| Sensor | | | | | | | | | | | | | | |
|------------------|-----------|------------|--------------------|---------------|-------|------------------|----------|-------------|----------|------------------------------|-------|-----------------|----------|-----------------|
| Brand | Inductive | Capacitive | Ultrasonic wave | Photoelectric | Laser | Optical fiber | Magnetic | Temperature | Pressure | Rotary and linear encoder | Fluid | Liquid level | Vision | Weight/ Mass |
| Pepperl & Fuchs | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | | |
| Sick | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | ✓ | | ✓ | ✓ | |
| Omron | ✓ | ✓ | | ✓ | ✓ | ✓ | | | | | | ✓ | ✓ | |
| Telemecanique | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | | | |
| ifm electronic | ✓ | ✓ | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | ✓ | ✓ | |
| Baumer | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | | |
| Balluff | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | ✓ | | | | |
| Druck | | | | | | | | | | | | | | |
| Gems | | | | | | | | | | | | | | |
| Cynergy3 | | | | | | | | | | | | | | |
| Kubler/Hengslter | | | | | | | | | | ✓ | | | | |
| Honeywell | | | ✓ | | | | ✓ | ✓ | ✓ | | ✓ | ✓ | | |
| VEGA | | | | | | | | | ✓ | | | ✓ | | |
| Siemens | | | | | | | | | | | ✓ | ✓ | | |
| Emerson Mobrey | | | | | | | | | | | | ✓ | | |
| Tedea Huntleigh | | | | | | | | | | | | | | ✓ |
| RS Pro | ✓ | ✓ | | ✓ | | | ✓ | ✓ | ✓ | ✓ | ✓ | | | |



| oduct picture | Category | Brand | Product description | RS inventory N |
|---------------|---------------------------------------|-----------------------------------|--|----------------|
| | | | RS PRO Thermocouple Connector, Used for K-Type Thermocouple, Connector Size: Miniature, IEC, -35°C \sim 220°C | 4559764 |
| (Apo | | | RS PRO Thermocouple Connector, Used for K-Type Thermocouple, Connector Size: Miniature, IEC, -35°C \sim 220°C | 4559758 |
| | Temperature sensor accessories | RS PRO | RS PRO Thermocouple Connector, Used for K-Type Thermocouple, Connector Size: Miniature, IEC, -35°C \sim 220°C | 3817435 |
| - | | | RS PRO Thermocouple Connector, Used for K-Type Thermocouple, Connector Size: Miniature, IEC, -35°C \sim 220°C | 4559786 |
| | | | RS PRO Thermocouple Connector, Used for K-Type Thermocouple, Connector Size: Standard, IEC, -35°C \sim 220°C | 3629991 |
| 0 | Thermocouple and extension wire | RS PRO | RS PRO Thermocouple Temperature Measuring Line, K-Type Thermocouple, Working Temperature Range: -75 → +250°C, 25 m (L), 1 Core, No Shielding | 3630389 |
| N. | | | RS PRO Thermocouple, K-Type, 1m (L) Probe, Small Plug End, Probe Diameter: 1/0.2mm, Temperature Induction: -75°C~+250°C | 3630250 |
| M | | | RS PRO Thermocouple, K-Type, Stainless Steel Probe, Cable End Type, Probe Diameter: 6mm, Temperature Induction: -50°C~350°C | 6212271 |
| | Thermocouple | RS PRO | RS PRO Thermocouple, K-Type, Cable End Type, Probe Diameter: 0.3mm, Temperature Induction: -50°C~+400°C | 6212170 |
| 20 | | | RS PRO Thermocouple, K-Type, 2m (L) Probe, Small Plug End, Probe Diameter: 1/0.2mm, Temperature Induction: -60°C~+350°C | 3630294 |
| | | | RS PRO Thermocouple, K-Type, Cable End Type, Probe Diameter: 0.6Mm, Temperature Induction: -50°C~+250°C | 6212158 |
| della | | RS PRO | RS PRO Inductive Sensor, Thread Size M12 X 1, Cylinder, Detection Range: 8 mm, Output Type: PNP-NO | 0208257 |
| ш | Dunyimity quitab | Sick Sick Telemecanique Sensors | Sick Inductive Sensor, Thread Size M12 X 1, Cylinder, Detection Range: 4 mm, Output Type: PNP-NO | 6956729 |
| | Proximity switch | | Telemecanique Sensors Inductive Sensor, Thread Size M12 X 1, Cylinder, Detection Range: 4 mm, Output Type: PNP-NO | 7033713 |
| | | | Telemecanique Sensors Inductive Sensor, Thread Size M8 X 1, Cylinder, Detection Range: 2.5 mm, Output Type: PNP-NO | 4443265 |
| | Photoelectric sensor | Omron | Omron Optical Fiber Sensor, PNP Output, Red LED, 12 → 24 V DC | 4730957 |
| 3 | Photoelectric sensor accessories | Telemecanique Sensors | Telemecanique Reflective Tape XUZB05, Used for XU Series | 3241614 |
| 40. | Photoelectric | Panasonic | Panasonic Photoelectric Sensor, EX10 Series, Block, Backward Reflection, Output Type PNP-NO, Detection Range 2 to 25 mm | 3615554 |
| 1000 | sensor | Omron | Omron Photoelectric Sensor, Fork, Straight Beam (Fork), Output Type: NPN, Detection Range: 5 mm | 2192280 |
| A. C. | Sensor, switch cables and | Telemecanique Sensors | Telemecanique Sensors Cable and Connector, M12, 4 Needles, Female, Used for Inductance Proximity Sensors | 6122235 |
| 4 | connectors | Omron | Omron cables and connectors | 2192454 |
| | | Assemtech | Assemtech Magnet, Rectangular, Proximity Switch, 30 x 7 x 20 mm | 2897812 |
| | Sensors and mag- | ZF | ZF Proximity Switch, Rectangular, Magnetic Proximity Sensor, 28.58 x 19.1 x 6.35 mm | 7659331 |
| | netic switches | | RS PRO Magnet, Rectangular, Magnetic Proximity Switch, 38 x 25 x 10 mm | 0339768 |
| | | RS PRO | RS PRO Magnet, Rectangular, Proximity Switch, 32 x 8 x 15 mm | 3614927 |
| | | RS PRO | RS PRO Sensor Tester, 18 V DC, 35 mA Rated Current, Used for Proximity Switch | 8399875 |
| | Sensor tester | | | 4139815 |



| Product picture | Category | Brand | Product description | RS inventory No. |
|-----------------|-------------------|-----------|--|------------------|
| | | | Honeywell Temperature Controller, 0 ~+150°C, Single-Pole Single Throw, NC, Rated at: 15A, Fast End, Bimetal | 0339308 |
| | | | Honeywell Temperature Controller, Single-Pole Single Throw, NC, Rated at: 10 \rightarrow 15 A, Fast End, Bimetal | 0331528 |
| | | | Honeywell Temperature Controller, 0 ~+260°C, Single-Pole Single Throw, NC, Rated at: 15A, Fast End, Bimetal | 2282529 |
| | Temperature | | Honeywell Temperature Controller, 0 ~+150°C, SPST-NO, Rated at: 10 A, Bonding Pad End, Bimetal | 2282557 |
| | controlled switch | | Honeywell Temperature Controller, SPST, Rated at: 10 A, Bonding Pad End, Bimetal | 2282658 |
| | | | Honeywell Temperature Controller, 0 ~+150°C, NC, Rated at: 10 A, Fast End, Bimetal | 0339314 |
| | | | Honeywell Temperature Controller, 0 ~+150°C, NC, Rated at: 10 A, Bonding Pad End, Bimetal | 2282636 |
| | | | Honeywell Temperature Controller, 0 ~+186°C, NC, Rated at: 10 A, Bonding Pad End, Bimetal | 2295890 |
| | | | Honeywell Temperature Controller, 0 ~+260°C, NC, Rated at: 10 A, Bonding Pad End, Bimetal | 2282541 |
| | | D0 DD0 | RS PRO, Rectangular, CO Reed Switch, 400 mA, 175V | 8110748 |
| | | RS PRO | RS PRO, Flat, CO Reed Switch, 2 A, 400V | 0339752 |
| | Reed switch | | Assemtech S1366, Rectangular, Regular On, Reed Switch, 500 mA, 240V | 2897799 |
| | | Assemtech | Assemtech MMPSA 240/100, Rectangular, Regular On, Reed Switch, 500 mA, 400V | 6138195 |



Key technology

Industrial control and relay

A large number of buttons, limit switches, control stations, isolators, contactors, and industrial relays are used in industrial line control systems and in the final product. You can find all these products in RS.









































| Industrial control | | | | | | |
|------------------------|-------------------------|--------|------------------|------------|---------------|--------------|
| Brand | Contactor/thermal relay | Button | Isolation switch | Cam switch | Motor starter | Limit switch |
| Schneider Electric | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| ABB | ✓ | ✓ | ✓ | ✓ | ✓ | |
| Siemens | ✓ | ✓ | ✓ | | ✓ | ✓ |
| Eaton | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Rockwell/Allen Bradley | ✓ | ✓ | ✓ | | ✓ | |
| Lovato | ✓ | ✓ | | | ✓ | |
| Kraus&Naimer | | | ✓ | ✓ | | |
| Honeywell | | | | | | ✓ |
| Васо | | ✓ | ✓ | | | |
| Bartec | | ✓ | ✓ | | | |
| Craig&Derricot | | ✓ | ✓ | | | |
| Socomec | | | ✓ | | | |
| RS Pro | | ✓ | | | ✓ | |

| Relay | | | | | |
|--------------------|-------------------------|-------------------|--|--|--|
| Brand | Electromechanical relay | Solid-state relay | | | |
| Crouzet | | ✓ | | | |
| Sensata / Crydom | | ✓ | | | |
| Finder | ✓ | · | | | |
| Omron | ✓ | ✓ | | | |
| RS Pro | ✓ | ✓ | | | |
| TE Connectivity | ✓ | | | | |
| Schneider Electric | ✓ | ✓ | | | |
| Phoenix Contact | ✓ | ✓ | | | |



| Product picture | Category | Brand | Product description | RS inventory No. |
|--|--|-----------------------|---|------------------|
| | | Allen Bradley | Allen Bradley Contactor, 700C Series, 24 V DC Coil, 25A, 4, Minimum Working Temperature: -25°C, 700 Series | 7768494 |
| | | Eaton | Eaton Contactor, DILEM Series, 24 V DC Coil, 9 A, 3, Minimum Working Temperature: -25°C, 3 NO Contacts | 4679341 |
| | Contactor | Lovato | Lovato Contactor, BF Series, 230 V AC Coil, 25 A, 3, Minimum Working Temperature: -50°C, Orange, 3 NO Contacts | 6851444 |
| 140000 | | Schneider Electric | Schneider Electric Contactor, LC1D Series, 220 V AC Coil, 32 A, 3 Made in China, TeSys D, 3 NO Contacts | 7430938 |
| | | Siemens | Siemens Contactor, 3RT1 Series, 24 V DC Coil, 9 A, 3, Minimum Working Temperature: -25°C, SIRIUS Classic | 2436631 |
| - | | Schneider | Schneider Electric Button, Harmony XB4 Series, Green, 22mm, Panel Mounting, NO | 3308638 |
| Carrier . | Button switch | Electric | Schneider Electric Button | 6419309 |
| | Button head | Eaton | Eaton Button Switch Head, M22 Series, 22mm Diameter, Red Button, Mushroom-Shaped | 4676134 |
| THE PARTY NAMED IN | Contact switch | BACO | BACO Contact Block, Contact Block, 1 NC, Screw End | 0260154 |
| die | module and button seat with lamp | Eaton | Eaton Button Seat with Lamp, RMQ Titan Series, Lighting Block, White, 12 → 30V AC/DC, LED, Screw End | 3993630 |
| | | | E Stop 40mm Trig Act Turn Rel Red 1NO1NC | 4258449 |
| Sh | Emergency stop button | Schneider Electric | Schneider Electric Emergency Button, Harmony XB4 Series, Section Diameter 22mm, Red, Head Diameter 40mm | 3309388 |
| Bear 125 B | Micro-switch | Crouzet | M/Sw 83137 SPCO quick-conn Wire act | 0539309 |
| | | Sensata / | Sensata/Crydom Solid State Relay, Maximum Load Current 25 A rms, Maximum Load Voltage 280 V, Virtual Value, Surface Mounting, SCR Output | 0346918 |
| | Solid-state relay | Crydom | Sensata/Crydom Solid State Relay, Maximum Load Current 40 A, Maximum Load Voltage 100 V, Surface Mounting, MOSFET Output | 2002064 |
| | Interface relay module | Finder | Finder Interface Relay Module, 38 Series, SPDT Contact, Coil Voltage 24V DC, 6A DIN Guide | 3864419 |
| C. C. C. | | Phoenix Electric | Phoenix Contact Interface Relay Module, PLC-RSC Series, SPDT Contact, Coil Voltage 24V DC, 6A | 3588301 |
| | Control relay | Broyce Control | Broyce Control Monitoring Relay, L-Series, Used for Phase and Voltage Monitoring, 280 → 520 V AC | 8505370 |
| 1 | | Finder | Finder Intermediate Relay, 34 Series, 24V DC Coil Voltage, SPDT, 6A Switching Current, PCB Mounting | 4572846 |
| The state of the s | | Finder | Finder Intermediate Relay, 55 Series, 24V DC Coil Voltage, 4PDT, 7 A Switching Current, Plug-In Mounting | 0385929 |
| | | | Omron Intermediate Relay, MY, 24V DC Coil Voltage, DPDT, 10 A Switching Current, Plug-In Mounting | 4881960 |
| No. | Intermediate relay | Omron | Omron Intermediate Relay, MY, 24V DC Coil Voltage, DPDT, 10 A Switching Current, Plug-In Mounting | 4882610 |
| die . | | Schneider Electric | Schneider Electric Intermediate Relay, 24V DC Coil Voltage, DPDT, 12 A Switching Current, Plug-In Mounting | 8841278 |
| | | TE | TE Connectivity Intermediate Relay, PT, 24V DC Coil Voltage, 4PDT, 6 A Switching Current, Plug-In Mounting | 3340020 |
| | | Connectivity | TE Connectivity Intermediate Relay, MT, 24V DC Coil Voltage, 3PDT, 10 A Switching Current, Plug-In Mounting | 2565155 |
| | | | Finder Relay Socket, 95 Series, Suitable for Various Series, 250V AC Voltage, Screw Mounting | 4009130 |
| | | Finder | Finder Relay Socket, 93 Series, Suitable for 34.81, 34.51 Series Relays, 250V AC Voltage, 5 Contacts | 6668093 |
| | | | Omron Relay Socket, Suitable for Various Series, 250V AC Voltage, 2 Contacts | 0803376 |
| | Relay socket | | Omron Relay Socket, Suitable for Various Series, 250V AC Voltage, 4 Contacts | 0403285 |
| | | Omron | Omron Relay Socket, Suitable for Various Series, 240V AC Voltage, 8 Contacts | 0329884 |
| | | 5 | Omron Relay Socket, Suitable for LY4, LY4-D, LY4F, LY4N, LY4N-D2 Series, 110V AC Voltage, 14 Contacts | 0329890 |
| | | | Omron Relay Socket, Suitable for G2R-2-S Series Relays, 250V AC Voltage | 0353966 |



Key technology

Motor and control

Many parts of the industry require motion driven by motor, which combines in panel control via a variable speed drive, soft start or DC speed controller, and the AC or DC motor on the machine.

Circuit protection

RS offers a wide range of circuit protection and circuit breakers, where you will find leading brands such as Schneider Electric, Siemens and ABB.

































| Motor-AC/DC | | | | | |
|-------------|----------|----------|--|--|--|
| Brand | DC motor | AC motor | | | |
| ABB | | ✓ | | | |
| Crouzet | ✓ | | | | |
| DOGA | | ✓ | | | |
| Maxon | ✓ | | | | |
| Panasonic | ✓ | ✓ | | | |
| Parvalux | ✓ | ✓ | | | |
| Portescap | ✓ | | | | |
| RS Pro | ✓ | | | | |
| Siemens | | ✓ | | | |
| TECO | | ✓ | | | |

| Motor control | | | | | |
|-------------------------|---------------------|---------------------|--|--|--|
| Brand | Frequency converter | DC speed controller | | | |
| ABB | · | | | | |
| Allen Bradley(Rockwell) | √ | | | | |
| Eurotherm | | ✓ | | | |
| Eaton | · | | | | |
| Mitsubishi | ✓ | | | | |
| Omron | ✓ | | | | |
| RS Pro | | ✓ | | | |
| Schneider Electric | ✓ | | | | |
| Siemens | ✓ | | | | |
| Sprint Electric | | ✓ | | | |



| Motor control | | | | | | |
|--------------------|---------------------|---------------------|--|--|--|--|
| Brand | Frequency converter | DC speed controller | | | | |
| ABB | ✓ | ✓ | | | | |
| Eaton | | ✓ | | | | |
| Schneider Electric | | ✓ | | | | |
| Siemens | | √ | | | | |
| Bussmann | ✓ | | | | | |
| RS Pro | √ | √ | | | | |

| Product picture | Category | Brand | Product description | RS inventory No |
|-----------------|----------------------------|----------------------------|---|-----------------|
| | | Crouzet | Crouzet DC Gear Motor, 24 V DC, 54 RPM Output, Brush-Type | 1784995 |
| | | Crouzet | Crouzet DC Gear Motor, 24 V DC, 13 RPM Output, Brush-Type | 1785011 |
| | | McLennan Servo Supplies | McLennan Servo Supplies DC Gear Motor, 12 V DC, 9 RPM Output | 2456118 |
| A | | | RS PRO DC Gear Motor, 24 V DC, 80 RPM Output, Brush-Type | 9013317 |
| | DC gear motor | | RS PRO DC Gear Motor, 24 V DC, 23 RPM Output, Brush-Type | 9013320 |
| 650 | | D0 DD0 | RS PRO DC Gear Motor, 24 V DC, 75 RPM Output | 2588316 |
| | | RS PRO | RS PRO DC Gear Motor, 24 V DC, 30 RPM Output | 2588344 |
| | | | RS PRO DC Gear Motor, 24 V DC, 155 RPM Output, Brush-Type | 9013314 |
| | | | RS PRO DC Gear Motor, 24 V DC, 9 RPM Output, Brush-Type | 9013323 |
| 2 | DO . | Faulhaber | Faulhaber 2232 Series DC Motor, 12 V DC, Brushless, Rated Current 1 A', Rated Power 8.8 W, 14.7 mNm | 8734818 |
| | DC motor | Maxon | Maxon 2232 DC Motor, 12 V DC, Brushless, Rated Current 2.14 A', Rated Power 30 W, 59 mNm | 4205192 |
| 1 | Servo motor | RS PRO | RS PRO 30W Servo Motor, 27 Ncm Torsion, 24 V DC, 12 Nm, 1600 rpm | 2635995 |
| | Stepping motor | McLennan Servo Supplies | McLennan Servo Supplies 1.8° Unipolar, Hybrid, Permanent Magnet Stepper Motor 23HSX-306, 8-Wire, 1.25Nm, 70V DC | 3403733 |
| | - | McLennan Servo Supplies | McLennan Servo Supplies 5:1 Gear Transmission, MRIG02 (5:1), Max Torque 1.5 Nm | 0718852 |
| 2/10 | Transmission | Trident Engineering | Trident Engineering 160:1 Oval Transmission, RG1/8.0160, 4mm Spindle Diameter | 0336258 |
| (C.) | | | Mitsubishi Inverter, FR-D720S Series, 0.2 kW, 230 V AC, IP20, 0.2 → 400Hz, 1.4 A | 7673043 |
| | Frequency con- | Mitsubishi | Mitsubishi Inverter, FR-D720S Series, 0.4 kW, 230 V AC, IP20, 0.2 → 400Hz, 2.5 A | 7673046 |
| | verter | | Siemens Inverter, MICROMASTER 440 Series, 0.75 kW, 230 V AC, IP20, 0 → 550Hz, 8.2 A | 4659987 |
| | | Siemens | Siemens Inverter, SINAMICS G110 Series, 0.75 kW, 230 V AC, IP20, 0 → 550Hz, 10 A | 5052090 |
| | EMI filter and accessories | Omron | Omron EMI Filter, 10 A, 200 V AC, 0.4 kW, 169 x 71 x 45 mm, Used for MX2 Series | 7051780 |



Key technology

Process control (PLC, HMI, Data Acquisition and Temperature Control)

PLC, HMI, data acquisition and temperature control can control almost all processes in industry - either individual standalone machines or an entire production line.

Box body and guide rail terminal

RS provides a complete range of metal and plastic boxes for electrical and industrial applications, as well as common rail terminals in boxes.



















































| PLCs, human-machine interface, i | ndustrial data exchange | | |
|----------------------------------|-------------------------|-------------------------|-----|
| Brand | PLC | Human-machine interface | IPC |
| Siemens | ✓ | ✓ | ✓ |
| Schneider Electric | ✓ | ✓ | |
| Allen Bradley/Rockwell | ✓ | ✓ | |
| Mitsubishi | ✓ | ✓ | |
| Omron | ✓ | ✓ | |
| ABB | ✓ | | ✓ |
| Phoenix Contact | | | ✓ |
| Crouzet | ✓ | ✓ | |
| Eaton | ✓ | ✓ | |
| Harting | | | ✓ |
| Insys iCom | | | ✓ |

| Temperature control | | | | | |
|---------------------|---------------------|--|--|--|--|
| Brand | Temperature control | | | | |
| ABB | ✓ | | | | |
| CAL Controls | ✓ | | | | |
| Carel | ✓ | | | | |
| Eurotherm | ✓ | | | | |
| Fuji | ✓ | | | | |
| Jumo | ✓ | | | | |
| Omron | ✓ | | | | |
| Panasonic | ✓ | | | | |
| RS Pro | ✓ | | | | |
| West Instruments | ✓ | | | | |



| Box body and guide rail terminal | | | | | |
|----------------------------------|----------|----------------|--|--|--|
| Brand | Вох | Guide terminal | | | |
| Phoenix Contact | | ✓ | | | |
| Weidmuller | | ✓ | | | |
| Wago | | ✓ | | | |
| Rose/Bopla | | ✓ | | | |
| Rittal | | | | | |
| Fibox | | | | | |
| Bartec | ✓ | ✓ | | | |
| RS Pro | ✓ | ✓ | | | |

| PLC CPU Siemens PLC CPU, Siemens PLC CPU, Simatric S7-200 Series, Used for Simatric S7-200 Series, 40 I/O Port Siemens PLC CPU, S7-1200 Series, Used for Simatric S7-1200 Series, 14I/O Port, 1 MB Memory, Ethernet Crouzet Logic module Mitsubishi Mitsubishi Iogic Module, in Series, USB, 2 Ports, Relay Output, 8x Input, 4x Output, 24Y DC, Logic Control Module Siemens Logic Module, Relay Output, 15x Input, 9x Output, 24Y DC, 124.6 x 90 x 52 mm, Logic Control Module Siemens Logic Module, Ethernet Communication Port Type, 1 Port, Relay Output, 8x Input, 4x Output PC data acquisition PC data acquisition Weidmuller Weidmuller, Used for Ethernet, Ethernet Media Converter, RS-485, RS-422, RS-232, 2 Input, Compatible with Linux, Windows Weidmuller, Used for Ethernet, Unmanaged Ethernet switch, Ethernet Brainboxes Brainboxes Adapter US-101, Used for RS232 Networks Brainboxes Industrial Interface Converter ES-522 Phoenix Contact Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 Series | 7457872 8624474 5368890 4420802 1653226 7898116 8936796 6883321 7690506 7124049 4685835 |
|--|---|
| Siemens PLC CPU, S7-1200 Series, Used for SIMATIC S7-1200 Sseries, 1141/O Port, 1 MB Memory, Ethernet | 5368890 4420802 1653226 7898116 8936796 6883321 7690506 7124049 4685835 |
| Logic module Logic module Mitsubishi Logic Module, Relay Output, 15x Input, 9x Output, 24 V DC, 124.6 x 90 x 52 mm, Logic Control Module Siemens Siemens Logic Module, Ethernet Communication Port Type, 1 Port, Relay Output, 8x Input, 4x Output PC data acquisition PC data acquisition PC data acquisition PC data acquisition accessories Brainboxes Brainboxes Adapter US-101, Used for RS232 Networks Brainboxes Industrial Interface Converter ES-522 Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | 4420802 1653226 7898116 8936796 6883321 7690506 7124049 4685835 |
| PLC, HMI and data acquisition PC data acquisition | 1653226 7898116 8936796 6883321 7690506 7124049 4685835 |
| PLC, HMI and data acquisition PC data acquisition PC data acquisition PLC, HMI and data acquisition PC data ac | 7898116 8936796 6883321 7690506 7124049 4685835 |
| PC data acquisition Weidmuller Weidmuller, Used for Ethernet, Unmanaged Ethernet switch, Ethernet PC data acquisition PC data acquisition PC data acquisition PC data acquisition accessories Brainboxes Adapter US-101, Used for RS232 Networks Brainboxes Industrial Interface Converter ES-522 Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | 8936796 6883321 7690506 7124049 4685835 |
| PLC, HMI and data acquisition PC data acquisition accessories PLC Accessories Weidmuller Weidmuller, Used for Ethernet, Unmanaged Ethernet switch, Ethernet Brainboxes Adapter US-101, Used for RS232 Networks Brainboxes Industrial Interface Converter ES-522 Phoenix Contact Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XAO, Used for 6ES Series Siemens Connector 6ES7392-1AM00-0AAO, Used for SIMATIC S7-300 | 6883321 7690506 7124049 4685835 |
| data acquisition PC data acquisition accessories PC data acquisition accessories Phoenix Contact Phoenix Contact Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | 7690506 7124049 4685835 |
| Brainboxes Industrial Interface Converter ES-522 Phoenix Contact Phoenix Contact Ethernet Switch 2891002, Used for Ethernet Network Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series PLC Accessories Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | 7124049 4685835 |
| Siemens Cable 6ES7901-3DB30-0XA0, Used for 6ES Series PLC Accessories Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | 4685835 |
| PLC Accessories Siemens Connector 6ES7392-1AM00-0AA0, Used for SIMATIC S7-300 | |
| Siemens Connector 0E5/392-IAMUU-UAAU, Used for Simalic 5/-300 | I-ESSESS |
| | 4532589 |
| IOT Development Suite Siemens Intelligent Gateway 6ES7647-0AA00-0YA2, Intel Quark x 1000 (x86 400 MHz) Chip, Arduino, Yocto Linux System | 1244037 |
| PLC I/O Module Siemens SIMATIC ET 200S Series PLC Input/Output Modules 6ES7132- 4BF00-0AA0, 8x I/O, 500 mA, 24 V DC, 81 x 15 x 52 mm | 6623592 |
| Digital Key- board, HMI Display Beijer Electronics Beijer Electronics E10 Series STN HMI Panel E1012, 160 x 32 Pixels, Digi- tal Keyboard, 3 Ports, 24 V DC | 1233857 |
| Phoenix Contact Terminal Card, E/UK Series, Terminal Clamp, ATEX, Used for NS 32 or NS 35/7.5 DIN Guide | 1012723 |
| Phoenix Contact Jump, Jump | 6879792 |
| Used for NS 32 or NS 35/7.5 DIN Guide Phoenix Contact Jump, Jump Phoenix Contact End Bracket, E/NS 35N Series, End Clamp, Used for DIN Guide Terminal | 8039481 |
| Phoenix Contact End Cover, D-UK4/10 Series, End Plate, ATEX, Used for Terminal Block | 4843687 |
| Connection row and DIN guide terminal DIN guide ter | 6273383 |
| Phoenix Contact End Cover, D-UT 2.5/10 Series, End Plate, Used for Terminal Block | 6273973 |
| Phoenix Contact Jump, FBS5-5 Series, Jump | 6879805 |
| Phoenix Contact Jump, Jump | 6879802 |
| RS PRO RS PRO Terminal, 2005.2 Series, Screw Downward Terminal | 8725637 |
| Wago Terminal, 249 Series, Terminal, Used for Terminal Block | 7960460 |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|---------------------------|---------------------------------|---------------------|---|------------------|
| | | | Weidmuller | Weidmuller Installation Leg, FM 4 Series, Installation Leg, Used for Terminal Block | 2864250 |
| | | DIN guide termi- | | Weidmuller End Bracket, EW Series, End Bracket, ATEX, Used for Terminal Block | 0425314 |
| | | nal accessories | weiamulier | Weidmuller Installation Leg, FM 5 Series, Installation Leg, Used for Terminal Block | 2864238 |
| | | | | Weidmuller End Plate, W Series, End Plate, ATEX, Used for Terminal Block | 0425291 |
| | Connection row | Grounding block | Phoenix Contact | Phoenix Contact Ground Terminal Block, Green/Yellow, 2-way, DIN Guide, Screw Tightening End Connection, 24 → 10 AWG | 4629188 |
| | and DIN guide terminal | | | Phoenix Contact Standard Din Guide Terminal, UK Series, Single Layer, 24 → 12 AWG, 24A | 7767823 |
| 29 | | | Phoenix Contact | Phoenix Contact Standard Din Guide Terminal, UK3 N Series, Single Layer, 24 → 12 AWG, 32A | 7767826 |
| 11 33 | | Fuse-free DIN guide terminal | Prideriix Contact | Phoenix Contact Feed-Through Terminal Block, UT Clipline Series, Single Layer, 26 → 12 AWG, 24A | 6273737 |
| - | | | | Phoenix Contact Standard Din Guide Terminal, UK 5 N Series, Single Layer, 24 \rightarrow 10 AWG, 32A | 1012789 |
| | | | Weidmuller | Weidmuller Feed-Through Terminal Block, WDU Series, Single Layer, 30 → 12 AWG, 32A | 0425190 |
| | | DID thormostat | CAL D thermostat | CAL 3200 Series, Multiple Temperature Ranges Optional, PID Temperature Controller 320000, 48 x 24 (1/32DIN) mm, 90 \rightarrow 264 V AC | 0730004 |
| | | | | CAL 9900 Series, Multiple Temperature Ranges Optional, PID Temperature Controller 991.12C, 48 X 48 (1/16 DIN) mm, 230 V AC, 2 Output | 0354925 |
| IIII I I I I | | | | CAL 9900 Series, Multiple Temperature Ranges Optional, PID Temperature Controller 992.22C, 48 X 48 (1/16 DIN) mm, 230 V AC, 2 Output | 0354969 |
| | | | | CAL 3300 Series, PID Temperature Controller 330000000, 48 X 24 (1/32 DIN) mm, 100 V AC, 240V DC, 2 Output | 3121784 |
| | | PID triefmostat | | CAL 9500 Series, PID Temperature Controller 95001PA000, 48 X 48 (1/16 DIN) mm, 100 V AC, 240V DC, 2 Output | 3488863 |
| 8 | | | | CAL 3300 Series, PID Temperature Controller 330000030, 12 \rightarrow 24 V AC/DC, 2 Output | 5118897 |
| | | | Carel | Carel IR33 Series, Multiple Temperature Ranges Optional, PID Temperature Controller IR33W7LR20, 76.2 x 34.2mm | 7457958 |
| | Temperature control and | and | Eurotherm | Eurotherm 2200 Series, Multiple Temperature Ranges Optional, PID Temperature Controller 2216e/CC/VH/ LH/XX/XX, 48 x 48 (1/16 DIN)mm | 2082773 |
| | process neating | eess heating | | RS PRO XXX1.25 W 25 x 50 mm Rectangular Silicone Heating Pad, Peak Temperature +300°C, 12 V DC | 0245499 |
| | | Silicone | DS DDO | RS PRO 2.5 W 50 x 50mm Rectangular Silicone Heating Pad, Peak Temperature +300°C, 12 V DC | 0245506 |
| | | heating pad | RS PRO | RS PRO 5 W 50 x 100mm Rectangular Silicone Heating Pad, Peak Temperature +300°C, 12 V | 0245528 |
| | | | | RS PRO 150 W 150 x 300mm Rectangular Silicone Heating Pad, Peak Temperature +300°C, 30V DC | 0731388 |
| | | 11 | DC DDO | RS-Pro Tube Heater, Diameter 3/8in x Length 1.5in , 200 W, 220 V AC | 8607075 |
| | | Heating tube | RS PRO | RS PRO Tube Heater, Diameter 10 mm x Length 40mm, 200 W, 220 V AC | 8606909 |
| | | Ceramic heating element | RS PRO | RS PRO Ceramic Heating Element, 245 mm (L), 1 kW, 230 V AC | 1966484 |
| | | Temperature control module | CAL | CAL CAL Series, Temperature Control Module 3C0000400 | 3121813 |



Key technology

Power management

RS Components are provided with a variety of power sources and can be used in different installation systems, which means that you will be able to find power sources for any industrial, automated or electronic applications.





































| Power management | | | | | | |
|-------------------------------|----------|--------------|------------------|--------------|------------------------------|-------------------------|
| | DC-DC | | | | AC-DC | |
| Brand | Isolated | Non-isolated | Switch regulator | Switch power | Embedded linear power supply | Desktop PC power supply |
| TRACOPOWER | ✓ | | ✓ | ✓ | | |
| XP Power | ✓ | | | ✓ | | |
| Recom | ✓ | ✓ | ✓ | ✓ | | |
| Murata Power Solutions | ✓ | ✓ | ✓ | | | |
| Mean Well | ✓ | | | ✓ | | ✓ |
| Artesyn Embedded Technologies | ✓ | ✓ | | ✓ | | |
| Cosel | ✓ | | | ✓ | | |
| TDK-Lambda | ✓ | ✓ | | ✓ | | |
| BEL POWER SOLUTIONS INC | | | ✓ | ✓ | ✓ | |
| OEP | | | | | ✓ | |
| Calex | | | | | ✓ | |
| EOS | | | | ✓ | | |
| RS PRO | | | | ✓ | ✓ | ✓ |

| Din-Rail power supply | | | | | |
|-----------------------|-----------------------|--|--|--|--|
| Brand | Din-Rail power supply | | | | |
| Omron | ✓ | | | | |
| Phoenix Contact | ✓ | | | | |
| PULS | ✓ | | | | |
| RS Pro | ✓ | | | | |
| Siemens | ✓ | | | | |
| Schneider Electric | ✓ | | | | |
| Traco | ✓ | | | | |
| ABB | ✓ | | | | |
| RS PRO | ✓ | | | | |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|-----------|---------------------------------|------------------------------------|---|--|
| | | | Chinfa | Chinfa Din-Rail Power Supply, DRA240 Series, Rated Power 240W, 10A Output | 7894013 |
| | | | | Mean Well Din-Rail Power Supply, DR Series, Rated Power 120W, 5A Output | 0282502 |
| | | | Mean Well | Mean Well Din-Rail Power Supply, DR Series, Rated Power 15W, 630mA Output, 120 \rightarrow 370 V DC, 85 \rightarrow 264 V AC | 7127408 |
| | | | | Mean Well Din-Rail Power Supply, MDR Series, Rated Power 20W, 1A Output, 120 $ ightarrow$ 370 V DC, 85 $ ightarrow$ 264 V AC | 0428433 |
| | | | | Phoenix Contact PSU, STEP-PS/1AC/24DC/1.75 Series, 1.75A Output AC, 230V AC | 0540757 |
| - | | | Phoenix Contact | Phoenix Contact PSU, QUINT-PS/1AC/24DC/20 Series, 20A Output AC, 230V AC | 0540779 |
| | | | | Phoenix Contact PSU, QUINT-PS/1AC/24DC/40 Series, 40A Output AC, 230V AC | 7080435 |
| | | | | PULS DIN Rail Power Supply, DIMENSION Q Series, Rated Power 240W, 10A Output, 85 →276 V AC, 88 → 187 V DC | 5145574 |
| | | | | PULS DIN Rail Power Supply, MiniLine MLY Series, Rated Power 36W, 1.5A Output, 85→264 V AC, 85→375 V DC | 4246272 |
| | | DIN rail and panel installation | PULS | PULS DIN Rail Power Supply, DIMENSION C-Line Series, Rated Power 120W, 5A Output, 180 →264 V AC, 88 → 132 V DC | 6276174 |
| | | power supply | 1 010 | PULS DIN Rail Power Supply, DIMENSION Q Series, Rated Power 480W, 20A Output, 85 →276 V AC, 88 → 187 V DC | 6700677 |
| | | PSU power module | | PULS DIN Rail Power Supply, MiniLine MLY Series, Rated Power 30W, 3A Output, 230V AC | 4246266 |
| | | | | PULS DIN Rail Power Supply, DIMENSION C-Line Series, Rated Power 480W, 20A Output, 230V AC | 7697424 |
| 3 | | | RS PRO | RS PRO DIN Rail Power Supply, Rated Power 70W, 3A Output, 230V AC | 1368315 |
| | | | Siemens | Siemens DIN Rail Power Supply, SITOP PSU8200 Series, Rated Power 480W, 20A Output, 120 → 230V AC | 7141287 |
| | PSU power | | TRACOPOWER | TRACOPOWER DIN Rail Power Supply, TPC Series, Rated Power 26W, 2.2A Output | 8086645 |
| | module | | | TRACOPOWER DIN Rail Power Supply, TPC Series, Rated Power 30W, 1.25A Output | 8086649 |
| | | | | Phoenix Electric | Phoenix Contact PSU, QUINT-PS/1AC/24DC/5 Series, 5A Output AC, 230V AC |
| | | | Mean Well | Mean Well Din-Rail Power Supply, MDR Series, Rated Power 10W, 2A Output, 120 $ ightarrow$ 370 V DC, 85 $ ightarrow$ 264 V AC | 7127402 |
| | | Embedded linear power supply | | OEP Closed Embedded Linear Power Supply PS2127, 207 \rightarrow 253V AC Input, \pm 15V DC Output, 500mA Output, 15W | 4949151 |
| 10 | | | OEP | OEP Closed Embedded Linear Power Supply PS2126, 207 → 253V AC Input, ±12V DC Output, 400mA Output, 9.6W | 4949145 |
| | | | | OEP Closed Embedded Linear Power Supply PS2125, 207 → 253V AC Input, 5V DC Output, 1A Output, 5W, 119 x 69 x 51.3mm | 4949139 |
| | | Laptop power supply | Mean Well | Mean Well GST60A Series 60W Desktop PC Power Supply GS- T60A12-P1J | 8808408 |
| 200 | | Power accessories | TRACOPOWER | TRACOPOWER Common Mode Choke Coil, Used for TNH 15 | 7451187 |
| | | | TDK-Lambda | TDK-Lambda Switching Power Supply, Rated Power 180W, Output Voltage 5/+15/24V DC, 4 Output, 90 → 264V AC Input | 5288227 |
| | | | Artesyn Embed- ded Technologies | Artesyn Embedded Technologies Switching Power Supply, Rated Power 40W, Output Voltage 5/±15V DC, 3 Output | 1830054 |
| | | Switch power | Mean Well | Mean Well Switching Power Supply, Rated Power 15W, Output Voltage 5V DC, Single Output | 0413673 |
| | | | 20 5 | RS PRO Switching Power Supply, Rated Power 36W, Output Voltage 12V DC, Single Output, 88 → 264V AC Input, 3A Output, 86% Efficiency | 7112614 |
| | | | RS PRO | TRACOPOWER Switching Power Supply, Rated Power 35W, Output Voltage 5/12V DC, 2 Output, 85 → 264V AC Input, 2.5 A, 4 A Output | 4666840 |
| | | Р | | TRACOPOWER Heat Sink, Used for THN15, THN15WI, THN20, THN20WI | 7451247 |
| | | Power accessories | TRACOPOWER | TRACOPOWER Heat Sink, Used for TEN15, TEN20WIN, TEN20WIR, TEN30, TEN30WIN, TEN60, TEN60WIN | 7451234 |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|--------------------|--------------------------|---|--|------------------|
| 3 = 3 = 3 | | | Murata Power Solutions | Murata Power Solutions Switch Regulator OKI-78SR Series, 5V DC Output, Rated Power 7.5W | 7962138 |
| 2 | DCDC converter | Recom | Recom Switch Regulator, 3.3V DC Output, 4.75 32V DC Input, Rated Power 2.5W | 5328044 | |
| | | | TRACOPOWER | TRACOPOWER Switch Regulator, TSR 1 Series, 5V DC Output, 6.5 → 36V DC Input, Rated Power 5W | 6664379 |
| | DC-DC converter | Isolated DC-DC converter | PULS | PULS Isolated DC-DC Converter, DIMENSION-CD Series, 18 → 32.4 V DC Input, 12V DC Output 96W, 8A Output | 6700633 |
| | | | Recom | Recom Isolated DC-DC Converter, ROE Series, 4.5 → 5.5 V DC Input, 5V DC Output 1W, 200mA Output | 7773285 |
| | | | TDACODONATED | TRACOPOWER Isolated DC-DC Converter, TEN 5 Series, 18 → 36 V DC Input, 5V DC Output 6W, 1A Output | 2932757 |
| | | TRACOPOWER | TRACOPOWER Isolated DC-DC Converter, TEN 8 Series, 18 → 36 V DC Input, 5V DC Output 8W, 1.5A Output | 4239634 | |
| | Power connector | DC power socket | Kycon | Kycon DC Power Socket KPJX Series Panel Mounting, Rated Current 7.5A, Rated Voltage 48 V DC KPJX-PM-4S, Tin-Plated Contacts | 6677287 |



Key technology

Panel instruments, counters and timers

Panel meters are at the front line to find out how your process control machinery works. In our rich product range, you will find digital instruments, VU meters and power panel meters. RS Components are equipped with a large number of counters and timers.







































| Panel instruments, counters and timers | | | | | | |
|--|------------------|---------|-------|-------------|--|--|
| Brand | Panel instrument | Counter | Timer | Power meter | | |
| ABB | ✓ | | ✓ | ✓ | | |
| Baumer(IVO) | | ✓ | | | | |
| Brodersen | | | ✓ | | | |
| Broyce Control | | | ✓ | | | |
| Crouzet | | ✓ | ✓ | | | |
| Finder | | | ✓ | ✓ | | |
| Grasslin | | | ✓ | | | |
| Hengstler | | ✓ | ✓ | | | |
| HOBUT | ✓ | | | ✓ | | |
| Kubler | ✓ | ✓ | | | | |
| Lascar | ✓ | | | | | |
| Lovato | ✓ | | | | | |
| Muller(Hugo Muller) | | | ✓ | | | |
| Omron | ✓ | ✓ | ✓ | | | |
| Phoenix Contact | | | | ✓ | | |
| RS Pro | ✓ | ✓ | ✓ | | | |
| Socomec | | | | ✓ | | |
| Schneider Electric | | | ✓ | ✓ | | |
| Siemens | | | | ✓ | | |
| Timeguard/Theben | | | ✓ | | | |



| Product picture | 大类 | 小类 | 品牌 | 产品描述 | RS inventory No |
|-----------------|--|---------------------------|---------------------------|--|-----------------|
| | | 0 1 | Hengstler | Hengstler Digital Counter, TICO 731 Series, Pulse, LCD, 8-bit, Maximum Counting Frequency 7.5 kHz | 2274815 |
| | | Counter | Omron | Omron Counter, H7EC Series, LCD, 8-bit, Maximum Counting Frequency 1kHz | 3481929 |
| | | | Brodersen Sys- tems | Brodersen Systems Time Relay, XMW-D1 Series, 10.5 → 265 V AC/DC, Multifunctional | 3080784 |
| * | | Time relay | Broyce Control | Broyce Control Time Relay, 12 → 230 V AC/DC, 7 Functions, Time Range 0.1 s→ 100 h | 8285158 |
| | | | Finder | Finder Time Relay, 80 Series, 12 → 240 V AC/DC, Multifunctional | 4460327 |
| | Timer and counter | | Hengstler | Hengstler Hour Counter, 891 Series, Counting 99999.99, Voltage Input | 0260072 |
| | Counter | Hour counter | Kubler | Kubler Hour Counter, HK 17.251 Series, Counting 99999.99, Voltage Input | 3096098 |
| A. B. | | | Kubler | Kubler Hour Counter, H 57 Series, Counting 99999.99, Voltage Input | 2971178 |
| | | | Muller | Muller Hour Counter, BW70 Series, Counting 99999, Voltage Input | 2080345 |
| | | | Muller | Muller Hour Counter, BW40 Series, Counting 99999, in 0.01H, Voltage Input | 0854346 |
| | | | Muller | Muller Hour Counter, BG 40 Series, Counting 999999, in 0.1H, Voltage Input | 0331146 |
| | | | Muller | Muller Hour Counter, BW70 Series, Counting 99999, Voltage Input | 0313974 |
| 1000 | | Timing switch accessories | Omron | Omron Socket, Used for H3CR-A, H3CR-F, H3CR-G, H3CR-H Series | 0329468 |
| 1333 | | Charact | Murata Power Solutions | Murata Power Solutions 50A Digital Shunt 3020-01096-0, 50mV Output, ±0.25 % accurate | 8103267 |
| | Panel instru- ments and components | ments and | Murata Power Solutions | Murata Power Solutions 20 A Digital Shunt 3020-01098-0, 50mV Output, ±0.25 % accurate | 8103270 |
| | | Digital panel voltmeter | Lascar | Lascar DPM 959B 3.5-bit LED DC Digital Voltmeter, 72 x 40 mm, 0°C~+50°C | 4554450 |
| | Display and industrial display | Framework for display | Murata Power Solutions | Murata Power Solutions DMS-BZL4-C seat ring, 32.51 x 46.38mm | 2975114 |



Key technology

Signal regulating and monitoring relay

Temperature, voltage, current or frequency need to be monitored at the industrial site, and all signals need to be adjusted and converted, which can be found in RS.

Speaker and signal lighthouse

Speakers and signal lights promote safety and awareness in many industrial and commercial sectors, including construction, automotive and aviation. RS Components provides international and European guaranteed products to meet the needs of most applications, including fire alarm products, stack lights or tower lights.

Machine safety protection

From the machine protection and safety scope of RS Components, the product provides protection and safety equipment for all industries, including factory automation (food, beverage and pharmaceuticals) and process automation (utilities and mining). You will also find safety devices available such as mechanical and non-contact interlock switches, light curtains, safety relays, emergency stop buttons and pull ropes.































































| Signal regulating and monitoring relay Brand | Signal regulating relay | Supervision relay |
|---|-------------------------|-------------------|
| ABB | √ | ✓ |
| Brodersen | ✓ | |
| Broyce Control | | ✓ |
| Crouzet | | ✓ |
| Dold | | · |
| MTL | ✓ | |
| Omron | | ✓ |
| Phoenix Contact | ✓ | |
| PR Electronics | ✓ | |
| RS Pro | ✓ | ✓ |
| Schneider Electric | | √ |
| Siemens | ✓ | ✓ |
| Weidmuller | ✓ | |



| Speaker and signal lighthouse | | | | | |
|-------------------------------|---------|-------------------|--|--|--|
| Brand | Speaker | Signal lighthouse | | | |
| Fulleon(Eaton) | ✓ | ✓ | | | |
| E2S | ✓ | ✓ | | | |
| Klaxon | ✓ | ✓ | | | |
| Werma | ✓ | ✓ | | | |
| Schneider Electric | | · | | | |
| Cranford Controls | ✓ | ✓ | | | |
| Moflash | ✓ | ✓ | | | |
| RS Pro | ✓ | ✓ | | | |

| Machine safety protection | | | | | | | |
|---------------------------|--------------|--------------------------------|----------------------|---------------|--|--|--|
| Brand | Safety relay | Safety carpet and blank holder | Safety light curtain | Safety switch | | | |
| ABB(Jokab) | ✓ | | | ✓ | | | |
| Allen-Bradley Guardmaster | ✓ | ✓ | ✓ | ✓ | | | |
| Honeywell | | | ✓ | ✓ | | | |
| Omron | ✓ | | ✓ | ✓ | | | |
| Phoenix Contact | ✓ | | | | | | |
| Pilz | ✓ | | | ✓ | | | |
| Schmersal | ✓ | | | ✓ | | | |
| Sick | ✓ | | ✓ | | | | |
| Siemens | ✓ | ✓ | ✓ | ✓ | | | |
| Smartscan | | | ✓ | | | | |
| Telemecanique | ✓ | | ✓ | ✓ | | | |
| Wieland Electric | ✓ | | | | | | |

| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|----------------------------|-------------------|---------------|----------|--|------------------|
| | | | | Fulleon Electronic Speaker, Askari Panel Series, 50 mm, 9 \rightarrow 28 V DC, White, 32 Tones | 0626141 |
| | | | | Fulleon Electronic Speaker, ROLP Series, 93 mm, 9 → 28 V DC, Red, 32 Tones | 5294430 |
| Secretary of the second of | | Electronic | Fulleon | Fulleon Electronic Speaker, Roshni Series, 93 mm, 9 \rightarrow 28 V DC, Red, 32 Tones | 5294424 |
| 0 | | speaker | | Fulleon Electronic Speaker, Askari Panel Series, 50 mm, 9 \rightarrow 28 V DC, 24 V AC, White, 32 Tones | 0430091 |
| | | | | Fulleon Electronic Speaker, ROLP Series, 93 mm, 110 → 230 V AC, Red, 32 Tones | 6867887 |
| | | | Klaxon | Klaxon Electronic Speaker, Nexus 110 Series, 10 → 60 V DC, Red, 50 Tones | 5394697 |
| | Speaker and | Buzzer | Moflash | Moflash Buzzer, 24 V DC, Red, Panel Mounting, 40 mm in Diameter, 75 dB 1 m away | 0245348 |
| - | signal lighthouse | Buzzer | Werma | Werma Buzzer, 24 V AC/DC AC/DC, Black, Panel Mounted, 28 mm in Diameter | 3119107 |
| | | | | Klaxon Warning Light, Flashguard Xenon Series, Red Lampshade, Maximum Temperature +40°C, 12 V DC, 24 V DC | 3095764 |
| | | | Klaxon | Klaxon Warning Light, Flashguard Xenon Series, Amber Lampshade, Maximum Temperature +40°C, 12 V DC, 24 V DC | 3095944 |
| | | Warning light | | Klaxon Warning Light, Flashguard Xenon Series, Red Lampshade, Maximum Temperature +40°C, 12 V DC, 24 V DC | 3095922 |
| | | | Moflash | Moflash Warning Light, FF 201 Series, No Lampshade (Purchased Separately), 12 V DC, 24 V DC, Surface Mounting | 2979908 |
| | | | WIOTIGSN | Moflash Warning Light, X 125 Series, No Lampshade (Purchased Separately), Maximum Temperature +55°C | 6742028 |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|-------------------------------|--------------------------------|-----------------------|---|------------------|
| | | Alarm bell | Fulleon | Fulleon FB Series Red Electromagnetic Fire Alarm Bell FB/024/R, Single Tone, 95 dB1 m away, 24 V DC | 5305940 |
| | | Siren | Klaxon | Klaxon Grey/Black Alarm SLB-0002, 230 V AC/DC, 127 dB 1 m away | 0422321 |
| | | | e2s | e2s Sound-Light Alarm, SONFL1 Series, Red Lampshade, Flashing, Surface Mounting | 6173558 |
| | Speaker and signal lighthouse | Sound-light alarm | Fulleon | eFulleon Sound-Light Alarm, Flashni Series, Red Lampshade, Maximum 101dB, Flashing, Surface Mounting | 5294474 |
| | o.g.ra. ng.m.rouss | | Werma | Werma Signal Light-Buzzer Combination, 150 Series, Red Lampshade, Static Light Effect, Panel Mounting | 4668846 |
| | | Lamp, bulb and tube | Werma | Werma Transparent BA15d Incandescent Bulb 95584035, 24V | 3147382 |
| | | Light cover | Moflash | Moflash 50064RS Amber Lenses, Used for 88, 98, 201/200, 401/400 &501/500 Series | 2869025 |
| c // | | Safety standard | Allen Bradley | Allen Bradley Guardmaster Trojan 5 440K Series Safety Interlock Switch 440K-T11090, Glass Fiber Shell, 2 NC/1 NO | 0178181 |
| | | interlock switch | Schmersal | Schmersal AZ16 Series Safety Interlock Switch AZ16ZVRK-M20, Glass Fiber Shell, 1NC/1NO | 6232988 |
| | | | ABB | ABB Safety Relay, RT7A Series, Single or Dual Channel, Beam/Curtain Wall, Safety Pad/Contact, Safety Switch/Interlocking Function | 7332373 |
| | | | ADD | ABB Safety Relay, RT7B Series, Single or Dual Channel, Beam/Curtain Wall, Safety Pad/Contact, Safety Switch/Interlocking Function | 7332360 |
| | | Safety relay | Schneider Electric | Schneider Electric Safety Relay, XPS AF Series, Single or Dual Channel, Safety Switch/Interlocking Function | 3604346 |
| | | | Pilz | Pilz Safety Relay, PNOZ X3 Series, Dual Channel, Safety Switch/Interlocking Function, 24 V AC/DC | 2451848 |
| A | | | Schmersal | Schmersal Safety Relay, SRB 301MC Series, Single or Dual Channel | 7418650 |
| i, Agi | | | ABB | ABB, Safety Switch, Adam 2TLA Series, Eden Range, Coding, Magnetic Sensor, Plastic Shell, 24 V DC | 7332430 |
| _ | | | ADD | ABB, Safety Switch, Eva 2TLA Series, Eden Range, Coding, Plastic Shell, 24 V DC | 7332458 |
| - 6000000000 | Machine Protection and Safety | Non-contact safety switch | Omron | Omron, Safety Switch, Adam F3S-TGR-N Series, Coding, Magnetic Sensor, Plastic Shell, 24 V DC, Rectangle | 7467328 |
| ****** | | | Pilz | Pilz, Safety Switch, PSENmag Range, Magnetic Sensor, Plastic Shell, 24 V DC, Square | 6192818 |
| | | | Schmersal | Schmersal, Safety Switch, Adam BNS33 Series, Coding, Magnetic Sensor, Plastic Shell, 24 V DC | 6233133 |
| 220 222 | | Emergency stop button | ABB | ABB, Emergency Button, 2TLA Series, Red, Head Diameter 32.5mm | 7332492 |
| | | | Honeywell | Honeywell GKZ52M Actuator, Oblique Angled, Used for GKM Safety Switch | 0147528 |
| | | | Omron | Omron D4DS-K2 Plastic Actuator, Oblique Angled, Used for D4NS Safety Switch | 0549514 |
| | | | Allen Bradley | Allen Bradley Guardmaster 440G-A27011 Actuator, Standard, Used for TLS-GD2 Interlock Safety Switch | 3513874 |
| The same | | Machine protection accessories | | Schmersal AZ 15/16-B1 Actuator, Standard, Used for AZ 15 Interlock Safety Switch | 6233234 |
| | | | Schmersal | Schmersal BPS 33 Actuator, Magnetic, Used for BNS 33 Safety Switch | 1987863 |
| | | | ocninersal | Schmersal AZ15/16-B2 Actuator, Small Radius B2, Used for AZ Safety Switch | 2111562 |
| | | | | Schmersal AZ 15/16-B3 Actuator, Small Radius B3, Used for AZ Safety Switch | 2111578 |



Key technology

Pneumatic and hydraulic products

From our comprehensive range of hydraulic and pneumatic products, you can find air preparation filters, hydraulic pumps, quick-connection connectors, sensors, instruments, and thoroughly clean environmental standard actuators from industrial to food grade.



























| Pneumatic | | | | |
|----------------|-------------------|----------------------|-----------------------|------------------------|
| Brand | Actuating element | Air source treatment | Pneumatic control box | Fittings and air pipes |
| SMC | ✓ | ✓ | ✓ | ✓ |
| Parker | ✓ | ✓ | ✓ | ✓ |
| Bosch Rexroth | ✓ | ✓ | ✓ | |
| Festo | ✓ | ✓ | ✓ | |
| Domnick Hunter | | ✓ | | |
| Legris(Parker) | | | | ✓ |
| Norgen | ✓ | ✓ | ✓ | ✓ |
| PCL | | | | ✓ |
| RS Pro | ✓ | ✓ | ✓ | ✓ |

| Pneumatic | | | | | | | | |
|---------------|--------------------|------|----------|-------|-----------------|-------------------|--------|---------------------|
| Brand | Hoses and fittings | Pump | Cylinder | Valve | Pressure switch | System monitoring | Filter | High voltage system |
| Parker | ✓ | | | ✓ | ✓ | ✓ | ✓ | |
| Bosch Rexroth | | ✓ | ✓ | ✓ | ✓ | | ✓ | |
| Enerpac | | | | | | | | ✓ |
| Hiforce | | | | | | | | ✓ |
| Norgren | | | | | ✓ | | | |
| RS Pro | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | |

| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|-----------------------|--|--------|---|------------------|
| | | | | Legris 3109 Series Glass Reinforced Nylon, Right Angle, Elbow Joint, 3109 08 17, R 3/8 External Thread, Push-In 8 mm Pipe Connection | 2655466 |
| | Pneumatic | | | Legris 3109 Series Glass Reinforced Nylon, Right Angle, Elbow Joint, 3109 10 13, R 1/4 External Thread, Push-In 10 mm Pipe Connection | 1825002 |
| | adapter, accessory | Pneumatic elbow thread to tube adapter | Legris | Legris 3109 Series Glass Reinforced Nylon, Right Angle, Elbow Joint, 3109 08 13, R 1/4 External Thread, Push-In 8 mm Pipe Connection | 1824986 |
| | and joint | adapto. | | Legris 3109 Series Glass Reinforced Nylon, Right Angle, Elbow Joint, 3109 10 17, R 3/8 External Thread, Push-In 10 mm Pipe Connection | 2655488 |
| | | | | Legris 3109 Series Glass Reinforced Nylon, Right Angle, Elbow Joint, 3109 06 10, R 1/8 External Thread, Push-In 6 mm Pipe Connection | 0812156 |



| t picture | Category | Subcategory | Brand | Product description | RS inventory N |
|-----------|---|---|---------------|--|----------------|
| 200 | | Pneumatic | Legris | Legris 3106 Series Glass Reinforced Nylon Tube-to-Tube Pneumatic Direct Tube - Tube Adapter 3106 06 08, 20 bar Maximum Operating Pressure | 6190878 |
| 0 | | straight pipe to tube adapter | SMC | SMC KQ2 Series Polycarbonate Tube-to-Tube Pneumatic Direct Tube - Tube Adapter KQ2H06-00A, 10 bar Maximum Operating Pressure, Push-In 6 mm | 7715071 |
| | | | Legris | Legris 3175 Series 3175 08 13 Nickel-Plated Brass Direct Pneumatic Quick Connect Coupling, 20 bar Maximum Operating Pressure, R 1/4 External Thread Connection | 1824784 |
| | | Pneumatic straight thread to tube adapter | Legns | Legris 3175 Series 3175 06 13 Nickel-Plated Brass Direct Pneumatic Quick Connect Coupling, 20 bar Maximum Operating Pressure, R 1/4 External Thread Connection | 0812279 |
| 5 | Pneumatic adapter, accessory | to tube duapter | 0140 | SMC M-5 Series M-5H-6 Brass Direct Pneumatic Quick Connect Coupling, 1.5 MPa Maximum Operating Pressure, M5 External Thread Connection | 2223817 |
| | and joint | | SMC | SMC M-5 Series M-5H-4 Brass Direct Pneumatic Quick Connect Coupling, 1.5 MPa Maximum Operating Pressure, M5 External Thread Connection | 2223801 |
| ~ | | Pneumatic quick connect coupling | RS PRO | RS PRO 17 Series Brass , Steel Pneumatic Quick Connect Coupling, 35 bar Maximum Operating Pressure, R1/4 External Thread Connection | 6671702 |
| 3 | | Pneumatic tee to tube adapter | Legris | Legris 3104 Series Pneumatic Tee - Tube Adapter 3104 06 00, Push-In 6 mm, 20 bar Maximum Operating Pressure, -20 → +80°C | 0812083 |
| | | Pneumatic posi- tive pressure and vacuum check valve functional joint | SMC | SMC AKH Series Check Valve Tube Joint AKH08-00, -100 kPa \rightarrow 1 MPa, -5 \rightarrow +60° C | 3670630 |
| | Pneumatic instrument and switch | Pressure and vacuum switch | RS PRO | RS PRO F4 Series Adjustable Pressure Switch, G 1/4 Connection, -25 → +85°C, 0 → 25bar | 2970052 |
| | | | | RS PRO NMF Series 30m Blue Nylon Air Hose, 24 bar Working Pressure, -40 →+80°C, 4mm Outer Diameter, Suitable for a Variety of Applications | 4834970 |
| | Air pipe and | Air hose | RS PRO | RS PRO HR Series 15m Blue PU Air Hose, 15 Bar Working Pressure, -5 →+60°C, 8mm Outer Diameter | 7883736 |
|) | air hose | Spiral tube with- out connector | RS PRO | RS PRO 1005T Series, 5 m (L) Transparent 20 bar Fluoropolymer Air Tube Coil (Without Connector), $-40 \rightarrow +150 ^{\circ}\text{C}$ | 4868917 |
| | | Hose cutter | Legris | Legris 3000 7100 Nylon Hose Cutter, Stainless Steel Blade, Suitable for Plastic Pipe, Suitable for Cutting Tubes with an External Diameter Up to 14 mm | 0722198 |
| | | | | WIKA 9350569 Simulated Positive Pressure Gauge Rear Entrance 10bar, R 1/8 Connection Size | 0722788 |
| e e | | | | WIKA 9626829 Simulated Positive Pressure Gauge Bottom Entrance 10bar, G 1/4 Connection Size | 0110826 |
| | | | | WIKA 9626969 Simulated Positive Pressure Gauge Bottom Entrance 400bar, G 1/4 Connection Size | 0110882 |
| 9 | | Simulated | \A11/4 | WIKA 9626977 Simulated Positive Pressure Gauge Bottom Entrance 600bar, G 1/4 Connection Size | 0110898 |
| | Pressure measuring | positive pressure gauge | WIKA | WIKA 9626951 Simulated Positive Pressure Gauge Bottom Entrance 250bar, G 1/4 Connection Size | 0110876 |
| | | | | WIKA 9626943 Simulated Positive Pressure Gauge Bottom Entrance 160bar, G 1/4 Connection Size | 0110860 |
| | | | | WIKA 46852703 Simulated Positive Pressure Gauge Rear Entrance 100bar, G 1/4 Connection Size | 0540227 |
| 1 | | | | WIKA 9314201 Simulated Positive Pressure Gauge Rear Entrance 250bar, G 1/4 Connection Size | 0540249 |
| | | Pressure gauge accessories | Parker | Parker SCJN-KIT-600 Pressure Gauge Maintenance Kit (0-600 bar), Used for Digital Pressure Gauge | 5116706 |
| 8 | Hydraulic valve and confluence plate | Hydraulic flow control valve - straight line mounting | Parker | Parker SCV Series 210 bar Nickel-plated Brass Line Fixed Hydraulic Flow Control Valve SCV1701, Maximum Flow 3L/min, G 3/8 Connection Thread | 0828050 |
| } | Hydraulic cylinder, | Gear type hydraulic pump | Bosch Rexroth | Bosch Rexroth AZP Series Hydraulic Gear Pump 0510725030, 22.5cm3 Discharge, Clockwise Rotation, 2500rpm | 5115696 |
| | pump and power plant | Manual hydraulic pump | Hi-Force | Hi-Force 1.0L Manual Single-Speed Hydraulic Hand Pump HP110, 250mm Cylinder Stroke, 560 x 145 x 135 mm | 0807889 |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|------------------------------------|---|--------|---|------------------|
| | | | | Parker Galvanized Steel Hydraulic Straight Threaded Tapered Pipe RI3/8EDX-1/4CF, G 3/8 Male to G 1/4 Female, 400 bar Maximum Operating Pressure | 0807429 |
| | | | | Parker Yellow Chromed, Galvanized Steel Hydraulic Straight Threaded Adapter 4HMK4S, G 1/4 Male to G 1/4 Male, 450 bar Maximum Operating Pressure | 0807564 |
| | | Hydraulic straight thread- ed adapter, | | Parker Yellow Chromed, Galvanized Steel Hydraulic Straight Threaded Adapter 4-6F3MK4S, 1/4 Male to R3/8 Male, 450 bar Maximum Operating Pressure | 1836210 |
| | Hydraulic adapter, accessory | counterpart joint and variable diameter joint | Parker | Parker Yellow Chromed, Galvanized Steel Hydraulic Straight Threaded Adapter 12HMK4S, G 3/4 Male to G 3/4 Male, 280 bar Maximum Operating Pressure | 0807659 |
| | and joint | | | Parker Galvanized Steel Hydraulic Straight Threaded Adapter 6HMK4S, G 3/8 Male to G 3/8 Male, 350 bar Maximum Operating Pressure | 7972078 |
| | | | | Parker Galvanized Steel Hydraulic Straight Threaded Adapter 6-6F6MK4S, G 3/8 Female to G 3/8 Male, 350 bar Maximum Operating Pressure | 7972081 |
| | | Hydraulic elbow thread adapter | | Parker G 3/8 Male to G 3/8 Female Galvanized Steel Hydraulic Elbow Thread Adapter 6C6MK4S, -40 →+120°C | 7972003 |
| | | Hydraulic quick- change connector | | Parker IA Series Steel Hydraulic Quick-Change Connector 6605-8-10, 25 MPa Maximum Operating Pressure, 1/2 in Thread (G Standard) | 4100722 |



Key technology

Industrial pipeline, pipeline and process accessories

RS can provide a variety of pipe fittings and pipeline solutions.

Bearing

RS Components stocks a wide selection of rotary bearings, ball and roller bearings, as well as roller bearings and various bearing units in leading manufacturers in the industry such as SKF and IKO NipponThompson, to cope with production line operations.

Sleeve, axle ring and coupling

RS works with industry leaders Huco and Ruland to provide a wide selection of axle rings. You'll also find keyless sleeves, locking sleeves, normal sleeves, isometric sleeves and tapered sleeves to choose from, including brands such as Lenze, Fenner Drives and our high-quality own-brand RS Pro. RS has a wide range of roller chains and accessories.

Drive accessories

RS offers a wide range of power conveyor belts to meet any automation or industrial requirements. You will find polyurethane belts, hemp chain straps, synchronous toothed belts, as well as wedge and V-shaped friction belts of top brands such as Contitech. You can also browse RS Pro brand belts with a wide selection and competitive prices. And the material transfer accessories series provided by RS will meet the requirements of any material transportation, including universal ball joints and conveyor rollers.



























































ContiTech









| Industrial pipeline, p | pipeline and pr | ocess accessor | ies | | | | | |
|------------------------|-----------------|----------------|-----------|----|---------|----------------------|-----------------|-------|
| Brand | Brass | Bronze | Ductility | NP | Plastic | Slippage accessories | Stainless steel | Steam |
| Legris | ✓ | | | ✓ | | | ✓ | |
| RS Pro | ✓ | ✓ | ✓ | | | | | |
| Saint-Gobain | | | | | ✓ | | | |
| CEJN | | | | ✓ | | | ✓ | |
| George Fischer | | | ✓ | | ✓ | | | |
| John Guest Speedfit | | | | | | ✓ | | |
| Spirax-Sarco | | | | | | | | ✓ |
| Wade | ✓ | | | | | | | |



| Bearing | | | | | | | | Ball | bearing | | | | | | | | |
|---------|-----------------------------------|-------|-----------------------|-----------|-------------------------|-----------------------|-----------|------------------------|------------------|---------------------------------------|-----------|-----------------|--------------|--------------------------------------|-----------|---------------------------|----------|
| | Deep groove ball bearing | | | | | | | Special | | Angular contact ball bearing | | | | Self- aligning ball bearing | | Thrust ball bearing | |
| Brand | | Steel | | | Stain- less steel | | | deep groove ball | Small bearing | Single | e-row | Dou- ble-row | | | | | |
| | Plastic | Open | With dust cover | With seal | Open | With dust cover | With seal | bearing | | Open | With seal | Open | With seal | Open | With seal | Plastic | Steel |
| SKF | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | ✓ | | ✓ | ✓ | ✓ | ✓ | | ✓ |
| NSK | | ✓ | ✓ | ✓ | | | | | | ✓ | | ✓ | | | | | ✓ |
| INA | | | | | | | | ✓ | | | | | ✓ | | | | |
| FAG | | | ✓ | ✓ | | | | | | ✓ | ✓ | | | ✓ | ✓ | | ✓ |
| TIMKEN | | | | | | | | | | | | | | | | | |
| IKO | | | | | | | | | | | | | | | | | |
| NMB | | | | | | | | | ✓ | | | | | | | | |
| BNL | ✓ | | | | | | | | | | | | | | | ✓ | |
| Igus | ✓ | | | | | | | | | | | | | | | | |
| RS Pro | | | ✓ | ✓ | | | ✓ | | | | | | | | | | |

| Roller be | earing | | | | |
|-----------|----------------------------|------------------------|--------------------------|------------------------|----------------|
| Brand | Cylindrical roller bearing | Tapered roller bearing | Spherical roller bearing | Needle rolling bearing | Thrust bearing |
| SKF | ✓ | ✓ | ✓ | ✓ | ✓ |
| NSK | | | | | |
| INA | ✓ | | | ✓ | |
| FAG | | ✓ | ✓ | | |
| TIMKEN | | ✓ | | | |
| IKO | | | ✓ | ✓ | |
| NMB | | | | | |
| BNL | | | | | |
| Igus | | | | | |
| RS Pro | | | | | |



| Bearing | unit | | | | | | | | | | | | | | | | Clutch | Cam | follower | Others |
|---------|---------|---------|-----------------------------------|---------|---------------------|-----------------------------------|---------|----------|-----------------------------------|---------|----------|-----------------------------------|---------|---------|-----------------------------------|----------|---------|----------|----------|---------|
| | Bea | ıring b | lock | | uble flo bolting | | Four | -bolt fl | ange | C | Cartrido | ge | Hois | ting be | earing | Bearing | Bearing | Stud | Yoke | Knuckle |
| Brand | Plastic | Steel | Cor- rosion resis- tance | Plastic | Steel | Cor- rosion resis- tance | Plastic | Steel | Cor- rosion resis- tance | Plastic | Steel | Cor- rosion resis- tance | Plastic | Steel | Cor- rosion resis- tance | plugin | | | type | bearing |
| SKF | | ✓ | | | ✓ | | | ✓ | | | | | | | | ✓ | | ✓ | ✓ | |
| NSK | | ✓ | ✓ | | ✓ | ✓ | | ✓ | ✓ | | ✓ | | | | | ✓ | | | | |
| INA | | | | | | | | ✓ | | | | | | | | ✓ | ✓ | ✓ | ✓ | |
| FAG | | | | | | | | | | | | | | | | | | | | |
| TIMKEN | | | | | | | | | | | | | | | | | | | | |
| IKO | | | | | | | | | | | | | | | | | | | | |
| NMB | | | | | | | | | | | | | | | | | | | | |
| BNL | | | | | | | | | | | | | | | | | | | | |
| lgus | ✓ | | | ✓ | | | ✓ | | | | | | | | | ✓ | | | | ✓ |
| RS Pro | | ✓ | | | ✓ | | | ✓ | | | ✓ | | | | ✓ | ✓ | | ✓ | ✓ | ✓ |

| Sleeve, axle ring o | and coupling | | | | |
|---------------------|----------------|--------------|----------------|----------------------------------|----------------|
| Brand | Locking sleeve | Shaft sleeve | Keyless sleeve | Plain sleeve and reducing sleeve | Tapered sleeve |
| Lenze | ✓ | | | | |
| TOLLOCK | ✓ | | | | |
| Huco | | ✓ | | ✓ | |
| Ruland | ✓ | | | | |
| RS Pro | | ✓ | ✓ | ✓ | ✓ |
| Fenner Drives | | | ✓ | | |
| Fibet | | | ✓ | | |



| Chain and chainwheel | | | | | | | |
|----------------------|-------|-------------|--|--|--|--|--|
| Brand | Chain | Chain wheel | | | | | |
| Renold | ✓ | | | | | | |
| INA | | ✓ | | | | | |
| RS Pro | ✓ | | | | | | |
| TYC | ✓ | | | | | | |
| Resatec | ✓ | ✓ | | | | | |
| Wippermann | ✓ | ✓ | | | | | |
| Witra | ✓ | | | | | | |

| Belt and pulley | | | | | |
|-----------------|------------------|--|---|-------------------------|--------|
| Brand | Synchronous belt | Wedge and V-shaped belt Torsion circle b | | Polyurethane round belt | Pulley |
| Contitech | ✓ | ✓ | | | |
| Fenner Drives | | ✓ | ✓ | ✓ | |
| Hutchinson | | ✓ | | | |
| RS Pro | ✓ | ✓ | | ✓ | ✓ |
| BNL | | | | | ✓ |
| INA | | | | | ✓ |

| Material transfer accessories | | | | |
|-------------------------------|-------------------------------|--|--|--|
| Brand | Material transfer accessories | | | |
| RS Pro | ✓ | | | |
| Alwayse | ✓ | | | |
| Bosch Rexroth | ✓ | | | |
| Igus | ✓ | | | |
| Hutchinson | ✓ | | | |
| BNL | ✓ | | | |
| Steerman | ✓ | | | |



| Product picture | Category | Subcategory | Brand | Product description | RS inventory No. |
|-----------------|--|---|-----------|---|------------------|
| | Power transmission - rotary bearing | Ball bearing | NMB | NMB Steel Radial Ball Bearing DDL-1060ZZMTP24LY121, 194N Static Load, 6mm Inner Diameter, 10mm Outer Diameter | 747771 |
| | Material transpor- tation - caster and wheel | Caster | LAG | LAG Caster, Wheel Diameter 150 mm, 1400 kg Load, PUR Tire, Cast Iron Hub | 2478326 |
| | Power transmis- sion-clutch and brake | Clutch-adjust- able friction type | Huco | Huco Friction Clutch 279.25.28, 8mm Aperture, 132Ncm Torque, 25.8mm Total Torque | 748617 |
| | | | | Huco Friction Clutch 271.25.28, 8mm Aperture, 53Ncm Torque, 25.8mm Total Torque | 748601 |
| 9 | | | Huco | Huco Corrugated Coupling 132Ncm Torque 10mm Aperture Electrolytic Nickel, 17mm Outer Diameter, 27mm (L), Fastening Screw, 103Nm/rad Torsional Stiffness | 748285 |
| | | 0 " | | Huco Coupling 1.8Nm Torque 10mm Aperture, 48mm (L) | 8090758 |
| (I) | | - | Ruland | Ruland Aluminum Elastic Beam Coupling PCMR19-6-6-A, 1.58Nm Torque, 19.1mm Outer Diameter, A6mm Bore B 6mm, 22.9mm (L), Clamp Fixed | 814483 |
| | Power transmis- sion-coupling | | | Ruland Coupling 0.92 Nm Torque, 12.7 mm Outer Diameter, 19.1 mm (L), 6.66° /Nm Torsional Stiffness | 814433 |
| 6 3 | | Double slider coupling torque disc | Huco | Huco 4Nm Torque Acetal Oldham Coupling Torque Disc 236.25, 13Nm Static Fracture Torque, 205Nm/rad Torsional Stiffness | 6928103 |
| | | Universal/ steering offset coupling | Huco | Huco 6mm Aperture 0.3Nm Torque Brass Universal/Transverse Offset Coupling 207.18.2222, Clamping and Fastening | 748320 |
| 000 000 | | Seal and O-ring | ng RS PRO | RS PRO Nitrile Butadiene Inch Metric O-ring, Containing 382 Pieces | 756028 |
| | | | | RS PRO Viton® Metric O-ring Suite, Containing 510 Pieces | 2459628 |
| | | | | RS PRO Viton® Inch Metric O-ring, Containing 382 Pieces | 756040 |
| | | suite | | RS PRO MBK-05V FPM Metric O-ring Suite, Containing 386 Pieces | 7058952 |
| | Power transmission - gasket, seal and | | | RS PRO Butadiene Metric O-ring Suite, Containing 385 Pieces | 7058958 |
| | | | | RS PRO Butadiene Metric O-ring Joint Suite, Containing 18 Pieces | 136601 |
| | packing | Seal and O-ring | RS PRO | RS PRO Nitrile Rubber Seals, 13.74 mm Inner Diameter, 20.57 mm Outer Diameter, 2.03 mm Thick, -10 →+80°C | 689473 |
| | | | | RS PRO Viton® O-ring suite | 2459612 |
| | | | | RS PRO Nitrile Rubber Seals, 9mm Inner Diameter, 15.5 → 17.5mm Outer Diameter, 5.5mm Thick, -40 →+100°C | 749581 |
| | | O-ring tool | RS PRO | RS PRO O-ring gauge | 7058961 |



Main technology

Sensor products

RS has a large inventory of sensors and converters for a wide range of industrial applications.

RS products cover a wide range of applications including proximity, ultrasonic, photoelectric, laser, optical fiber, temperature, pressure, fluid, vision, weight, etc.

Trusted global brands

FPEPPERL+FUCHS































Industrial control and relay

A large number of buttons, limit switches, control stations, isolators, contactors, and industrial relays are used in industrial line control systems and in the final product. You can find all these products in RS.

Many parts of the industry require mo-

tion driven by motor, which combines

in panel control via a variable speed

drive, soft start or DC speed controller,

and the AC or DC motor on the ma-

































































Circuit protection

chine.

Motor and control

RS offers a wide range of circuit protection and circuit breakers, where you will find leading brands such as Schneider Electric, Siemens and ABB.

Process control (PLC, HMI, **Data Acquisition and Tem**perature Control)

PLC, HMI, data acquisition and temperature control can control almost all processes in industry - either individual standalone machines or an entire production line.

Box body and guide rail terminal

RS provides a complete range of metal and plastic boxes for electrical and industrial applications, as well as common rail terminals in boxes.

SIEMENS





























F Fuji Electric

Innovating Energy Technology



















Main technology

Power management

RS Components are provided with a variety of power sources and can be used in different installation systems, which means that you will be able to find power sources for any industrial, automated or electronic applications.

Panel instruments, counters and timers

Panel meters are at the front line to find out how your process control machinery works. In our rich product range, you will find digital instruments, VU meters and power panel meters. RS Components are equipped with a large number of counters and timers.

Signal regulating and monitoring relay

Temperature, voltage, current or frequency need to be monitored at the industrial site, and all signals need to be adjusted and converted, which can be found in RS.

Speaker and signal lighthouse

Speakers and signal lights promote safety and awareness in many industrial and commercial sectors, including construction, automotive and aviation. RS Components provides international and European guaranteed products to meet the needs of most applications, including fire alarm products, stack lights or tower lights.

Machine safety protection

From the machine protection and safety scope of RS Components, the product provides protection and safety equipment for all industries, including factory automation (food, beverage and pharmaceuticals) and process automation (utilities and mining). You will also find safety devices available such as mechanical and non-contact interlock switches, light curtains, safety relays, emergency stop buttons and pull ropes.

Trusted global brands

OMRON PHENIX PULS SIEMENS Schneider Pleactric































































































































Main technology

Trusted global brands

Pneumatic and hydraulic products

From our comprehensive range of hydraulic and pneumatic products, you can find air preparation filters, hydraulic pumps, quick-connection connectors, sensors, instruments, and thoroughly clean environmental standard actuators from industrial to food grade.



























Industrial pipeline, pipeline and process accessories

RS can provide a variety of pipe fittings and pipeline solutions.









John Guest®







Bearing

RS Components stocks a wide selection of rotary bearings, ball and roller bearings, as well as roller bearings and various bearing units in leading manufacturers in the industry such as SKF and IKO NipponThompson, to cope with production line operations.

















Sleeve, axle ring and coupling

RS works with industry leaders Huco and Ruland to provide a wide selection of axle rings. You'll also find keyless sleeves, locking sleeves, normal sleeves, isometric sleeves and tapered sleeves to choose from, including brands such as Lenze, Fenner Drives and our high-quality own-brand RSPro. RS has a wide range of roller chains and accessories.



























ContiTech





Drive accessories

RS offers a wide range of power conveyor belts to meet any automation or industrial requirements.

You will find polyurethane belts, hemp chain straps, synchronous toothed belts, as well as wedge and V-shaped friction belts of top brands such as Contitech. You can also browse RS Pro brand belts with a wide selection and competitive prices.

And the material transfer accessories series provided by RS will meet the requirements of any material transportation, including universal ball joints and conveyor rollers.















